



US008539763B2

(12) **United States Patent**
McBride et al.

(10) **Patent No.:** **US 8,539,763 B2**
(45) **Date of Patent:** ***Sep. 24, 2013**

(54) **SYSTEMS AND METHODS FOR EFFICIENT TWO-PHASE HEAT TRANSFER IN COMPRESSED-AIR ENERGY STORAGE SYSTEMS**

(71) Applicants: **Troy O. McBride**, Norwich, VT (US);
Benjamin R. Bollinger, Topsfield, MA (US); **Jon Bessette**, Tewksbury, MA (US); **Alexander Bell**, Kensington, NH (US); **Dax Kepshire**, Newburyport, MA (US); **Arne La Ven**, Hampton, NH (US); **Adam Rauwerdink**, West Lebanon, NH (US)

(72) Inventors: **Troy O. McBride**, Norwich, VT (US);
Benjamin R. Bollinger, Topsfield, MA (US); **Jon Bessette**, Tewksbury, MA (US); **Alexander Bell**, Kensington, NH (US); **Dax Kepshire**, Newburyport, MA (US); **Arne La Ven**, Hampton, NH (US); **Adam Rauwerdink**, West Lebanon, NH (US)

(73) Assignee: **SustainX, Inc.**, Seabrook, NH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **13/755,636**

(22) Filed: **Jan. 31, 2013**

(65) **Prior Publication Data**
US 2013/0145764 A1 Jun. 13, 2013

Related U.S. Application Data

(63) Continuation of application No. 13/644,456, filed on Oct. 4, 2012, which is a continuation of application No. 13/473,128, filed on May 16, 2012.

(60) Provisional application No. 61/486,937, filed on May 17, 2011, provisional application No. 61/489,762, filed on May 25, 2011, provisional application No. 61/512,981, filed on Jul. 29, 2011, provisional application No. 61/569,528, filed on Dec. 12, 2011, provisional application No. 61/601,641, filed on Feb. 22, 2012, provisional application No. 61/620,018, filed on Apr. 4, 2012.

(51) **Int. Cl.**
F01K 3/00 (2006.01)
F15B 21/04 (2006.01)

(52) **U.S. Cl.**
USPC **60/509**; 60/512; 60/514; 91/4 A

(58) **Field of Classification Search**
USPC 60/508–515, 651, 671; 91/4 R, 4 A
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

114,297 A 5/1871 Ivens et al.
224,081 A 2/1880 Eckart

(Continued)

FOREIGN PATENT DOCUMENTS

BE 898225 3/1984
BE 1008885 8/1996

(Continued)

OTHER PUBLICATIONS

“Hydraulic Transformer Supplies Continuous High Pressure,”
Machine Design, Penton Media, vol. 64, No. 17, (Aug. 1992), 1 page.

(Continued)


Primary Examiner — Hoang Nguyen

(74) *Attorney, Agent, or Firm* — Bingham McCutchen LLP

(57) **ABSTRACT**

In various embodiments, foam is compressed to store energy and/or expanded to recover energy.

30 Claims, 50 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

233,432 A	10/1880	Pitchford	4,124,182 A	11/1978	Loeb
1,353,216 A	9/1920	Carlson	4,126,000 A	11/1978	Funk
1,635,524 A	7/1927	Aikman	4,136,432 A	1/1979	Melley, Jr.
2,141,703 A	12/1938	Bays	4,142,368 A	3/1979	Mantegani
2,280,100 A	4/1942	SinQleton	4,147,204 A	4/1979	Pfenninger
2,280,845 A	4/1942	Parker	4,149,092 A	4/1979	Cros
2,404,660 A	7/1946	Rouleau	4,150,547 A	4/1979	Hobson
2,420,098 A	5/1947	Rouleau	4,154,292 A	5/1979	Herrick
2,486,081 A	10/1949	Weenen	4,167,372 A	9/1979	Tackett
2,539,862 A	1/1951	Rushinq	4,170,878 A	10/1979	Jahniq
2,628,564 A	2/1953	Jacobs	4,173,431 A	11/1979	Smith
2,632,995 A	3/1953	Noe	4,189,925 A	2/1980	Long
2,712,728 A	7/1955	Lewis et al.	4,194,889 A	3/1980	Wanner
2,813,398 A	11/1957	Wilcox	4,195,481 A	4/1980	Gregory
2,829,501 A	4/1958	Walls	4,197,700 A	4/1980	Jahniq
2,880,759 A	4/1959	Wisman	4,197,715 A	4/1980	Fawcett et al.
3,041,842 A	7/1962	Heinecke	4,201,514 A	5/1980	Huetter
3,100,965 A	8/1963	Blackburn	4,204,126 A	5/1980	Diggs
3,236,512 A	2/1966	Caslav et al.	4,206,608 A	6/1980	Bell
3,237,523 A *	3/1966	Wallace 91/4 A	4,209,982 A	7/1980	Pitts
3,269,121 A	8/1966	Ludwig	4,220,006 A	9/1980	Kindt
3,538,340 A	11/1970	LanQ	4,229,143 A	10/1980	Pucher
3,599,425 A *	8/1971	Lewis 60/514	4,229,661 A	10/1980	Mead et al.
3,608,311 A	9/1971	Roesel, Jr.	4,232,253 A	11/1980	Mortelmans
3,648,458 A	3/1972	McAlister	4,237,692 A	12/1980	Ahrens et al.
3,650,636 A	3/1972	Eskeli	4,242,878 A	1/1981	Brinkerhoff
3,672,160 A	6/1972	Kim	4,246,978 A	1/1981	Schulz et al.
3,677,008 A	7/1972	Koutz	4,262,735 A	4/1981	Courrage
3,704,079 A	11/1972	Berlyn	4,273,514 A	6/1981	Shore et al.
3,757,517 A	9/1973	RiQollot	4,274,010 A	6/1981	Lawson-tancred
3,793,848 A	2/1974	Eskeli	4,275,310 A	6/1981	Summers et al.
3,801,793 A	4/1974	Goebel	4,281,256 A	7/1981	Ahrens
3,803,847 A	4/1974	McAlister	4,293,323 A	10/1981	Cohen
3,839,863 A	10/1974	Frazier	4,299,198 A	11/1981	Woodhull
3,847,182 A	11/1974	Greer	4,302,684 A	11/1981	Gogins
3,895,493 A	7/1975	Riqollot	4,304,103 A	12/1981	Hamrick
3,903,696 A	9/1975	Carman	4,311,011 A	1/1982	Lewis
3,935,469 A	1/1976	Haydock	4,316,096 A	2/1982	Syverson
3,939,356 A	2/1976	Loane	4,317,439 A	3/1982	Emmerlinq
3,942,323 A	3/1976	Maillet	4,335,867 A	6/1982	Bihlmaier
3,945,207 A	3/1976	Hyatt	4,340,822 A	7/1982	Gregg
3,948,049 A	4/1976	Ohms et al.	4,341,072 A	7/1982	Clyne
3,952,516 A	4/1976	Lapp	4,348,863 A	9/1982	Taylor et al.
3,952,723 A	4/1976	Browning	4,353,214 A	10/1982	Gardner
3,958,899 A	5/1976	Coleman, Jr. et al.	4,354,420 A	10/1982	Bianchetta
3,986,354 A	10/1976	Erb	4,355,956 A	10/1982	Ringrose et al.
3,988,592 A	10/1976	Porter	4,358,250 A	11/1982	Payne
3,988,897 A	11/1976	Strub	4,367,786 A	1/1983	Hafner et al.
3,990,246 A	11/1976	Wilmers	4,368,692 A	1/1983	Kita
3,991,574 A	11/1976	Frazier	4,368,775 A	1/1983	Ward
3,996,741 A	12/1976	HerberQ	4,370,559 A	1/1983	Langley, Jr.
3,998,049 A	12/1976	McKinley et al.	4,372,114 A	2/1983	Burnham
3,999,388 A	12/1976	Nystrom	4,375,387 A	3/1983	deFilippi et al.
4,008,006 A	2/1977	Bea	4,380,419 A	4/1983	Morton
4,027,993 A	6/1977	Wolff	4,392,062 A	7/1983	Bervig
4,030,303 A	6/1977	Kraus et al.	4,393,752 A	7/1983	Meier
4,031,702 A	6/1977	Burnett et al.	4,411,136 A	10/1983	Funk
4,031,704 A	6/1977	Moore et al.	4,416,114 A	11/1983	Martini
4,041,708 A	8/1977	Wolff	4,421,661 A	12/1983	Claar et al.
4,050,246 A	9/1977	Bourquardez	4,428,711 A	1/1984	Archer
4,055,950 A	11/1977	Grossman	4,435,131 A	3/1984	Ruben
4,058,979 A	11/1977	Germain	4,444,011 A	4/1984	Kolin
4,075,844 A	2/1978	Schiferli	4,446,698 A	5/1984	Benson
4,089,744 A	5/1978	Cahn	4,447,738 A	5/1984	Allison
4,094,356 A	6/1978	Ash et al.	4,449,372 A	5/1984	Rilett
4,095,118 A	6/1978	Ratbun	4,452,046 A	6/1984	Valentin
4,100,745 A	7/1978	Gyarmathy et al.	4,452,047 A	6/1984	Hunt et al.
4,104,955 A	8/1978	Murphy	4,454,429 A	6/1984	Buonome
4,108,077 A	8/1978	Laing	4,454,720 A	6/1984	Leibowitz
4,109,465 A	8/1978	Plen	4,455,834 A	6/1984	Earle
4,110,987 A	9/1978	Cahn et al.	4,462,213 A	7/1984	Lewis
4,112,311 A	9/1978	Theyse	4,474,002 A	10/1984	Perry
4,117,342 A	9/1978	Melley, Jr.	4,476,851 A	10/1984	Brugger et al.
4,117,696 A	10/1978	Fawcett et al.	4,478,553 A	10/1984	Leibowitz et al.
4,118,637 A	10/1978	Tackett	4,489,554 A	12/1984	Otters
			4,491,739 A	1/1985	Watson
			4,492,539 A	1/1985	Specht
			4,493,189 A	1/1985	Slater
			4,496,847 A	1/1985	Parkings

US 8,539,763 B2

4,498,848 A	2/1985	Petrovsky	5,387,089 A	2/1995	Stogner et al.
4,502,284 A	3/1985	Chrisoqhilos	5,394,693 A	3/1995	Plyter
4,503,673 A	3/1985	Schachle	5,427,194 A	6/1995	Miller
4,515,516 A	5/1985	Perrine et al.	5,436,508 A	7/1995	Sorensen
4,520,840 A	6/1985	Michel	5,448,889 A	9/1995	Bronicki
4,525,631 A	6/1985	Allison	5,454,408 A	10/1995	Dibella et al.
4,530,208 A	7/1985	Sato	5,454,426 A	10/1995	Moseley
4,547,209 A	10/1985	Netzer	5,467,722 A	11/1995	Meratla
4,574,592 A *	3/1986	Eskeli 62/114	5,473,899 A	12/1995	Viteri et al.
4,585,039 A	4/1986	Hamilton	5,477,677 A	12/1995	Krnavek
4,589,475 A	5/1986	Jones	5,491,969 A	2/1996	Cohn et al.
4,593,202 A	6/1986	Dickinson	5,491,977 A	2/1996	Cho
4,619,225 A	10/1986	Lowther	5,524,821 A	6/1996	Vie et al.
4,624,623 A	11/1986	Wagner	5,537,822 A	7/1996	Shnaid et al.
4,648,801 A	3/1987	Wilson	5,544,698 A	8/1996	Paulman
4,651,525 A	3/1987	Cestero	5,557,934 A	9/1996	Beach
4,653,986 A	3/1987	Ashton	5,561,978 A	10/1996	Buschur
4,671,742 A	6/1987	Gyimesi	5,562,010 A	10/1996	McGuire
4,676,068 A	6/1987	Funk	5,579,640 A	12/1996	Gray, Jr. et al.
4,679,396 A	7/1987	Heggie	5,584,664 A	12/1996	Elliott et al.
4,691,524 A	9/1987	Holscher	5,592,028 A	1/1997	Pritchard
4,693,080 A	9/1987	Van Hooff	5,595,587 A	1/1997	Steed
4,706,456 A	11/1987	Backe	5,598,736 A	2/1997	Erskine
4,707,988 A	11/1987	Palmers	5,599,172 A	2/1997	Mccabe
4,710,100 A	12/1987	Laing et al.	5,600,953 A	2/1997	Oshita et al.
4,735,552 A	4/1988	Watson	5,616,007 A	4/1997	Cohen
4,739,620 A	4/1988	Pierce	5,634,340 A	6/1997	Grennan
4,760,697 A	8/1988	Heggie	5,641,273 A	6/1997	Moseley
4,761,118 A	8/1988	Zanarini et al.	5,674,053 A	10/1997	Paul et al.
4,765,142 A	8/1988	Nakhamkin	5,685,154 A	11/1997	Bronicki et al.
4,765,143 A	8/1988	Crawford et al.	5,685,155 A	11/1997	Brown
4,767,938 A	8/1988	Bervig	5,768,893 A	6/1998	Hoshino et al.
4,792,700 A	12/1988	Ammons	5,769,610 A	6/1998	Paul et al.
4,849,648 A	7/1989	Longardner	5,771,693 A	6/1998	Coney
4,870,816 A	10/1989	Nakhamkin	5,775,107 A	7/1998	Sparkman
4,872,307 A	10/1989	Nakhamkin	5,778,675 A	7/1998	Nakhamkin
4,873,828 A	10/1989	Lainq et al.	5,794,442 A	8/1998	Lisniansky
4,873,831 A	10/1989	Dehne	5,797,980 A	8/1998	Fillet
4,876,992 A	10/1989	Sobotowski	5,819,533 A	10/1998	Moonen
4,877,530 A	10/1989	Moses	5,819,635 A	10/1998	Moonen
4,885,912 A	12/1989	Nakhamkin	5,831,757 A	11/1998	DiFrancesco
4,886,534 A	12/1989	Castan	5,832,728 A	11/1998	Buck
4,907,495 A	3/1990	Sugahara	5,832,906 A	11/1998	Douville et al.
4,936,109 A	6/1990	Longardner	5,839,270 A	11/1998	Jirnov et al.
4,942,736 A	7/1990	Bronicki	5,845,479 A	12/1998	Nakhamkin
4,947,977 A	8/1990	Raymond	5,873,250 A	2/1999	Lewis
4,955,195 A	9/1990	Jones et al.	5,901,809 A	5/1999	Berkun
4,984,432 A	1/1991	Corey	5,924,283 A	7/1999	Burke, Jr.
5,016,441 A	5/1991	Pinto	5,934,063 A	8/1999	Nakhamkin
5,056,601 A	10/1991	Grimmer	5,934,076 A	8/1999	Coney
5,058,385 A	10/1991	Everett, Jr.	5,937,652 A	8/1999	Abdelmalek
5,062,498 A	11/1991	Tobias	5,971,027 A	10/1999	Beachley et al.
5,107,681 A	4/1992	Wolfbauer, III	6,012,279 A	1/2000	Hines
5,133,190 A	7/1992	Abdelmalek	6,023,105 A	2/2000	Youssef
5,138,838 A	8/1992	Crosser	6,026,349 A	2/2000	Heneman
5,140,170 A	8/1992	Henderson	6,029,445 A	2/2000	Lech
5,152,260 A	10/1992	Erickson et al.	6,073,445 A	6/2000	Johnson
5,161,449 A	11/1992	Everett, Jr.	6,073,448 A	6/2000	Lozada
5,169,295 A	12/1992	Stoqner et al.	6,085,520 A	7/2000	Kohno
5,182,086 A	1/1993	Henderson et al.	6,090,186 A	7/2000	Spencer
5,203,168 A	4/1993	Oshina	6,119,802 A	9/2000	Puett, Jr.
5,209,063 A	5/1993	Shirai et al.	6,132,181 A	10/2000	Mccabe
5,213,470 A	5/1993	Lundquist	6,145,311 A	11/2000	Cyphelly
5,239,833 A	8/1993	Fineblum	6,148,602 A	11/2000	Demetri
5,259,345 A	11/1993	Richeson	6,153,943 A	11/2000	Mistr, Jr.
5,271,225 A	12/1993	Adamides	6,158,499 A	12/2000	Rhodes
5,279,206 A	1/1994	Krantz	6,170,443 B1	1/2001	Hofbauer
5,296,799 A	3/1994	Davis	6,178,735 B1	1/2001	Frutschi
5,309,713 A	5/1994	Vassallo	6,179,446 B1	1/2001	Sarmadi
5,321,946 A	6/1994	Abdelmalek	6,188,182 B1	2/2001	Nickols et al.
5,327,987 A	7/1994	Abdelmalek	6,202,707 B1	3/2001	Woodall et al.
5,339,633 A	8/1994	Fujii et al.	6,206,660 B1	3/2001	Coney et al.
5,341,644 A	8/1994	Nelson	6,210,131 B1	4/2001	Whitehead
5,344,627 A	9/1994	Fujii et al.	6,216,462 B1	4/2001	Gray, Jr.
5,364,611 A	11/1994	Iijima et al.	6,225,706 B1	5/2001	Keller
5,365,980 A	11/1994	Deberardinis	6,276,123 B1	8/2001	Chen et al.
5,375,417 A	12/1994	Barth	6,327,858 B1	12/2001	Negre et al.
5,379,589 A	1/1995	Cohn et al.	6,327,994 B1	12/2001	Labrador
5,384,489 A	1/1995	Bellac	6,349,543 B1	2/2002	Lisniansky

US 8,539,763 B2

RE37,603 E	3/2002	Coney	7,028,934 B2	4/2006	Burynski, Jr.
6,352,576 B1	3/2002	Spencer et al.	7,040,083 B2	5/2006	Horii et al.
6,360,535 B1	3/2002	Fisher	7,040,108 B1	5/2006	Flammang
6,367,570 B1	4/2002	Long, III	7,040,859 B2	5/2006	Kane
6,372,023 B1	4/2002	Kiyono et al.	7,043,920 B2	5/2006	Viteri et al.
6,389,814 B2	5/2002	Viteri et al.	7,047,744 B1	5/2006	Robertson et al.
6,397,578 B2	6/2002	Tsukamoto	7,055,325 B2	6/2006	Wolken
6,401,458 B2	6/2002	Jacobson	7,067,937 B2	6/2006	Enish et al.
6,407,465 B1	6/2002	Peltz et al.	7,075,189 B2	7/2006	Heronemus
6,419,462 B1	7/2002	Horie et al.	RE39,249 E	8/2006	Link, Jr.
6,422,016 B2	7/2002	Alkhamis	7,084,520 B2	8/2006	Zambrano
6,453,659 B1	9/2002	Van Liere et al.	7,086,231 B2	8/2006	Pinkerton
6,470,679 B1 *	10/2002	Ertle 60/512	7,093,450 B2	8/2006	Jimenez Haertel et al.
6,478,289 B1	11/2002	Trewin	7,093,626 B2	8/2006	Li et al.
6,484,498 B1	11/2002	Bonar, II	7,098,552 B2	8/2006	Mccoin
6,512,966 B2	1/2003	Lof	7,107,766 B2	9/2006	Zacche' et al.
6,513,326 B1	2/2003	Maceda et al.	7,107,767 B2	9/2006	Frazer et al.
6,516,615 B1	2/2003	Stockhausen et al.	7,116,006 B2	10/2006	Mccoin
6,516,616 B2	2/2003	Carver	7,124,576 B2	10/2006	Cherney et al.
6,554,088 B2	4/2003	Severinsky et al.	7,124,586 B2	10/2006	Neqre et al.
6,598,392 B2	7/2003	Majeres	7,127,887 B2	10/2006	Nakamura et al.
6,598,402 B2	7/2003	Kataoka et al.	7,127,895 B2	10/2006	Pinkerton et al.
6,606,860 B2	8/2003	McFarland	7,128,777 B2	10/2006	Spencer
6,612,348 B1	9/2003	Wiley	7,134,279 B2	11/2006	White
6,619,930 B2	9/2003	Jansen et al.	7,155,912 B2	1/2007	Enis et al.
6,626,212 B2	9/2003	Morioka et al.	7,168,928 B1	1/2007	West
6,629,413 B1	10/2003	Wendt et al.	7,168,929 B2	1/2007	Sieqel et al.
6,637,185 B2	10/2003	hatamiya et al.	7,169,489 B2	1/2007	Redmond
6,652,241 B1	11/2003	Alder	7,177,751 B2	2/2007	Froloff
6,652,243 B2	11/2003	Krasnov	7,178,337 B2	2/2007	Pflanz
6,666,024 B1	12/2003	Moskal	7,191,603 B2	3/2007	Taube
6,670,402 B1	12/2003	Lee et al.	7,197,871 B2	4/2007	Yoshino
6,672,056 B2	1/2004	Roth et al.	7,201,095 B2	4/2007	Hughey
6,675,765 B2	1/2004	Endoh	7,218,009 B2	5/2007	Hendrickson et al.
6,688,108 B1	2/2004	Van Liere	7,219,779 B2	5/2007	Bauer et al.
6,698,472 B2	3/2004	Camacho et al.	7,225,762 B2	6/2007	Mahlanen
6,711,984 B2	3/2004	Tagge et al.	7,228,690 B2	6/2007	Barker
6,712,166 B2	3/2004	Rush et al.	7,230,348 B2	6/2007	Poole
6,715,514 B2	4/2004	Parker, III	7,231,998 B1	6/2007	Schechter
6,718,761 B2	4/2004	Merswolke et al.	7,240,812 B2	7/2007	Kamikozuru
6,739,131 B1	5/2004	Kershaw	7,249,617 B2	7/2007	Musselman et al.
6,739,419 B2	5/2004	Jain et al.	7,254,944 B1	8/2007	Goetzinger et al.
6,745,569 B2	6/2004	Gerdes	7,273,122 B2	9/2007	Rose
6,745,801 B1	6/2004	Cohen et al.	7,281,371 B1	10/2007	Heidenreich
6,748,737 B2	6/2004	Lafferty	7,308,361 B2	12/2007	Enis et al.
6,762,926 B1	7/2004	Shiue et al.	7,317,261 B2	1/2008	Rolt
6,786,245 B1	9/2004	Eichelberger	7,322,377 B2	1/2008	Baltes
6,789,387 B2	9/2004	Brinkman	7,325,401 B1	2/2008	Kesseli et al.
6,789,576 B2	9/2004	Umetsu et al.	7,328,575 B2	2/2008	Hedman
6,797,039 B2	9/2004	Spencer	7,329,099 B2	2/2008	Hartman
6,815,840 B1	11/2004	Aldendeshe	7,347,049 B2	3/2008	Rajendran et al.
6,817,185 B2	11/2004	Coney et al.	7,353,786 B2	4/2008	Scuderi et al.
6,834,737 B2	12/2004	Bloxham	7,353,845 B2	4/2008	Underwood et al.
6,840,309 B2	1/2005	Wilson et al.	7,354,252 B2	4/2008	Baatrup et al.
6,848,259 B2	2/2005	Kelller-sornig	7,364,410 B2	4/2008	Link, Jr.
6,857,450 B2	2/2005	Rupp	7,392,871 B2	7/2008	Severinsky et al.
6,874,453 B2	4/2005	Coney et al.	7,406,828 B1	8/2008	Nakhmkin
6,883,775 B2	4/2005	Coney et al.	7,407,501 B2	8/2008	Zvuloni
6,886,326 B2	5/2005	Holtzapple et al.	7,415,835 B2	8/2008	Cowans et al.
6,892,802 B2	5/2005	Kelly et al.	7,415,995 B2	8/2008	Plummer et al.
6,900,556 B2	5/2005	Provanzana	7,417,331 B2	8/2008	De La Torre et al.
6,922,991 B2	8/2005	Polcuch	7,418,820 B2	9/2008	Harvey et al.
6,925,821 B2	8/2005	Sienel	7,436,086 B2	10/2008	Mcclintic
6,927,503 B2	8/2005	Enish et al.	7,441,399 B2	10/2008	Utamura
6,931,848 B2	8/2005	Maceda et al.	7,448,213 B2	11/2008	Mitani
6,935,096 B2	8/2005	Haiun	7,453,164 B2	11/2008	Borden et al.
6,938,415 B2	9/2005	Last	7,469,527 B2	12/2008	Neqre et al.
6,938,654 B2	9/2005	Gershtein et al.	7,471,010 B1	12/2008	Fingersh
6,946,017 B2	9/2005	Leppin et al.	7,481,337 B2	1/2009	Luharuka et al.
6,948,328 B2	9/2005	Kidwell	7,488,159 B2	2/2009	Bhatt et al.
6,952,058 B2	10/2005	Mccoin	7,527,483 B1	5/2009	Glauber
6,959,546 B2	11/2005	Corcoran	7,579,700 B1	8/2009	Meller
6,963,802 B2	11/2005	Enis	7,603,970 B2	10/2009	Scuderi et al.
6,964,165 B2	11/2005	Uhl et al.	7,607,503 B1	10/2009	Schechter
6,964,176 B2	11/2005	Kidwell	7,693,402 B2	4/2010	Hudson et al.
6,974,307 B2	12/2005	Antoune et al.	7,694,514 B2	4/2010	Smith et al.
7,000,389 B2	2/2006	Lewellin	7,802,426 B2	9/2010	Bollinger
7,007,474 B1	3/2006	Ochs et al.	7,827,787 B2	11/2010	Cherney et al.
7,017,690 B2	3/2006	Burke	7,832,207 B2	11/2010	McBride et al.

US 8,539,763 B2

7,843,076 B2	11/2010	Gogoana et al.	2007/0074533 A1	4/2007	Hugenroth et al.
7,874,155 B2	1/2011	McBride et al.	2007/0095069 A1	5/2007	Joshi et al.
7,900,444 B1	3/2011	McBride et al.	2007/0113803 A1	5/2007	Froloff et al.
7,958,731 B2	6/2011	McBride et al.	2007/0116572 A1	5/2007	Barbu et al.
7,963,110 B2	6/2011	McBride et al.	2007/0137595 A1	6/2007	Greenwell
8,037,678 B2	10/2011	McBride et al.	2007/0151528 A1	7/2007	Hedman
8,046,990 B2	11/2011	Bollinger et al.	2007/0158946 A1	7/2007	Annen et al.
8,104,274 B2	1/2012	McBride et al.	2007/0181199 A1	8/2007	Weber
8,109,085 B2	2/2012	McBride et al.	2007/0182160 A1	8/2007	Enis et al.
8,117,842 B2	2/2012	McBride et al.	2007/0205298 A1	9/2007	Harrison et al.
8,122,718 B2	2/2012	McBride et al.	2007/0234749 A1	10/2007	Enis et al.
8,171,728 B2	5/2012	Bollinger et al.	2007/0243066 A1	10/2007	Baron
8,191,362 B2	6/2012	McBride et al.	2007/0245735 A1	10/2007	Ashikian
8,225,606 B2	7/2012	McBride et al.	2007/0258834 A1	11/2007	Froloff et al.
8,234,862 B2	8/2012	McBride et al.	2008/0000436 A1	1/2008	Goldman
8,234,863 B2	8/2012	McBride et al.	2008/0016868 A1	1/2008	Ochs et al.
8,234,868 B2	8/2012	Bollinger et al.	2008/0047272 A1	2/2008	Schoell
8,240,140 B2	8/2012	McBride et al.	2008/0050234 A1	2/2008	Ingersoll et al.
8,240,146 B1	8/2012	Bollinger	2008/0072870 A1	3/2008	Chomyszak et al.
8,245,508 B2	8/2012	Bollinger et al.	2008/0087165 A1	4/2008	Wright et al.
8,250,863 B2	8/2012	Bollinger et al.	2008/0104939 A1	5/2008	Hoffmann et al.
8,272,212 B2	9/2012	Blieske	2008/0112807 A1	5/2008	Uphues et al.
8,359,856 B2	1/2013	McBride et al.	2008/0127632 A1	6/2008	Finkenrath et al.
8,448,433 B2	5/2013	McBride et al.	2008/0138265 A1	6/2008	Lackner et al.
2001/0045093 A1	11/2001	Jacobson	2008/0155975 A1	7/2008	Brinkman
2003/0131599 A1	7/2003	Gerdes	2008/0155976 A1	7/2008	Smith et al.
2003/0145589 A1	8/2003	Tillyer	2008/0157528 A1	7/2008	Wang et al.
2003/0177767 A1	9/2003	Keller-sornig et al.	2008/0157537 A1	7/2008	Richard
2003/0180155 A1	9/2003	Coney et al.	2008/0164449 A1	7/2008	Gray et al.
2004/0050042 A1	3/2004	Frazer	2008/0185194 A1	8/2008	Leone
2004/0050049 A1	3/2004	Wendt et al.	2008/0202120 A1	8/2008	Karyambas
2004/0146406 A1	7/2004	Last	2008/0211230 A1	9/2008	Gurin
2004/0146408 A1	7/2004	Anderson	2008/0228323 A1	9/2008	Laumer et al.
2004/0148934 A1	8/2004	Pinkerton et al.	2008/0233029 A1	9/2008	Fan et al.
2004/0211182 A1	10/2004	Gould	2008/0238105 A1	10/2008	Ortiz et al.
2004/0244580 A1	12/2004	Coney et al.	2008/0238187 A1	10/2008	Garnett et al.
2004/0261415 A1	12/2004	Negre et al.	2008/0250788 A1	10/2008	Nuel et al.
2005/0016165 A1	1/2005	Enis et al.	2008/0251302 A1	10/2008	Lynn et al.
2005/0028529 A1	2/2005	Bartlett et al.	2008/0272597 A1	11/2008	Althaus
2005/0047930 A1	3/2005	Schmid	2008/0272598 A1	11/2008	Nakhamkin
2005/0072154 A1	4/2005	Frutschi	2008/0272605 A1	11/2008	Borden et al.
2005/0115234 A1	6/2005	Asano et al.	2008/0308168 A1	12/2008	O'Brien, II et al.
2005/0155347 A1	7/2005	Lewellin	2008/0308270 A1	12/2008	Wilson
2005/0166592 A1	8/2005	Larson et al.	2008/0315589 A1	12/2008	Malmrup
2005/0274334 A1	12/2005	Warren	2009/0000290 A1	1/2009	Brinkman
2005/0275225 A1	12/2005	Bertolotti	2009/0007558 A1	1/2009	Hall et al.
2005/0279086 A1	12/2005	Hoos	2009/0010772 A1	1/2009	Siemroth
2005/0279292 A1	12/2005	Hudson et al.	2009/0021012 A1	1/2009	Stull et al.
2005/0279296 A1	12/2005	Coney et al.	2009/0056331 A1	3/2009	Zhao et al.
2006/0055175 A1	3/2006	Grinblat	2009/0071153 A1	3/2009	Boyapati et al.
2006/0059912 A1	3/2006	Romanelli et al.	2009/0107784 A1	4/2009	Gabriel et al.
2006/0059936 A1	3/2006	Radke et al.	2009/0145130 A1	6/2009	Kaufman
2006/0059937 A1	3/2006	Perkins et al.	2009/0158740 A1	6/2009	Littau et al.
2006/0075749 A1	4/2006	Cherney et al.	2009/0178409 A1	7/2009	Shinnar
2006/0090467 A1	5/2006	Crow	2009/0200805 A1	8/2009	Kim et al.
2006/0090477 A1	5/2006	Rolff	2009/0220364 A1	9/2009	Rigal et al.
2006/0107664 A1	5/2006	Hudson et al.	2009/0229902 A1	9/2009	Stansbury, III
2006/0123778 A1*	6/2006	Huynh 60/508	2009/0249826 A1	10/2009	Hugelman
2006/0162543 A1	7/2006	Abe et al.	2009/0282822 A1	11/2009	McBride et al.
2006/0162910 A1	7/2006	Kelly et al.	2009/0282840 A1	11/2009	Chen et al.
2006/0175337 A1	8/2006	Defosset	2009/0294096 A1	12/2009	Mills et al.
2006/0201148 A1	9/2006	Zabtcioglu	2009/0301089 A1	12/2009	Bollinger
2006/0218924 A1	10/2006	Mitani	2009/0317267 A1	12/2009	Gill et al.
2006/0248886 A1	11/2006	Ma	2009/0322090 A1	12/2009	Wolf
2006/0248892 A1	11/2006	Ingersoll	2010/0018196 A1	1/2010	Li et al.
2006/0254281 A1	11/2006	Badeer et al.	2010/0077765 A1	4/2010	Japikse
2006/0260311 A1	11/2006	Ingersoll	2010/0089063 A1	4/2010	McBride et al.
2006/0260312 A1	11/2006	Ingersoll	2010/0133903 A1	6/2010	Rufer
2006/0262465 A1	11/2006	Wiederhold	2010/0139277 A1	6/2010	McBride et al.
2006/0266034 A1	11/2006	Ingersoll	2010/0193270 A1	8/2010	Deshaies et al.
2006/0266035 A1	11/2006	Ingersoll et al.	2010/0199652 A1	8/2010	Lemofouet et al.
2006/0266036 A1	11/2006	Ingersoll	2010/0205960 A1	8/2010	McBride et al.
2006/0266037 A1	11/2006	Ingersoll	2010/0229544 A1	9/2010	Bollinger et al.
2006/0280993 A1	12/2006	Keefe et al.	2010/0257862 A1	10/2010	Howes et al.
2006/0283967 A1	12/2006	Cho et al.	2010/0307156 A1	12/2010	Bollinger
2007/0006586 A1	1/2007	Hoffman et al.	2010/0326062 A1	12/2010	Fong et al.
2007/0022754 A1	2/2007	Perkins et al.	2010/0326064 A1	12/2010	Fong et al.
2007/0022755 A1	2/2007	Pinkerton et al.	2010/0326066 A1	12/2010	Fong et al.
2007/0062194 A1	3/2007	Ingersoll	2010/0326068 A1	12/2010	Fong et al.

2010/0326069	A1	12/2010	Fong et al.	2013/0074941	A1	3/2013	McBride et al.
2010/0326075	A1	12/2010	Fong et al.	2013/0074949	A1	3/2013	McBride et al.
2010/0329891	A1	12/2010	Fong et al.	2013/0091834	A1	4/2013	McBride et al.
2010/0329903	A1	12/2010	Fong et al.	2013/0091835	A1	4/2013	McBride et al.
2010/0329909	A1	12/2010	Fong et al.	2013/0091836	A1	4/2013	McBride et al.
2011/0023488	A1	2/2011	Fong et al.	2013/0098027	A1	4/2013	Le Roux et al.
2011/0023977	A1	2/2011	Fong et al.	2013/0104533	A1	5/2013	Fong et al.
2011/0030359	A1	2/2011	Fong et al.	2013/0108480	A1	5/2013	Fong et al.
2011/0030552	A1	2/2011	Fong et al.	2013/0111895	A1	5/2013	Fong et al.
2011/0056193	A1	3/2011	McBride et al.	2013/0126014	A1	5/2013	Fong et al.
2011/0056368	A1	3/2011	McBride et al.				
2011/0061741	A1	3/2011	Ingersoll et al.				
2011/0061836	A1	3/2011	Ingersoll et al.				
2011/0062166	A1	3/2011	Ingersoll et al.				
2011/0106321	A1	5/2011	Cherian et al.				
2011/0107755	A1	5/2011	McBride et al.				
2011/0115223	A1	5/2011	Stahlkopf et al.				
2011/0131966	A1	6/2011	McBride et al.				
2011/0138797	A1	6/2011	Bollinger et al.				
2011/0167813	A1	7/2011	McBride et al.				
2011/0204064	A1	8/2011	Crane et al.				
2011/0219760	A1	9/2011	McBride et al.				
2011/0219763	A1	9/2011	McBride et al.				
2011/0232281	A1	9/2011	McBride et al.				
2011/0233934	A1	9/2011	Crane et al.				
2011/0252777	A1	10/2011	Bollinger et al.				
2011/0258996	A1	10/2011	Ingersoll et al.				
2011/0258999	A1	10/2011	Ingersoll et al.				
2011/0259001	A1	10/2011	McBride et al.				
2011/0259442	A1	10/2011	McBride et al.				
2011/0266810	A1	11/2011	McBride et al.				
2011/0283690	A1	11/2011	McBride et al.				
2011/0296822	A1	12/2011	Bollinger et al.				
2011/0296823	A1	12/2011	McBride et al.				
2011/0314800	A1	12/2011	Fong et al.				
2011/0314804	A1	12/2011	Fong et al.				
2011/0314810	A1	12/2011	McBride et al.				
2012/0000557	A1	1/2012	McBride et al.				
2012/0006013	A1	1/2012	McBride et al.				
2012/0017580	A1	1/2012	Fong et al.				
2012/0019009	A1	1/2012	Fong et al.				
2012/0023919	A1	2/2012	Fong et al.				
2012/0036851	A1	2/2012	McBride et al.				
2012/0042772	A1	2/2012	Fong et al.				
2012/0047884	A1	3/2012	McBride et al.				
2012/0057996	A1	3/2012	Fong et al.				
2012/0057998	A1	3/2012	Ingersoll et al.				
2012/0067036	A1	3/2012	Fong et al.				
2012/0073432	A1	3/2012	Ingersoll et al.				
2012/0085086	A1	4/2012	Bollinger et al.				
2012/0090314	A1	4/2012	Fong et al.				
2012/0096845	A1	4/2012	Ingersoll et al.				
2012/0102935	A1	5/2012	Ingersoll et al.				
2012/0102954	A1	5/2012	Ingersoll et al.				
2012/0118137	A1	5/2012	Fong et al.				
2012/0119513	A1	5/2012	McBride et al.				
2012/0119514	A1	5/2012	Crane et al.				
2012/0137668	A1	6/2012	McBride et al.				
2012/0174569	A1	7/2012	Ingersoll et al.				
2012/0197683	A1	8/2012	Marcus				
2012/0210705	A1	8/2012	McBride et al.				
2012/0222424	A1	9/2012	Ingersoll et al.				
2012/0255292	A1	10/2012	Fong et al.				
2012/0260645	A1	10/2012	Fong et al.				
2012/0269651	A1	10/2012	Fong et al.				
2012/0279209	A1	11/2012	McBride et al.				
2012/0285154	A1	11/2012	Bollinger et al.				
2012/0286522	A1	11/2012	Stahlkopf et al.				
2012/0291989	A1	11/2012	Fong et al.				
2012/0297772	A1	11/2012	McBride et al.				
2012/0297776	A1	11/2012	Bollinger et al.				
2012/0299310	A1	11/2012	McBride et al.				
2013/0001958	A1	1/2013	Crane et al.				
2013/0009408	A1	1/2013	Crane et al.				
2013/0032743	A1	2/2013	Fong et al.				
2013/0047597	A1	2/2013	Fong et al.				
2013/0074485	A1	3/2013	McBride et al.				
2013/0074488	A1	3/2013	McBride et al.				
2013/0074940	A1	3/2013	McBride et al.				

FOREIGN PATENT DOCUMENTS

CN	1061262	5/1992
CN	1171490	1/1998
CN	1276308	12/2000
CN	1277323	12/2000
CN	1412443	4/2003
CN	1743665	3/2006
CN	2821162	9/2006
CN	2828319	10/2006
CN	2828368	10/2006
CN	1884822	12/2006
CN	1888328	1/2007
CN	1967091	5/2007
CN	101033731	9/2007
CN	101042115	9/2007
CN	101070822	11/2007
CN	101149002	3/2008
CN	101162073	4/2008
CN	201103518	8/2008
CN	201106527	8/2008
CN	101289963	10/2008
CN	201125855	10/2008
CN	101377190	4/2009
CN	101408213	4/2009
CN	101435451	5/2009
DE	25 38 870	4/1976
DE	19530253	11/1996
DE	19903907	8/2000
DE	19911534	9/2000
DE	10042020	5/2001
DE	20118183	3/2003
DE	20120330	4/2003
DE	10147940	5/2003
DE	10205733	8/2003
DE	10212480	10/2003
DE	20312293	12/2003
DE	10220499	4/2004
DE	10334637	2/2005
DE	10 2005 047622	4/2007
EP	0204748	3/1981
EP	0091801	10/1983
EP	0097002	12/1983
EP	0196690	10/1986
EP	0212692	3/1987
EP	0364106	4/1990
EP	0507395	10/1992
EP	0821162	1/1998
EP	0 857 877	8/1998
EP	1 388 442	2/2004
EP	1405662	4/2004
EP	1657452	11/2004
EP	1726350	11/2006
EP	1741899	1/2007
EP	1 780 058	5/2007
EP	1988294	11/2008
EP	2014896	1/2009
EP	2078857	7/2009
FR	2449805	9/1980
FR	2816993	5/2002
FR	2829805	3/2003
GB	722524	11/1951
GB	772703	4/1957
GB	1449076	9/1976
GB	1479940	7/1977
GB	2106992	4/1983
GB	2223810	4/1990
GB	2 300 673	11/1996
GB	2373546	9/2002

GB	2403356	12/2004	WO	WO-2005/095155	10/2005
JP	57010778	1/1982	WO	WO-2006/029633	3/2006
JP	57070970	5/1982	WO	WO-2006/058085	6/2006
JP	57120058	7/1982	WO	WO-2006/124006	11/2006
JP	58183880	10/1982	WO	WO-2007/002094	1/2007
JP	58150079	9/1983	WO	WO-2007/003954	1/2007
JP	58192976	11/1983	WO	WO-2007/012143	2/2007
JP	60206985	10/1985	WO	WO-2007/035997	4/2007
JP	62101900	5/1987	WO	WO-2007/051034	5/2007
JP	63227973	9/1988	WO	WO-2007/066117	6/2007
JP	2075674	3/1990	WO	WO-2007/086792	8/2007
JP	2247469	10/1990	WO	WO-2007/089872	8/2007
JP	3009090	1/1991	WO	WO-2007/096656	8/2007
JP	3281984	12/1991	WO	WO-2007/111839	10/2007
JP	4121424	4/1992	WO	WO-2007/136765	11/2007
JP	6185450	7/1994	WO	WO-2007/140914	12/2007
JP	8145488	6/1996	WO	WO-2008/003950	1/2008
JP	9166079	6/1997	WO	WO-2008/014769	2/2008
JP	10313547	11/1998	WO	WO-2008023901	2/2008
JP	2000-346093	6/1999	WO	WO-2008/027259	3/2008
JP	11351125	12/1999	WO	WO-2008/028881	3/2008
JP	2000166128	6/2000	WO	WO-2008/039725	4/2008
JP	2000346093	12/2000	WO	WO-2008/045468	4/2008
JP	2002127902	5/2002	WO	WO-2009045468	4/2008
JP	2003083230	3/2003	WO	WO-2008/051427	5/2008
JP	2005023918	1/2005	WO	WO-2008/074075	6/2008
JP	2005036769	2/2005	WO	WO-2008/084507	7/2008
JP	2005068963	3/2005	WO	WO-2008/091373	7/2008
JP	2006220252	8/2006	WO	WO 2008102292	8/2008
JP	2007001872	1/2007	WO	WO-2008/106967	9/2008
JP	2007145251	6/2007	WO	WO-2008/108870	9/2008
JP	2007211730	8/2007	WO	WO-2008/109006	9/2008
JP	2008038658	2/2008	WO	WO-2008/110018	9/2008
KR	840000180	2/1984	WO	WO-2008/115479	9/2008
KR	2004004637	1/2004	WO	WO-2008/121378	10/2008
RU	2101562	1/1998	WO	WO-2008139267	11/2008
RU	2169857	6/2001	WO	WO-2008/152432	12/2008
RU	2213255	9/2003	WO	WO-2008/153591	12/2008
SU	800438	1/1981	WO	WO-2008/157327	12/2008
UA	69030	8/2004	WO	WO-2009/034548	3/2009
WO	WO-82/00319	2/1982	WO	WO-2009/038973	3/2009
WO	WO-8802818	4/1988	WO	WO-2009034421	3/2009
WO	WO-99/41498	8/1990	WO	WO-2009/045110	4/2009
WO	WO-92/22741	12/1992	WO	WO-2009044139	4/2009
WO	WO-93/06367	4/1993	WO	WO-2009/114205	9/2009
WO	WO-93/11363	6/1993	WO	WO-2009/126784	10/2009
WO	WO-93/24754	12/1993	WO	WO-2010/006319	1/2010
WO	WO 9412785	6/1994	WO	WO-2010/009053	1/2010
WO	WO-95/25381	9/1995	WO	WO-2010/040890	4/2010
WO	WO-96/01942	1/1996	WO	WO-2010/105155	9/2010
WO	WO-96/22456	7/1996	WO	WO-2010/135658	11/2010
WO	WO-96/34213	10/1996	WO	WO-2011/008321	1/2011
WO	WO-97/01029	1/1997	WO	WO-2011/008325	1/2011
WO	WO-97/17546	5/1997	WO	WO-2011/008500	1/2011
WO	WO-98/02818	1/1998	WO	WO-2011/079267	6/2011
WO	WO-98/17492	4/1998	WO	WO-2011/079271	6/2011
WO	WO-00/01945	1/2000			
WO	WO-00/37800	6/2000			
WO	WO-00/65212	11/2000			
WO	WO-00/68578	11/2000			
WO	WO-01/75308	10/2001			
WO	WO 0175290	10/2001			
WO	WO-02/25083	3/2002			
WO	WO-02/46621	6/2002			
WO	WO-02/103200	12/2002			
WO	WO-03/021107	3/2003			
WO	WO-03021702	3/2003			
WO	WO-03/078812	9/2003			
WO	WO-03081011	10/2003			
WO	WO-2004/037391	5/2004			
WO	WO-2004/059155	7/2004			
WO	WO-2004/072452	8/2004			
WO	WO-2004/074679	9/2004			
WO	WO-2004/109172	12/2004			
WO	WO-2005/044424	5/2005			
WO	WO-2005/062969	7/2005			
WO	WO-2005/067373	7/2005			
WO	WO-2005/079461	9/2005			
WO	WO-2005/088131	9/2005			

OTHER PUBLICATIONS

Lemofouet, "Investigation and Optimisation of Hybrid Electricity Storage Systems Based on Compressed Air and Supercapacitors," (Oct. 20, 2006), 250 pages.

Cyphelly et al., "Usage of Compressed Air Storage Systems," BFE-Program "Electricity," Final Report, May 2004, 14 pages.

Lemofouet et al., "A Hybrid Energy Storage System Based on Compressed Air and Supercapacitors with Maximum Efficiency Point Tracking (MEPT)," IEEE Transactions on Industrial Electron, vol. 53, No. 4, (Aug. 2006) pp. 1105-1115.

International Search Report and Written Opinion issued Sep. 15, 2009 for International Application No. PCT/US2009/040027, 8 pages.

International Search Report and Written Opinion issued Aug. 30, 2010 for International Application No. PCT/US2010/029795, 9 pages.

International Search Report and Written Opinion issued Dec. 3, 2009 for International Application No. PCT/US2009/046725, 9 pages.

International Search Report and Written Opinion issued Jan. 4, 2011 for International Application No. PCT/US2010/055279, 13 pages.

International Search Report and Written Opinion mailed May 25, 2011 for International Application No. PCT/US2010/027138, 12 pages.

Rufer et al., "Energetic Performance of a Hybrid Energy Storage System Based on Compressed Air and Super Capacitors," *Power Electronics, Electrical Drives, Automation and Motion*, (May 1, 2006), pp. 469-474.

Lemofouet et al. "Hybrid Energy Storage Systems based on Compressed Air and Supercapacitors with Maximum Efficiency Point Tracking," *Industrial Electronics Laboratory (LEI)*, (2005), pp. 1-10.

Lemofouet et al. "Hybrid Energy Storage Systems based on Compressed Air and Supercapacitors with Maximum Efficiency Point Tracking," *The International Power Electronics Conference*, (2005), pp. 461-468.

International Preliminary Report on Patentability mailed Oct. 13, 2011 for International Application No. PCT/US2010/029795 (9 pages).

Stephenson et al., "Computer Modelling of Isothermal Compression in the Reciprocating Compressor of a Complete Isoengine," 9th International Conference on Liquid Atomization and Spray Systems (Jul. 13-17, 2003).

Coney et al., "Development of a Reciprocating Compressor Using Water Injection to Achieve Quasi-Isothermal Compression," *Purdue University International Compressor Engineering Conference* (2002).

Linnemann et al., "The Isoengine—A Novel High Efficiency Engine with Optional Compressed Air Energy Storage (CAES)," *International Joint Power Generation Conference* (Jun. 16-19, 2003).

Linnemann et al., "The Isoengine: Realisation of a High-Efficiency Power Cycle Based on Isothermal Compression," *Int. J. Energy Tech. and Policy*, vol. 3, Nos. 1-2, pp. 66-84 (2005).

Winterburn et al., "Mechanisms of Ultrasound Foam Interactions," *Asia-Pac. J. Chem. Eng.*, vol. 4, pp. 184-190 (2009).

* cited by examiner

FIG. 1

100




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

800




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 21




FIG. 22




FIG. 23




FIG. 25

2500




FIG. 26




FIG. 27





FIG. 28






FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34

3400




FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39

3900




FIG. 40




FIG. 41




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48





FIG. 49



**SYSTEMS AND METHODS FOR EFFICIENT
TWO-PHASE HEAT TRANSFER IN
COMPRESSED-AIR ENERGY STORAGE
SYSTEMS**

RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/644,456, filed Oct. 4, 2012, which is a continuation of U.S. patent application Ser. No. 13/473,128, filed May 16, 2012, which claims the benefit of and priority to U.S. Provisional Patent Application No. 61/486,937, filed May 17, 2011, U.S. Provisional Patent Application No. 61/489,762, filed May 25, 2011, U.S. Provisional Patent Application No. 61/512,981, filed Jul. 29, 2011, U.S. Provisional Patent Application No. 61/569,528, filed Dec. 12, 2011, U.S. Provisional Patent Application No. 61/601,641, filed Feb. 22, 2012, and U.S. Provisional Patent Application No. 61/620,018, filed Apr. 4, 2012. The entire disclosure of each of these applications is hereby incorporated herein by reference.

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH

This invention was made with government support under IIP-0923633 awarded by the NSF and DE-OE0000231 awarded by the DOE. The government has certain rights in the invention.

FIELD OF THE INVENTION

In various embodiments, the present invention relates to pneumatics, hydraulics, power generation, and energy storage, and more particularly, to systems and methods using pneumatic, pneumatic/hydraulic, and/or hydraulic cylinders for energy storage and recovery.

BACKGROUND

Storing energy in the form of compressed gas has a long history and components tend to be well tested and reliable, and have long lifetimes. The general principle of compressed-gas or compressed-air energy storage (CAES) is that generated energy (e.g., electric energy) is used to compress gas (e.g., air), thus converting the original energy to pressure potential energy; this potential energy is later recovered in a useful form (e.g., converted back to electricity) via gas expansion coupled to an appropriate mechanism. Advantages of compressed-gas energy storage include low specific-energy costs, long lifetime, low maintenance, reasonable energy density, and good reliability.

If a body of gas is at the same temperature as its environment, and expansion occurs slowly relative to the rate of heat exchange between the gas and its environment, then the gas will remain at approximately constant temperature as it expands. This process is termed “isothermal” expansion. Isothermal expansion of a quantity of high-pressure gas stored at a given temperature recovers approximately three times more work than would “adiabatic expansion,” that is, expansion where no heat is exchanged between the gas and its environment—e.g., because the expansion happens rapidly or in an insulated chamber. Gas may also be compressed isothermally or adiabatically.

An ideally isothermal energy-storage cycle of compression, storage, and expansion would have 100% thermodynamic efficiency. An ideally adiabatic energy-storage cycle would also have 100% thermodynamic efficiency, but there

are many practical disadvantages to the adiabatic approach. These include the production of higher temperature and pressure extremes within the system, heat loss during the storage period, and inability to exploit environmental (e.g., cogenerative) heat sources and sinks during expansion and compression, respectively. In an isothermal system, the cost of adding a heat-exchange system is traded against resolving the difficulties of the adiabatic approach. In either case, mechanical energy from expanding gas must usually be converted to electrical energy before use.

An efficient and novel design for storing energy in the form of compressed gas utilizing near isothermal gas compression and expansion has been shown and described in U.S. Pat. No. 7,832,207, filed Apr. 9, 2009 (the ‘207 patent) and U.S. Pat. No. 7,874,155, filed Feb. 25, 2010 (the ‘155 patent), the disclosures of which are hereby incorporated herein by reference in their entireties. The ‘207 and ‘155 patents disclose systems and techniques for expanding gas isothermally in staged cylinders and intensifiers over a large pressure range in order to generate electrical energy when required. Mechanical energy from the expanding gas may be used to drive a hydraulic pump/motor subsystem that produces electricity. Systems and techniques for hydraulic-pneumatic pressure intensification that may be employed in systems and methods such as those disclosed in the ‘207 and ‘155 patents are shown and described in U.S. Pat. No. 8,037,678, filed Sep. 10, 2010 (the ‘678 patent), the disclosure of which is hereby incorporated herein by reference in its entirety.

In the systems disclosed in the ‘207 and ‘155 patents, reciprocal mechanical motion is produced during recovery of energy from storage by expansion of gas in the cylinders. This reciprocal motion may be converted to electricity by a variety of techniques, for example as disclosed in the ‘678 patent as well as in U.S. Pat. No. 8,117,842, filed Feb. 14, 2011 (the ‘842 patent), the disclosure of which is hereby incorporated herein by reference in its entirety. The ability of such systems to either store energy (i.e., use energy to compress gas into a storage reservoir) or produce energy (i.e., expand gas from a storage reservoir to release energy) will be apparent to any person reasonably familiar with the principles of electrical and pneumatic machines.

The power density (volumetric or mass-based) of an energy-storage system that approximates isothermal expansion and compression of a gas by mingling a heat-exchange liquid with the gas may be defined as the maximum sustained power (kilowatts, kW) that the system can either convert to a stored form or extract from storage, divided by either the volume (m³) or mass (kg) of the system. The power density (either volumetric or mass-based) of an energy-storage system therefore may have units of kW/m³ or of kW/kg. An energy-storage system having higher power density will in general be capable of more economic storage and retrieval of energy than an otherwise comparable system with lower power density, i.e., averaged over the lifetime of the system its use will require fewer cents per kilowatt-hour stored and retrieved (¢/kWh).

Power density may be increased by a number of techniques; one such technique is to increase the rate at which thermal energy is exchanged by the heat-exchange liquid and the gas. One technique for achieving rapid heat exchange between the heat-exchange liquid and the gas is to spray the liquid through the gas as a mist or rain of droplets, which tends to increase the surface area of a given volume of liquid compared to the surface area of the same volume of liquid in a compact shape, e.g., a single cylinder or sphere. However, in many applications even more rapid heat exchange is desirable, and increasingly small heat-exchange droplet size (i.e.,

for increased heat-exchange surface area) may be difficult or impractical to attain. Thus, there is a need for systems and techniques for more-rapid heat exchange between a heat-exchange fluid and a gas to be or being compressed and/or expanded in compressed-gas energy storage and recovery systems.

SUMMARY

Embodiments of the present invention improve the performance of an energy storage-and-recovery system that employs heat exchange between a liquid and a gas to approximate isothermal (constant-temperature) expansion and compression of the gas in cylinders by mingling the liquid and the gas to form an aqueous foam, which increases the surface area of the liquid and facilitates rapid heat exchange with the gas and, therefore, improved power density. Thermal energy is typically exchanged more rapidly when liquid and gas are mingled as a foam than when the gas is brought into contact with liquid having a more compact shape (e.g., a single cylinder) or divided into a number of bodies having a more compact shape (e.g., spheroids, even if these are very small). Accelerated heat exchange is advantageous (e.g., supportive of higher system power density) in energy storage-and-recovery systems that approximate isothermal expansion and compression of gas, as described above. Embodiments of the invention allow for characteristics of the foam (e.g., bubble (i.e., “foam cell”) size, void fraction) to be altered during operation of the system, offering advantages detailed hereinbelow. Herein, the void fraction of a foam (also termed “gas fraction”) of a foam is defined as the fraction of a given volume of the foam that is occupied by gas.

An aqueous foam is a two-phase system (i.e., a system featuring both gas and liquid) in which a large volume fraction of gas is dispersed as bubbles or cells throughout a continuous liquid matrix (as discussed in J. B. Winterburn and P. J. Martin, “Mechanisms of ultrasound foam interactions,” *Asia-Pac. J. Chem. Eng.* 2009:4:184-190, the entire disclosure of which is incorporated by reference herein). These gas bubbles are contained by liquid films typically stabilized by an admixed surfactant, i.e., a substance consisting essentially of or comprising surface-active, amphiphilic molecules that preferentially accumulate at the liquid-gas interface. These liquid films are typically interconnected at their meeting points, forming a continuous liquid phase throughout the foam structure. The structure of a particular foam varies depending on its liquid fraction; foams may be divided into two broad classes accordingly. “Wet foams” consist essentially of approximately spherical bubbles separated by thick liquid films. In the limit of perfectly spherical, close-packed gas bubbles in a wet foam, geometry determines that the void fraction in the foam is approximately 0.74 by volume. Foams with void fractions greater than approximately 0.74 are “dry foams,” in which polyhedral gas cells are separated by thin liquid lamellae (i.e., walls or membranes). Embodiments of the present invention utilize wet and/or dry aqueous foam.

In embodiments of the invention, a pneumatic compressor-expander cylinder (herein termed a “cylinder”) is divided into two chambers by a slidably disposed piston, at least one of which (herein termed the “air chamber”) may contain gas or a gas-liquid mixture (e.g., a foam). Gas to be expanded or compressed may be introduced into the air chamber; a liquid (herein termed “heat-exchange liquid”) may also be introduced into the air chamber. Force may be exerted on the piston by the fluids within the air chamber or by a rod aligned with the cylinder, passing through a suitable port in one end of

the cylinder, and connected to a mechanical device (e.g., crankshaft) external to the cylinder.

In one embodiment of the invention, liquid and gas are mingled to form a foam (i.e., the liquid and gas are “foamed”) in a chamber or vessel external to a cylinder in which gas is to be expanded or compressed. In particular, a liquid may be used that promotes foaming with air (or another suitable gas) when agitated, sprayed, or otherwise energetically modified. An example of such a liquid is water containing, e.g., 2% to 5% of certain additives (e.g., surfactants), some of which are described in U.S. patent application Ser. No. 13/082,808, filed on Apr. 8, 2011 (the ‘808 application), the entire disclosure of which is incorporated by reference herein. The foam is admitted to the air chamber of the cylinder through a suitable mechanism (e.g., a valved port). Exchange of thermal energy between the gas and the liquid occurs whenever the gas and liquid are in contact with each other, but occurs more rapidly when foaming has increased the surface area over which the gas and liquid are in contact with each other. In various states of operation, the air chamber of the cylinder may contain no foam, be partly filled with foam, or be substantially filled with foam.

In various embodiments of the invention, the chamber or vessel in which the liquid and gas are foamed is a storage reservoir for gas at high pressure (e.g., approximately 3,000 psi). Liquid tending to separate from the foam may accumulate at the bottom of the reservoir and may be recirculated into the reservoir through a spray head or other foam-generating mechanism in order to maintain or regenerate a quantity of foam within the storage reservoir.

In various embodiments of the invention, foam (or the separated liquid component of a foam) that is at a desired temperature (e.g., relatively cold or relatively hot) may be diverted into a vessel in order to store exergy therein. Herein, the exergy of a system, e.g., the fluid contents of a vessel, is the maximum amount of work that can ideally be performed by bringing the system into thermal equilibrium with the environment. Herein, a vessel in which relatively cool or hot liquid is stored for the purpose of storing exergy is termed a “thermal well.”

In various embodiments of the invention, the liquid and gas are foamed in a dedicated device, herein termed a “mixing chamber,” that may employ spraying, eduction, sparging, passage through a packed bed or solid foam, fogging, spray of suspended droplets, and/or other mechanisms to produce foam. As utilized herein, a “sparger” is a mechanism for the introduction of foam (typically a lower-liquid-content foam) and/or gas into liquid and/or a foam (typically a higher liquid-content foam) to produce foam therewith.

In various states of operation of certain embodiments, foam may be directed to a vessel or chamber (e.g., placed in a fluid path communicating between the storage reservoir and the mixing chamber, or between the air chamber of one cylinder and the air chamber of another cylinder) for the purpose of separating the liquid and gas components of the foam. Such a vessel or chamber is herein termed a “separator.” Partial or substantially entire separation of foams may occur within separators, cylinders, mixing chambers, storage reservoirs, and other components (e.g., tubing). Liquid separated from foam in a separator or other component may be passed through a heat exchanger to alter its temperature, or otherwise treated or processed, and re-directed to the generation of foam in another portion of the system (e.g., a mixing chamber).

Fluid foams may be passed through one or more screens, riddles, or solid foams (all of which are herein termed “screens”) to control foam quality (e.g., bubble uniformity, average bubble size). Such screens may be constructed so as

to permit alteration of bubble size in various states of operation: for example, two perforated plates in substantial contact may be caused to slide with respect to each other, aligning or disaligning their perforations in a manner that allows passage of variously sized bubbles. Fluid foams may also be excited (e.g., in the mixing chamber) with acoustic vibrations (e.g., ultrasound) in order to affect the size and uniformity of the cells (bubbles) in the foam.

In various states of operation, gas or gas-liquid mixtures may be bypassed around a mixing chamber. For example, when gas is being expanded from storage, valves and piping may be configured so as to pass the gas through a mixing chamber for foaming. However, when gas is being compressed into storage, compressed gas or foam may be routed through a bypass (e.g., a pipe), and not through the mixing chamber. Routing gas through a bypass will in general dissipate less energy than routing through a mixing chamber, and therefore improve system efficiency.

In various embodiments of the invention, alternatively or additionally to foam generation outside a cylinder, foam may be generated by direct injection of liquid into the air chamber of a cylinder through, e.g., a spray head or other foam-generating device.

In various embodiments of the invention, foam may be excited with acoustic vibrations (e.g., ultrasound) in the air chamber of a cylinder to accelerate heat exchange between the gas and liquid components of the foam. Acoustic vibrations may accelerate such heat exchange between the gas and liquid components of a foam through various mechanisms (e.g., surface waves set up at the liquid-gas interfaces of bubbles or cells, or increased flow through lamellae and Plateau borders).

Various embodiments of the invention may include one or more of the following components: mixing chambers, separators, bypasses, screens, ultrasound generators, assemblies of two or more cylinders operating over different pressure ranges, and other components. As described in U.S. Pat. No. 7,802,426 (the '426 patent), the entire disclosure of which is incorporated by reference herein, compressible fluid (e.g., gas or foam) undergoing either compression or expansion may be directed, continuously or in installments, through a heat-exchange subsystem external to the cylinder. The heat-exchange subsystem either rejects heat to the environment (to cool fluid undergoing compression) or absorbs heat from the environment (to warm fluid undergoing expansion). Again, an isothermal process may be approximated via judicious selection of this heat-exchange rate.

Generally, the systems described herein may be operated in both an expansion mode and in the reverse compression mode as part of a full-cycle energy storage system with high efficiency. For example, the systems may be operated as both compressor and expander, storing electricity in the form of the potential energy of compressed gas and producing electricity from the potential energy of compressed gas. Alternatively, the systems may be operated independently as compressors or expanders.

Embodiments of the present invention are typically utilized in energy storage systems utilizing compressed gas. In a compressed-gas energy storage system, gas is stored at high pressure (e.g., approximately 3,000 psi). This gas may be expanded into a cylinder having a first compartment (or "chamber") and a second compartment separated by a piston slidably disposed within the cylinder (or by another boundary mechanism). A shaft may be coupled to the piston and extend through the first compartment and/or the second compartment of the cylinder and beyond an end cap of the cylinder, and a transmission mechanism may be coupled to the shaft for

converting a reciprocal motion of the shaft into a rotary motion, as described in the '678 and '842 patents. Moreover, a motor/generator may be coupled to the transmission mechanism. Alternatively or additionally, the shaft of the cylinders may be coupled to one or more linear generators, as described in the '842 patent.

As also described in the '842 patent, the range of forces produced by expanding a given quantity of gas in a given time may be reduced through the addition of multiple, series-connected cylinder stages. That is, as gas from a high-pressure reservoir is expanded in one chamber of a first, high-pressure cylinder, gas from the other chamber of the first cylinder is directed to the expansion chamber of a second, lower-pressure cylinder. Gas from the lower-pressure chamber of this second cylinder may either be vented to the environment or directed to the expansion chamber of a third cylinder operating at still lower pressure; the third cylinder may be similarly connected to a fourth cylinder; and so on.

The principle may be extended to more than two cylinders to suit particular applications. For example, a narrower output force range for a given range of reservoir pressures is achieved by having a first, high-pressure cylinder operating between, for example, approximately 3,000 psig and approximately 300 psig and a second, larger-volume, lower-pressure cylinder operating between, for example, approximately 300 psig and approximately 30 psig. When two expansion cylinders are used, the range of pressure within either cylinder (and thus the range of force produced by either cylinder) is reduced as the square root relative to the range of pressure (or force) experienced with a single expansion cylinder, e.g., from approximately 100:1 to approximately 10:1 (as set forth in the '842 patent). Furthermore, as set forth in the '678 patent, N appropriately sized cylinders can reduce an original operating pressure range R to $R^{1/N}$. Any group of N cylinders staged in this manner, where $N \geq 2$, is herein termed a cylinder group.

Embodiments of the present invention provide for the use of positive-displacement pumps to efficiently circulate liquid at relatively high pressure, e.g., liquid for the production of liquid sprays and/or aqueous foams used to approximate isothermal expansion and compression within cylinder assemblies, with resulting gain in the efficiency of the overall energy-storage and energy-recovery processes. Such positive-displacement pumps may be piston-in-tube-type pumps, rotary positive-displacement pumps (e.g., screw pumps, progressive cavity pumps), or other types of pump. As disclosed in U.S. patent application Ser. No. 13/009,409, filed Jan. 19, 2011 (the '409 application), the entire disclosure of which is incorporated by reference herein, efficient circulation of high-pressure fluid may be achieved using a high-inlet pressure low-differential pressure pump such as a reciprocating, double-acting, positive-displacement pump having a fluid-filled chamber containing a piston or other mechanism that separates the fluid on one side of the piston from the fluid on the other side; or using a screw pump, progressive cavity pump, or other rotary positive-displacement pump.

Various embodiments of the present invention use a rotary positive-displacement pump (e.g., screw pump) to enable the energy-efficient pumping of fluid already at high pressure (e.g., from approximately 1,000 pounds per square inch gauge [psig] to approximately 3,000 psig, or higher) to a somewhat higher pressure (e.g., approximately 50 psig higher than the input pressure). Useful applications of such a pump include, but are not limited to, (1) the introduction of a foam, foaming liquid, or liquid spray into a vessel storing pressurized gas, the resulting foam or spray enabling the transfer of heat to or from the gas, (2) the energy-efficient introduction of a foam, foaming liquid, or liquid spray into a chamber con-

taining pressurized gas, where the foam, foaming liquid, or spray enables the approximately isothermal expansion or compression of the gas within the chamber.

Herein, a screw pump is a positive-displacement pump that employs one or more screws in order to compress a fluid; a “positive displacement pump” is any device that traps a volume of fluid and then moves (displaces) that fluid, possibly compressing it in so doing; and a “screw” is a rod with a helical ridge or thread running along its length. Typically, in a screw pump, a screw meshes with a complementary surface defined by one or more ancillary components (e.g., a housing, or one or more other screws) in such a way that one or more approximately spiral-shaped volumes of fluid are trapped between the surface of the screw and the complementary surface. As the screw revolves, fluid is admitted at one end of the screw, trapped in approximately spiral-shaped volumes, moved longitudinally along the screw while possibly undergoing compression, and expelled or exhausted at the other end of the screw. In screw pumps where the pitch of the screw changes longitudinally, the volumes of fluid trapped between the screw and the complementary surface are compressed as they move longitudinally along the screw. Screw pumps that compress fluid are typically termed screw compressors. Screw pumps and compressors of various designs, including single-screw, dual-screw, and triple-screw pumps, as well as the properties and features of such pumps and compressors, will be known to persons reasonably familiar with the principles of compressors and pumps. Herein, the term “screw pump” generally refers to a screw compressor of the dual- or triple-screw type, but the use of screw pumps or rotary positive-displacement pumps of other types, including but not limited to Wendelkolben pumps, helical twisted Roots pumps, and eccentric screw pumps, is also contemplated and within the scope of the invention.

It will be apparent to persons familiar with the principles of compressors and pumps that a screw pump capable of compressing fluid may, in principle, be operated in reverse as an expander. In such reverse operation, fluid at a relatively high pressure is admitted at one end of the turning screw, trapped in an approximately spiral-shaped volume between the screw and the complementary surface, and moved longitudinally along the rotating screw as the trapped volume expands. This fluid, at lower pressure than the pressure at which it was admitted, is exhausted from the end of the screw opposite to the end at which it was admitted.

Embodiments of the present invention also provide for increasing the minimum or starting pressure within the inlet chambers of the cylinder group in compression mode by a pre-compressor. As disclosed in U.S. Pat. No. 8,104,274, filed May 18, 2011 (the '274 patent), the entire disclosure of which is incorporated by reference herein, pre-compression of air prior to the inlet chambers of the cylinder group may be used to increase power density of a compressed-gas energy storage system. Additionally, venting of gas from the cylinder group at pressures above atmospheric may increase power density. At least some of this potential energy remaining in the vented super-atmospheric pressure gas may be recovered in an expander device. In various embodiments where starting pressure is increased by a pre-compressor, the pre-compressor may include or consist essentially of a rotodynamic blower (e.g., radial centrifugal, axial) or positive-displacement type blower (e.g., lobe-type) or pump (e.g., screw pump). In various embodiments where cylinder group venting pressure is super-atmospheric, an expander may include or consist essentially of a second unidirectional device or the same device as the pre-compressor operated bidirectionally. Examples of such devices that may be used as expanders

include rotodynamic expanders (e.g., radial centrifugal, axial) and positive-displacement type expanders (e.g., piston-type) and pump/motors (e.g. screw pump/motor).

When, e.g., a screw pump is operated as a pre-compressor, work is performed to compress the fluid passing through the pump. This energy is supplied by a mechanism exterior to the pump (e.g., an electric motor). When, e.g., a screw pump is operated as an expander, the gas performs work on the pump and on any mechanisms to which the pump is attached (e.g., an electric generator). Moreover, compression of gas within a screw pump operated as a compressor (or within any other pre-compressor with sufficient capacity to avoid complete destruction (i.e., separation) of the foam prior to compression) may be made to occur substantially isothermally by the introduction, at and/or before the intake of the screw pump, and/or within the screw pump itself, of a foam or foaming liquid that partially or substantially fills the trapped spiral-shaped volume of fluid within the screw pump during the compression of the gas. The foaming liquid may be combined with gas prior to undergoing compression in order to produce substantially isothermal compression of the gas. Similarly, expansion of gas within a screw pump operated as an expander (or within any other expander with sufficient capacity to avoid complete destruction of the foam prior to expansion) may be made to occur substantially isothermally by the introduction, at and/or before the intake of the screw pump, and/or within the screw pump itself, of a suitable quantity of a foam or foaming liquid that partially or substantially fills the trapped spiral-shaped volume of fluid within the screw pump during the expansion of the gas. Droplets of heat-exchange liquid (introduced through, e.g., perforations in the surface of the screw or in the complementary surface) may be combined with foam or employed instead of foam in order to effect substantially isothermal compression or expansion of gas within the screw pump. In a pump used as a pre-compressor or as a post-expander, substantially isothermal operation may increase the overall efficiency of the energy storage system.

Increasing the minimum or starting pressure within the inlet chamber of a cylinder group typically decreases the range of gauge pressures occurring within the cylinder group (and thus the range of forces exerted by the cylinder group). Gauge pressure range is reduced in direct proportion to degree of pre-compression. For example, for a system having a non-pre-compressed inlet pressure of approximately 1 psig and a maximum pressure of approximately 2,500 psig, the range of gauge pressures is approximately 2500:1; for an otherwise identical system having a pre-compressed inlet pressure of approximately 5 psig and a maximum pressure of approximately 2,500 psig, the range of gauge pressures is one-fifth as great (i.e., approximately 500:1).

Additionally, the mass of air in the inlet chamber at the initial pressure is increased in a pre-compressed system versus a non-pre-compressed system by approximately the ratio of the absolute pressures (e.g., approximately 19.7 psia/14.7 psia, depending on the polytropic coefficient of the compression or expansion). Thus, if a single compression stroke takes the same amount of time in a system with pre-compression as in a system without pre-compression, a greater mass of compressed air at the output pressure (e.g., approximately 2,500 psig), representing a proportionately greater amount of stored energy, is produced in a given time interval. In other words, for a single complete compression by a given cylinder, higher compression power is achieved by pre-compression.

It will be apparent to persons familiar with the principles of compressors and pumps that some blowers and pumps (e.g., screw pump) may be operated in reverse as an expanders. That is, e.g., fluid at a relatively high pressure is admitted at

one end of the turning screw, trapped in an approximately spiral-shaped volume between the screw and the complementary surface, and moved longitudinally along the rotating screw as the trapped volume expands. This gas, at lower pressure than the pressure at which it was admitted, is exhausted from the end of the screw opposite to the end at which it was admitted. Expansion of gas within a screw pump that is operated as an expander may be made to occur substantially isothermally by the introduction, at and/or before the intake of the screw pump, and/or within the screw pump itself, of a foam or foaming liquid that partially or substantially fills the trapped spiral-shaped volume of fluid within the screw pump during the expansion of the gas.

It will be clear to persons familiar with the principles of compressors and pumps that by similar reasoning, when the system is operated as an expander rather than as a compressor, higher expansion power is achieved by allowing the outlet pressure of the cylinder group to be significantly above atmospheric pressure. Moreover, expanding this super-atmospheric-pressure outlet gas through a device upon which the gas performs work (e.g., a screw-pump expander) allows some of the potential energy of the outlet gas to be converted into work. Recovery of this work increases the overall efficiency of the energy storage system.

Every compression or expansion of a quantity of gas, where such a compression or expansion is herein termed “a gas process,” is generally one of three types: (1) adiabatic, during which the gas exchanges no heat with its environment and, consequently, rises or falls in temperature, (2) isothermal, during which the gas exchanges heat with its environment in such a way as to remain at constant temperature, and (3) polytropic, during which the gas exchanges heat with its environment but its temperature does not remain constant. Perfectly adiabatic gas processes are not practical because some heat is always exchanged between any body of gas and its environment (ideal insulators and reflectors do not exist); perfectly isothermal gas processes are not practical because for heat to flow between a quantity of gas and a portion of its environment (e.g., a body of liquid), a nonzero temperature difference must exist between the gas and its environment—e.g., the gas must be allowed to heat during compression in order that heat may be conducted to the liquid. Hence real-world gas processes are typically polytropic, though they may approximate adiabatic or isothermal processes.

The Ideal Gas Law states that for a given quantity of gas having mass m , pressure p , volume V , and temperature T , $pV=mRT$, where R is the gas constant ($R=287$ J/K·kg for air). For an isothermal process, T is a constant throughout the process, so $pV=C$, where C is some constant.

For a polytropic process, as will be clear to persons familiar with the science of thermodynamics, $pV^n=C$ throughout the process, where n , termed the polytropic index, is some constant generally between 1.0 and 1.6. For $n=1$, $pV^n=pV^1=pV=C$, i.e., the process is isothermal. In general, a process for which n is close to 1 (e.g., 1.05) may be deemed approximately isothermal.

For an adiabatic process, $pV^\gamma=C$, where γ , termed the adiabatic coefficient, is equal to the ratio of the gas’s heat capacity at constant pressure C_p to its heat capacity at constant volume, C_v , i.e., $\gamma=C_p/C_v$. In practice, γ is dependent on pressure. For air, the adiabatic coefficient γ is typically between 1.4 and 1.6.

Herein, we define a “substantially isothermal” gas process as one having $n \leq 1.1$. The gas processes conducted within cylinders described herein are preferably substantially isothermal with $n \leq 1.05$. Herein, wherever a gas process taking place within a cylinder assembly or storage vessel is

described as “isothermal,” this word is synonymous with the term “substantially isothermal.”

The amount of work done in compression or expansion of a given quantity of gas varies substantially with polytropic index n . For compressions, the lowest amount of work done is for an isothermal process and the highest for an adiabatic process, and vice versa for expansions. Hence, for gas processes such as typically occur in the compressed-gas energy storage systems described herein, the end temperatures attained by adiabatic, isothermal, and substantially isothermal gas processes are sufficiently different to have practical impact on the operability and efficiency of such systems. Similarly, the thermal efficiencies of adiabatic, isothermal, and substantially isothermal gas processes are sufficiently different to have practical impact on the overall efficiency of such energy storage systems. For example, for compression of a quantity of gas from initial temperature of 20° C. and initial pressure of 0 psig (atmospheric) to a final pressure of 180 psig, the final temperature T of the gas will be exactly 20° C. for an isothermal process, approximately 295° C. for an adiabatic process, approximately 95° C. for a polytropic compression having polytropic index $n=1.1$ (10% increase in n over isothermal case of $n=1$), and approximately 60° C. for a polytropic compression having polytropic index $n=1.05$ (5% increase in n over isothermal case of $n=1$). In another example, for compression of 1.6 kg of air from an initial temperature of 20° C. and initial pressure of 0 psig (atmospheric) to a final pressure of approximately 180 psig, including compressing the gas into a storage reservoir at 180 psig, isothermal compression requires approximately 355 kilojoules of work, adiabatic compression requires approximately 520 kilojoules of work, and a polytropic compression having polytropic index $n=1.045$ requires approximately 375 kilojoules of work; that is, the polytropic compression requires approximately 5% more work than the isothermal process, and the adiabatic process requires approximately 46% more work than the isothermal process.

It is possible to estimate the polytropic index n of gas processes occurring in cylinder assemblies such as are described herein by empirically fitting n to the equation $pV^n=C$, where pressure p and volume V of gas during a compression or expansion, e.g., within a cylinder, may both be measured as functions of time from piston position, known device dimensions, and pressure-transducer measurements. Moreover, by the Ideal Gas Law, temperature within the cylinder may be estimated from p and V , as an alternative to direct measurement by a transducer (e.g., thermocouple, resistance thermal detector, thermistor) located within the cylinder and in contact with its fluid contents. In many cases, an indirect measurement of temperature via volume and pressure may be more rapid and more representative of the entire volume than a slower point measurement from a temperature transducer. Thus, temperature measurements and monitoring described herein may be performed directly via one or more transducers, or indirectly as described above, and a “temperature sensor” may be one of such one or more transducers and/or one or more sensors for the indirect measurement of temperature, e.g., volume, pressure, and/or piston-position sensors.

All of the approaches described above for converting potential energy in a compressed gas into mechanical and electrical energy may, if appropriately designed, be operated in reverse to store electrical energy as potential energy in a compressed gas. Since the accuracy of this statement will be apparent to any person reasonably familiar with the principles of electrical machines, power electronics, pneumatics, and the principles of thermodynamics, the operation of these

mechanisms to both store energy and recover it from storage will not be described for each embodiment. Such operation is, however, contemplated and within the scope of the invention and may be straightforwardly realized without undue experimentation.

The systems described herein, and/or other embodiments employing foam-based heat exchange, liquid-spray heat exchange, and/or external gas heat exchange, may draw or deliver thermal energy via their heat-exchange mechanisms to external systems (not shown) for purposes of cogeneration, as described in U.S. Pat. No. 7,958,731, filed Jan. 20, 2010 (the '731 patent), the entire disclosure of which is incorporated by reference herein.

The compressed-air energy storage and recovery systems described herein are preferably "open-air" systems, i.e., systems that take in air from the ambient atmosphere for compression and vent air back to the ambient atmosphere after expansion, rather than systems that compress and expand a captured volume of gas in a sealed container (i.e., "closed-air" systems). The systems described herein generally feature one or more cylinder assemblies for the storage and recovery of energy via compression and expansion of gas. The systems also include (i) a reservoir for storage of compressed gas after compression and supply of compressed gas for expansion thereof, and (ii) a vent for exhausting expanded gas to atmosphere after expansion and supply of gas for compression. The storage reservoir may include or consist essentially of, e.g., one or more one or more pressure vessels (i.e., containers for compressed gas that may have rigid exteriors or may be inflatable, that may be formed of various suitable materials such as metal or plastic, and that may or may not fall within ASME regulations for pressure vessels), pipes (i.e., rigid containers for compressed gas that may also function as and/or be rated as fluid conduits, have lengths well in excess (e.g., >100x) of their diameters, and do not fall within ASME regulations for pressure vessels), or caverns (i.e., naturally occurring or artificially created cavities that are typically located underground). Open-air systems typically provide superior energy density relative to closed-air systems.

Furthermore, the systems described herein may be advantageously utilized to harness and recover sources of renewable energy, e.g., wind and solar energy. For example, energy stored during compression of the gas may originate from an intermittent renewable energy source of, e.g., wind or solar energy, and energy may be recovered via expansion of the gas when the intermittent renewable energy source is nonfunctional (i.e., either not producing harnessable energy or producing energy at lower-than-nominal levels). As such, the systems described herein may be connected to, e.g., solar panels or wind turbines, in order to store the renewable energy generated by such systems.

In one aspect, embodiments of the invention feature a method of recovering energy. A first foam having a first foam expansion ratio is transferred to a first cylinder assembly, and the first foam is expanded in the first cylinder assembly, thereby recovering energy therefrom. Thereafter, a second foam is transferred to a second cylinder assembly different from the first cylinder assembly. The second foam has a second foam expansion ratio larger than the first foam expansion ratio. The second foam is expanded in the second cylinder assembly, thereby recovering energy therefrom. The first and second cylinder assemblies are preferably portions of a single power unit utilized for the expansion (and possibly compression) of gas and/or foam.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The expanded second foam may be exhausted from the sec-

ond cylinder assembly. At least a gaseous portion of the expanded second foam may be exhausted to ambient atmosphere. After expanding the first foam, the expanded first foam may be exhausted from the first cylinder assembly. The second foam may include or consist essentially of at least a portion (e.g., a gaseous portion or a foam portion) of the expanded first foam. The expanded first foam may be exhausted into a foam vessel, and heat-transfer liquid may be introduced into the foam vessel to form the second foam. After expanding the first foam, at least a portion of the expanded first foam may be separated into gaseous and liquid components. The separation may include or consist essentially of mechanical separation (e.g., by one or more blades, one or more shears, one or more baffles, and/or one or more centrifuges) and/or application of ultrasound energy. The second foam may be formed by introducing heat-transfer liquid into the gaseous component of the expanded first foam. The liquid component of the expanded first foam may be stored (e.g., in a storage reservoir). The mass ratio of the first foam may be approximately equal to the mass ratio of the second foam. The average cell size and/or the uniformity of cell size of the first foam may be altered before expanding the first foam. The average cell size and/or the uniformity of cell size of the second foam may be altered before expanding the second foam. The foam mass ratio of the first foam and/or the second foam may be selected from the range of 1 to 4. The first foam and/or the second foam may be expanded substantially isothermally. The first foam may be formed by mingling heat-transfer liquid and compressed gas. The void fraction of the first foam may be controlled by controlling a rate of transfer of heat-transfer liquid into the compressed gas. A pressure or a temperature within the first cylinder assembly may be sensed, and the rate of transfer may be controlled in response to the sensed pressure and/or temperature. Expanding the first foam and expanding the second foam may both drive a crankshaft mechanically coupled to the first and second cylinder assemblies.

In another aspect, embodiments of the invention feature a method of storing energy. Heat-transfer liquid is dispersed into gas (e.g., air at approximately atmospheric pressure) to form a first foam having a first foam expansion ratio. The first foam is compressed within a first cylinder assembly. Thereafter, a second foam is transferred to a second cylinder assembly different from the first cylinder assembly. The second foam has a second foam expansion ratio smaller than the first foam expansion ratio. The second foam is compressed within the second cylinder assembly, and the compressed second foam is exhausted from the second cylinder assembly. At least the gaseous component of the compressed second foam is stored (e.g., in a storage reservoir).

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The first foam may be transferred to the first cylinder assembly prior to compressing the first foam within the first cylinder assembly. At least a portion of a liquid component may be separated from the compressed second foam prior to storing the gaseous component. The separation may include or consist essentially of mechanical separation (e.g., by one or more blades, one or more shears, one or more baffles, and/or one or more centrifuges) and/or application of ultrasound energy. Both the gaseous component and the liquid component of the compressed second foam may be stored (i.e., together in the same storage reservoir or separately in separate reservoirs). After compressing the first foam within the first cylinder assembly, the compressed first foam may be exhausted from the first cylinder assembly. The second foam may include or consist essentially of at least a portion (e.g., a gaseous portion

or a foam portion) of the compressed first foam. The compressed first foam may be exhausted into a foam vessel (e.g., a pressure vessel, a pipe, or a manifold). Heat-transfer liquid may be introduced into the foam vessel to form the second foam. After compressing the first foam, at least a portion of the compressed first foam may be separated into gaseous and liquid components. The separation may include or consist essentially of mechanical separation (e.g., by one or more blades, one or more shears, one or more baffles, and/or one or more centrifuges) and/or application of ultrasound energy. The second foam may be formed by introducing heat-transfer liquid into the gaseous component of the compressed first foam. The heat-transfer liquid introduced into the gaseous component of the compressed first foam may include or consist essentially of at least a portion of the liquid component of the separated compressed first foam. The liquid component of the compressed first foam may be stored (e.g., in a storage reservoir). The mass ratio of the first foam may be approximately equal to the mass ratio of the second foam. The average cell size and/or the uniformity of cell size of the first foam may be altered before compressing the first foam. The average cell size and/or the uniformity of cell size of the second foam may be altered before compressing the second foam. The foam mass ratio of the first foam and/or of the second foam may be selected from the range of 1 to 4. The first foam and/or the second foam may be compressed substantially isothermally. The void fraction of the first foam may be controlled by controlling a rate of dispersal of heat-transfer liquid into the gas. A pressure or a temperature within the first cylinder assembly may be sensed, and the rate of dispersal may be controlled in response to the sensed pressure and/or temperature. A crankshaft may be driven to compress the first foam and the second foam. The crankshaft may be mechanically coupled to the first and second cylinder assemblies. Forming the first foam may include or consist essentially of spraying heat-transfer liquid on a screen.

In yet another aspect, embodiments of the invention feature an energy storage and recovery system. The system includes a cylinder assembly for storing energy by compression and/or recovering energy by expansion, a storage reservoir, and a mixing chamber for (i) receiving gas and heat-transfer liquid from the storage reservoir, (ii) mixing the gas with the heat-transfer liquid to form a foam, and (iii) transferring the foam to the cylinder assembly. The mixing chamber is selectively fluidly connected to the cylinder assembly and the storage reservoir. The mixing chamber is selectively fluidly connected to the storage reservoir by a first conduit for transferring gas (and which may additionally transfer liquid, but is typically connected to a substantially gas-filled region of the storage reservoir) and a second conduit, different from the first conduit, for transferring heat-transfer liquid (and which may additionally transfer gas, but is typically connected to a substantially liquid-filled region of the storage reservoir).

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The mixing chamber may include a mechanism for altering at least one characteristic of the foam (e.g., foam cell size and/or foam cell size uniformity). The mechanism may include or consist essentially of a screen and/or a source of ultrasound energy. A foam-generating mechanism may be coupled to the first conduit and/or the second conduit in the mixing chamber. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. The system may include a second cylinder assembly storing energy by compression or recovering energy by expansion over a pressure range different from a pressure range of the cylinder assem-

bly. A vent for exhausting expanded gas to atmosphere may be selectively fluidly connected to the second cylinder assembly. A control system may control the cylinder assembly and/or the mixing chamber to enforce substantially isothermal compression and/or substantially isothermal expansion in the cylinder assembly. A sensor may detect pressure within the cylinder assembly and/or the mixing chamber, and the control system may be responsive to the sensor. The control system may control the flow rate of heat-transfer liquid into the mixing chamber in response to the detected pressure. A circulation apparatus (e.g., a variable-speed pump) may transfer heat-transfer liquid within the second conduit. A movable boundary mechanism may separate the cylinder assembly into two chambers. A crankshaft may be mechanically coupled to the boundary mechanism and may convert reciprocal motion of the boundary mechanism into rotary motion. A motor/generator may be coupled to the crankshaft. The storage reservoir may include or consist essentially of a pressure vessel, a pipe, and/or a cavern.

In an additional aspect, embodiments of the invention feature a method of energy storage. Foam is compressed within a cylinder to a first pressure. The compressed foam is transferred to a storage reservoir, where it at least partially separates into gaseous and liquid components at approximately the first pressure. At least a portion of the liquid component is removed from the storage reservoir and stored at a second pressure lower than the first pressure.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. Prior to storing the at least a portion of the liquid component at the second pressure, energy may be recovered from the at least a portion of the liquid component by reducing its pressure. A crankshaft may be driven with the recovered energy. The crankshaft may be mechanically coupled to the cylinder. Prior to compressing the foam, the foam may be formed by mingling heat-transfer liquid and gas. The foam may be formed in a foam vessel selectively fluidly connected to the cylinder. The foam vessel may include or consist essentially of a pressure vessel, a pipe, and/or a manifold. Forming the foam may include or consist essentially of spraying heat-transfer liquid on a screen. Prior to compressing the foam, the average cell size or the uniformity of cell size of the foam may be altered. The void fraction of the foam may be controlled by controlling the rate of transfer of heat-transfer liquid into the gas. A pressure and/or a temperature within the cylinder may be sensed, and the rate of transfer may be controlled in response thereto. At least a portion of the stored liquid component may be mingled with gas to form additional foam, which may then be compressed. The foam mass ratio of the foam may be selected from the range of 1 to 4. The foam may be compressed substantially isothermally. Compressing the foam may include or consist essentially of driving a crankshaft coupled to the cylinder. The compressed foam may at least partially separate due to gravity. The compressed foam may be at least partially separated via at mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy.

In another aspect, embodiments of the invention feature an energy storage and recovery system including first and second cylinder assemblies for storing energy by compression and/or recovering energy by expansion. The second cylinder assembly has a pressure range of operation different from a pressure range of operation of the first cylinder assembly. A first foam vessel for at least one of intermediate storage or formation of a first foam therein is selectively fluidly connected to the first cylinder assembly. A second foam vessel for at least one of intermediate storage or formation of a second

foam therein is selectively fluidly connected to the first cylinder assembly and to the second cylinder assembly. A third foam vessel for at least one of intermediate storage or formation of a third foam therein is selectively fluidly connected to the second cylinder assembly.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A vent to a surrounding atmosphere may be selectively fluidly connected to the third foam vessel. A storage reservoir for the storage of compressed gas (e.g., as a gas or as part of a foam) may be selectively fluidly connected to the first foam vessel. The system may include a recirculation mechanism for transferring foam and/or liquid from a first location in the first foam vessel to a second location in the first foam vessel different from the first location. The first foam vessel may include or consist essentially of at least one of a pressure vessel, a pipe, or a manifold. The second foam vessel may include or consist essentially of at least one of a pressure vessel, a pipe, or a manifold. The third foam vessel may include or consist essentially of at least one of a pressure vessel, a pipe, or a manifold.

In yet another aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a foam-generating mechanism, a manifold, and, selectively fluidly connected to the manifold, at least one cylinder assembly expansion and/or compression of foam therewithin. The foam-generating mechanism includes or consists essentially of a spray chamber, at least one dispersal mechanism for dispersing liquid into gas flowing through the spray chamber, and fluidly coupled to the at least one dispersal mechanism, a reservoir for containing the liquid. The manifold receives foam from the spray chamber.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A circulation mechanism (e.g., a fan) may at least partially form a flow of gas through the spray chamber. Another circulation mechanism (e.g., a pump such as a variable-speed pump) may circulate liquid from the reservoir to the at least one dispersal mechanism. A valve for exhausting gas from the manifold at least during formation of foam within the manifold may be connected to the manifold. A screen through which foam is formed in the manifold from the dispersed liquid in the spray chamber may be disposed between the spray chamber and the manifold. A separation chamber may be selectively fluidly connected to the manifold. The separation chamber may comprise therewithin a separation mechanism for separating foam into gaseous and liquid components. The separation chamber may be selectively fluidly connected to the reservoir. The separation mechanism may include or consist essentially of a source of ultrasound energy, a blade, a shear, a baffle, and/or a centrifuge.

In an aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a plurality of cylinder pairs, a first foam-generating mechanism for generating foam at a low pressure within a first pressure range, and a second foam-generating mechanism, different from the first foam-generating mechanism, for generating foam at a high pressure within a second pressure range. Each cylinder pair includes or consists essentially of (i) a low-pressure cylinder for expansion and/or compression over the first pressure range and (ii) a high-pressure cylinder for expansion and/or compression over the second pressure range, which is different from the first pressure range and overlaps the first pressure range at least at an intermediate pressure.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A

manifold for intermediate storage of foam at the low pressure may be selectively fluidly connected to (i) the plurality of low-pressure cylinders and (ii) the first foam-generating mechanism. A manifold for intermediate storage of foam at the high pressure may be selectively fluidly connected to (i) the plurality of high-pressure cylinders and (ii) the second foam-generating mechanism. The first foam-generating mechanism may include or consist essentially of (i) at least one dispersal mechanism for dispersing liquid into gas and (ii) a screen through which foam is formed from the dispersed liquid. The second foam-generating mechanism may include or consist essentially of a dispersal mechanism for at least one of spraying, sparging, fogging, or agitating liquid. The system may include a third foam-generating mechanism for generating foam at the intermediate pressure. A manifold for intermediate storage of foam at the intermediate pressure may be selectively fluidly connected to (i) the plurality of low-pressure cylinders, (ii) the plurality of high-pressure cylinders, and (iii) the third foam-generating mechanism.

In another aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a cylinder assembly for compression to store energy and/or expansion to recover energy, a foam-generating mechanism for introducing a foam within the cylinder assembly, a pumping cylinder for pumping heat-transfer fluid to the foam-generating mechanism, a first storage reservoir for storage of compressed gas, and a second storage reservoir for storage of heat-transfer fluid. The cylinder assembly includes a first movable boundary mechanism therein and a first rod coupled to the first movable boundary mechanism. The pumping cylinder includes a second movable boundary mechanism therein and a second rod coupled to the second movable boundary mechanism. The first storage reservoir is selectively fluidly connected to the cylinder assembly. The second storage reservoir is selectively fluidly connected to the pumping cylinder.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The first storage reservoir and the second storage reservoir may be the same reservoir or may be different (i.e., discrete) reservoirs. A heat-transfer subsystem may thermally condition the heat-transfer fluid, and may include or consist essentially of a heat exchanger. The first and second rods may be mechanically coupled to a mechanism for interconverting reciprocal motion of the first and second rods with rotary motion. The mechanism may include or consist essentially of a crankshaft. The crankshaft may maintain the first and second rods in a fixed phase relationship. The foam-generating mechanism may be disposed within the cylinder assembly or disposed outside of the cylinder assembly and connected thereto via a conduit. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. The first storage reservoir may store fluid at a pressure different from a pressure at which the second storage reservoir stores fluid.

In an additional aspect, embodiments of the invention feature a method of storing and recovering energy. Compressed gas is transferred from a storage reservoir to a mixing chamber selectively fluidly connected thereto. In the mixing chamber, a first foam including or consisting essentially of the compressed gas and a heat-transfer fluid is formed. The first foam is transferred from the mixing chamber to a cylinder. The first foam is expanded in the cylinder to recover energy therefrom. The expanded first foam is removed from the cylinder. A second foam is introduced into the cylinder and compressed in the cylinder to store energy therein. At least a

portion of the compressed second foam is transferred to the storage reservoir, the transfer bypassing the mixing chamber.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The average cell size and/or the uniformity of cell size of the first foam may be altered before expanding the first foam. Removing the expanded first foam from the cylinder may include or consist essentially of exhausting a gaseous component of the expanded first foam to ambient atmosphere. Removing the expanded first foam from the cylinder may include or consist essentially of transferring the expanded first foam to a second cylinder, where it may be further expanded. The expanded first foam may be separated into a gaseous component and a liquid component. The expanded first foam may be separated via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. The liquid component of the expanded first foam may be stored. The foam mass ratio of the first foam may be selected from the range of 1 to 4. Transferring at least a portion of the compressed second foam to the storage reservoir may include or consist essentially of transferring a gaseous component of the at least a portion of the compressed second foam to the storage reservoir. Transferring at least a portion of the compressed second foam to the storage reservoir may include or consist essentially of transferring both a gaseous component and a liquid component of the at least a portion of the compressed second foam to the storage reservoir. The at least a portion of the compressed second foam may be transferred to the storage reservoir via a bypass connection between the cylinder and the storage reservoir. A valve may substantially prevent entry of the compressed second foam into the mixing chamber during transfer to the storage reservoir. A second portion of the compressed second foam may be transferred from the cylinder to the storage reservoir via the mixing chamber. The first foam and/or the second foam is expanded substantially isothermally. The cylinder may include a piston therein, and expanding the first foam in the cylinder may drive (i) a mechanism mechanically coupled to the piston and/or (ii) a hydraulic system coupled to the cylinder. Expanding the first foam may drive the mechanism, and the mechanism may include or consist essentially of a crankshaft. Forming the first foam may include or consist essentially of transferring heat-transfer liquid into the mixing chamber. The void fraction of the first foam may be controlled by controlling the rate of transfer of the heat-transfer liquid into the mixing chamber. A pressure and/or a temperature within the cylinder and/or the mixing chamber may be sensed, and the rate of transfer may be controlled in response thereto.

In yet another aspect, embodiments of the invention feature a method of recovering energy. A first foam including or consisting essentially of a compressed gas and a heat-transfer fluid is formed within a storage reservoir and transferred to a cylinder. The first foam is expanded in the cylinder to recover energy therefrom, and the expanded first foam is removed from the cylinder. A second foam is compressed in the cylinder to store energy therein, and at least a portion of the compressed second foam is stored in the storage reservoir.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. Forming the first foam may include or consist essentially of, within the storage reservoir, mixing heat-transfer fluid and compressed gas via a foam-generating mechanism. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. Heat-transfer liquid (e.g., substantially non-foamed heat-transfer liquid) may be circu-

lated from a region of the storage reservoir to the foam-generating mechanism. The heat-transfer liquid may be circulated outside of the storage reservoir. The average cell size and/or the uniformity of cell size of the first foam may be altered before expanding the first foam. Removing the expanded first foam from the cylinder may include or consist essentially of exhausting a gaseous component of the expanded first foam to ambient atmosphere. The expanded first foam may be separated into a gaseous component and a liquid component. The expanded first foam may be separated via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. The liquid component of the expanded first foam may be stored (e.g., in the storage reservoir). The foam mass ratio of the first foam may be selected from the range of 1 to 4. Storing at least a portion of the compressed second foam in the storage reservoir may include or consist essentially of storing a gaseous component of the at least a portion of the compressed second foam. Storing at least a portion of the compressed second foam in the storage reservoir may include or consist essentially of storing both a gaseous component and a liquid component of the at least a portion of the compressed second foam. Removing the expanded first foam from the cylinder may include or consist essentially of transferring the expanded first foam to a second cylinder, where it may be further expanded. The first foam and/or the second foam may be expanded substantially isothermally. The cylinder may include a piston therein. Expanding the first foam in the cylinder may drive (i) a mechanism mechanically coupled to the piston (e.g., a crankshaft) and/or (ii) a hydraulic system coupled to the cylinder.

In an additional aspect, embodiments of the invention feature a method of storing and recovering energy. Gas is transferred into a cylinder. Heat-transfer liquid is transferred into the cylinder to therein mix with the gas and form a foam including or consisting essentially of the gas and the heat-transfer liquid. Within the cylinder, the foam is compressed to store energy and/or expanded to recover energy, and the compressed or expanded foam is exhausted from the cylinder.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. Gas may be transferred into the cylinder from a storage reservoir, and the heat-transfer liquid may be transferred into the cylinder from the storage reservoir. The gas and the heat-transfer liquid may be transferred into the cylinder via different inlets. The foam may be compressed, and at least a portion of the compressed foam may be stored within a storage reservoir. Storing at least a portion of the compressed foam within the storage reservoir may include or consist essentially of storing a gaseous component of the compressed foam. Storing at least a portion of the compressed foam within the storage reservoir may include or consist essentially of storing both a gaseous component and a liquid component of the compressed foam. The void fraction of the foam may be controlled by controlling a rate of transfer of the heat-transfer liquid into the cylinder. A pressure and/or a temperature within the cylinder may be sensed, and the rate of transfer may be controlled in response thereto. The foam may be expanded, and exhausting the expanded foam from the cylinder may include or consist essentially of exhausting a gaseous component of the expanded foam to ambient atmosphere. The foam may be expanded, and exhausting the expanded foam from the cylinder may include or consist essentially of transferring the expanded foam to a second cylinder, where it may be further expanded. The foam may be expanded, and the expanded foam may be separated into a gaseous component and a liquid component. The expanded

foam may be separated via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. The foam may be expanded, and the liquid component of the expanded foam may be stored. The foam mass ratio of the foam may be selected from the range of 1 to 4. The foam may be expanded or compressed substantially isothermally. The foam may be expanded and the cylinder may include a piston therein. Expanding the foam may drive (i) a mechanism mechanically coupled to the piston (e.g., a crankshaft) and/or (ii) a hydraulic system coupled to the cylinder.

In yet an additional aspect, embodiments of the invention feature a method of storing and recovering energy. A gas is compressed or expanded in a plurality of discrete stages, each stage being performed over a different pressure range. During one of the stages, heat is exchanged between the gas and discrete droplets of a first heat-transfer fluid introduced into the gas. During another one of the stages, heat is exchanged between the gas and a second heat-transfer fluid, the gas and the second heat-transfer fluid being combined to form a foam.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. After the compression or expansion during the another one of the stages, at least a portion of the foam may be separated into gaseous and liquid components. The at least a portion of the foam may be separated via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. The gas may be compressed, and, thereafter, stored in a storage reservoir. The gas may be expanded, and, thereafter, vented to ambient atmosphere. The first and second heat-transfer fluids may include the same liquid (e.g., water). The second heat-transfer fluid may include a foaming additive. The discrete droplets of the first heat-transfer fluid may be introduced into the gas by spraying. The heat exchange between the discrete droplets of the first heat-transfer fluid and the gas may render the expansion or compression during that stage substantially isothermal. The heat exchange within the foam between the gas and the second heat-transfer fluid may render the expansion or compression during that stage substantially isothermal. The expansion or compression of foam may be performed within a cylinder. The foam may be generated by mixing the gas with the second heat-transfer fluid within the cylinder. The foam may be generated by mixing the gas with the second heat-transfer fluid outside of the cylinder, and then the foam may be transferred into the cylinder. The average cell size and/or the uniformity of cell size of the foam may be altered before the foam enters the cylinder. The gas may be expanded, and the cylinder may include a piston therein. Expanding the gas in the cylinder may drive (i) a mechanism mechanically coupled to the piston (e.g., a crankshaft) and/or (ii) a hydraulic system coupled to the cylinder. The foam mass ratio of the foam may be selected from the range of 1 to 4. Forming the foam may include or consist essentially of transferring the second heat-transfer fluid into the gas. The void fraction of the foam may be controlled by controlling a rate of transfer of the second heat-transfer fluid. A pressure and/or a temperature within at least one of the stages may be sensed, and the rate of transfer may be controlled in response thereto.

In an aspect, embodiments of the invention feature a method of storing and recovering energy. Two different processes are performed within a cylinder, the processes comprising (i) compressing gas to store energy and (ii) expanding gas to recover energy. During one of the processes, heat is exchanged with the gas by introducing discrete droplets of a first heat-transfer fluid thereto. During the other one of the

processes, heat is exchanged with the gas by mixing the gas with a second heat-transfer fluid to form a foam.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. After the other one of the processes, at least a portion of the foam may be separated into gaseous and liquid components. The separation may be performed via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. After gas is compressed, it may be stored in a storage reservoir. After gas is expanded, it may be vented to ambient atmosphere. The first and second heat-transfer fluids may include the same liquid (e.g., water). The second heat-transfer fluid may include a foaming additive. The discrete droplets of the first heat-transfer fluid may be introduced into the gas by spraying. The heat exchange between the discrete droplets of the first heat-transfer fluid and the gas may render that process substantially isothermal. The heat exchange within the foam between the gas and the second heat-transfer fluid may render that process substantially isothermal. The foam may be formed by mixing the gas with the second heat-transfer fluid within the cylinder. The foam may be formed by mixing the gas with the second heat-transfer fluid outside of the cylinder, and then the foam may be transferred into the cylinder. The average cell size and/or the uniformity of cell size of the foam may be altered before the foam enters the cylinder. The cylinder may include a piston therein. Expanding the gas in the cylinder may drive (i) a mechanism mechanically coupled to the piston (e.g., a crankshaft) or (ii) a hydraulic system coupled to the cylinder. The foam mass ratio of the foam may be selected from the range of 1 to 4. The void fraction of the foam may be controlled by controlling the rate of transfer of the second heat-transfer fluid into the gas. A pressure and/or a temperature of the gas may be sensed, and the rate of transfer may be controlled in response thereto.

In another aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a cylinder assembly storing energy by compression and/or recovering energy by expansion, a storage reservoir, a mixing chamber, and a bypass conduit. The storage reservoir is selectively fluidly connected to the cylinder assembly. The mixing chamber is selectively fluidly connected to the cylinder assembly and the storage reservoir, and the mixing chamber (i) receives gas from the storage reservoir, (ii) mixes the gas with a heat-transfer liquid to form a foam, and (iii) transfers the foam to the cylinder assembly. The bypass conduit selectively fluidly connects the cylinder assembly directly to the storage reservoir and transfers gas and/or foam from the cylinder assembly to the storage reservoir without traversing the mixing chamber.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The mixing chamber may be selectively fluidly connected to the storage reservoir by (i) a first conduit for transferring gas and (ii) a second conduit, different from the first conduit, for transferring heat-transfer liquid. A mechanism for altering at least one characteristic of the foam (e.g., foam cell size and/or foam cell size uniformity) may be disposed in the mixing chamber. The mechanism may include or consist essentially of a screen and/or a source of ultrasound energy. A foam-generating mechanism may be disposed in the mixing chamber. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. The system may include a second cylinder assembly for storing energy by compression or recovering energy by expansion over a pressure range different from a pressure range of the cylinder

assembly. A vent for exhausting expanded gas to atmosphere may be selectively fluidly connected to the second cylinder assembly. The system may include a control system for controlling the cylinder assembly and/or the mixing chamber to enforce substantially isothermal compression and/or substantially isothermal expansion in the cylinder assembly. The system may include a sensor for detecting a pressure within the cylinder assembly and/or the mixing chamber, and the control system may be responsive to the sensor. The control system may control the flow rate of heat-transfer liquid into the mixing chamber in response to the detected pressure. A circulation apparatus (e.g., a pump such as a variable-speed pump) may transfer heat-transfer liquid to the mixing chamber. A movable boundary mechanism may separate the cylinder assembly into two chambers. A crankshaft for converting reciprocal motion of the boundary mechanism into rotary motion may be mechanically coupled to the boundary mechanism. A motor/generator may be coupled to the crankshaft. The storage reservoir may include or consist essentially of a pressure vessel, a pipe, and/or a cavern.

In yet another aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a cylinder assembly storing energy by compression and/or recovering energy by expansion, a storage reservoir selectively fluidly connected to the cylinder assembly, and a foam-generating mechanism for generating, within the storage reservoir, a foam including or consisting essentially of gas and a heat-transfer liquid.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A mechanism for altering at least one characteristic of the foam (e.g., foam cell size and/or foam cell size uniformity) may be disposed between the storage reservoir and the cylinder assembly. The mechanism may include or consist essentially of a screen and/or a source of ultrasound energy. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. The system may include a second cylinder assembly for storing energy by compression or recovering energy by expansion over a pressure range different from a pressure range of the cylinder assembly. A vent for exhausting expanded gas to atmosphere may be selectively fluidly connected to the second cylinder assembly. The system may include a control system for controlling the cylinder assembly to enforce substantially isothermal compression and/or substantially isothermal expansion therein. The system may include a sensor for detecting pressure or temperature within the cylinder assembly, and the control system may be responsive to the sensor. A circulation apparatus (e.g., a pump such as a variable-speed pump) may transfer heat-transfer liquid to the foam generating mechanism. A conduit may selectively fluidly connect a bottom region of the storage reservoir with the foam-generating mechanism. The conduit may extend outside of the storage reservoir. A movable boundary mechanism may separate the cylinder assembly into two chambers. A crankshaft for converting reciprocal motion of the boundary mechanism into rotary motion may be mechanically coupled to the boundary mechanism. A motor/generator may be coupled to the crankshaft. The storage reservoir may include or consist essentially of a pressure vessel, a pipe, and/or a cavern.

In an additional aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a cylinder assembly for storing energy by compression and/or recovering energy by expansion, a storage reservoir, and disposed within the cylinder assembly, a foam-generating mechanism for generating a foam via

introduction of a heat-transfer liquid into gas within the cylinder assembly. The cylinder assembly is selectively fluidly connected to the storage reservoir by (i) a first conduit for transferring gas and (ii) a second conduit, different from the first conduit, for transferring heat-transfer liquid to the foam-generating mechanism.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. The system may include a second cylinder assembly for at least one of storing energy by compression or recovering energy by expansion over a pressure range different from a pressure range of the cylinder assembly. A vent for exhausting expanded gas to atmosphere may be selectively fluidly connected to the second cylinder assembly. The system may include a control system for controlling the cylinder assembly to enforce substantially isothermal compression and/or substantially isothermal expansion therein. The system may include a sensor for detecting a pressure or a temperature within the cylinder assembly, and the control system may be responsive to the sensor. The control system may control a flow rate of heat-transfer liquid through the foam-generating mechanism in response to the detected pressure. A circulation apparatus (e.g., a pump such as a variable-speed pump) may transfer heat-transfer liquid within the second conduit. A movable boundary mechanism may separate the cylinder assembly into two chambers. A crankshaft for converting reciprocal motion of the boundary mechanism into rotary motion may be mechanically coupled to the boundary mechanism. A motor/generator may be coupled to the crankshaft. The storage reservoir may include or consist essentially of a pressure vessel, a pipe, and/or a cavern.

In an aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a cylinder assembly for storing energy by compression and/or recovering energy by expansion, a spray mechanism for introducing discrete droplets of a first heat-transfer liquid within the cylinder assembly for heat exchange between gas and the discrete droplets of the first heat-transfer liquid, and, discrete from the spray mechanism, a foam-generating mechanism for generating and/or introducing within the cylinder assembly a foam including or consisting essentially of gas and a second heat-transfer liquid.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The first and second heat-transfer liquids may include the same liquid (e.g., water). The second heat-transfer liquid may include a foaming additive. The spray mechanism may include or consist essentially of a spray head and/or a spray rod. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. A storage reservoir for storage of compressed gas (e.g., a pressure vessel, a pipe, and/or a cavern) may be selectively fluidly connected to the cylinder assembly. A vent for exhausting expanded gas to ambient atmosphere may be selectively fluidly connected to the cylinder assembly.

In another aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of (i) a plurality of cylinder assemblies for, each over a different pressure range, storing energy by compression and/or recovering energy by expansion, (ii) selectively fluidly connected to one of the cylinder assemblies, a spray mechanism for introducing therein discrete droplets of a first heat-transfer liquid, and (iii) selectively fluidly connected to

a different one of the cylinder assemblies, a foam-generating mechanism for generating and/or introducing therewithin a foam including or consisting essentially of gas and a second heat-transfer liquid.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The first and second heat-transfer liquids may include the same liquid (e.g., water). The second heat-transfer liquid may include a foaming additive. The spray mechanism may include or consist essentially of a spray head and/or a spray rod. The foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. A storage reservoir for storage of compressed gas (e.g., a pressure vessel, a pipe, and/or a cavern) may be selectively fluidly connected to the cylinder assembly. A vent for exhausting expanded gas to ambient atmosphere may be selectively fluidly connected to the cylinder assembly.

In yet another aspect, embodiments of the invention feature a method of energy recovery. A piston within a pumping cylinder is driven to transfer heat-transfer liquid therefrom to a foam-generating mechanism. Compressed gas is transferred to a cylinder assembly or to the foam-generating mechanism. Via the foam-generating mechanism, (i) a foam is formed by mingling the heat-transfer liquid with the compressed gas and (ii) the foam is introduced within the cylinder assembly. The foam is expanded within the cylinder assembly, the expansion driving a piston within the cylinder assembly. At least a portion of the expanded foam is exhausted from the cylinder assembly.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The compressed gas may be transferred to the cylinder assembly from a first storage reservoir. Heat-transfer liquid may be transferred to the pumping cylinder from a second storage reservoir. The first and second storage reservoirs may be the same reservoir. At least a portion of the expanded foam may be separated into gaseous and liquid components. The liquid component may be transferred to the first storage reservoir. The separation may be performed via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. The second storage reservoir may be separate and distinct from the first storage reservoir. The storage pressure within the first storage reservoir may be higher than the storage pressure within the second storage reservoir (which may be, e.g., approximately atmospheric pressure). At least a portion of the expanded foam may be separated into gaseous and liquid components. The liquid component may be transferred to the second storage reservoir. The separation may be performed via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. The heat-transfer liquid may be thermally conditioned (i.e., heated or cooled) prior to the heat-transfer liquid entering the foam-generating mechanism. The foam-generating mechanism may be disposed within the cylinder assembly. The foam-generating mechanism may be disposed outside the cylinder assembly and connected thereto by a conduit. The pistons within the pumping cylinder and the cylinder assembly may be driven simultaneously. At least a portion of the expanded foam may be separated into gaseous and liquid components. The separation may be performed via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. Exhausting at least a portion of the expanded foam from the cylinder assembly may include or consist essentially of exhausting a gaseous portion of the expanded foam to ambient atmosphere. Exhausting at

least a portion of the expanded foam from the cylinder assembly may include or consist essentially of transferring the expanded foam or a gaseous portion thereof to a second cylinder assembly for further expansion thereof. The foam mass ratio of the foam may be selected from the range of 1 to 4. The void fraction of the foam may be controlled by controlling a rate of transfer of the heat-transfer liquid to the foam-generating mechanism. A pressure and/or a temperature within the cylinder and/or the foam-generating mechanism may be sensed, and the rate of transfer may be controlled in response thereto.

In an additional aspect, embodiments of the invention feature a method of energy storage. A piston within a pumping cylinder is driven to transfer heat-transfer liquid therefrom to a foam-generating mechanism. Gas is transferred to a cylinder assembly or to the foam-generating mechanism. Via the foam-generating mechanism, (i) a foam is formed by mingling the heat-transfer liquid with the compressed gas and (ii) the foam is introduced within the cylinder assembly. A piston within the cylinder assembly is driven to compress the foam within the cylinder assembly. At least a portion of the compressed foam is exhausted from the cylinder assembly.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. Exhausting the at least a portion of the compressed foam from the cylinder assembly may include or consist essentially of transferring the compressed foam to a first storage reservoir. Exhausting the at least a portion of the compressed foam from the cylinder assembly may include or consist essentially of transferring a gaseous component of the compressed foam to a first storage reservoir. Exhausting the at least a portion of the compressed foam from the cylinder assembly may include or consist essentially of transferring a liquid component of the compressed foam to a second storage reservoir. The first and second storage reservoirs may be the same reservoir. The second storage reservoir may be separate and distinct from the first storage reservoir. The storage pressure within the first storage reservoir may be higher than the storage pressure within the second storage reservoir (which may be, e.g., approximately atmospheric pressure). The heat-transfer liquid may be thermally conditioned (i.e., heated or cooled) prior to the heat-transfer liquid entering the foam-generating mechanism. The foam-generating mechanism may be disposed within the cylinder assembly. The foam-generating mechanism may be disposed outside the cylinder assembly and connected thereto by a conduit. The pistons within the pumping cylinder and the cylinder assembly may be driven simultaneously. At least a portion of the compressed foam may be separated into gaseous and liquid components. The separation may be performed via mechanical separation (e.g., by a blade, a shear, a baffle, and/or a centrifuge) and/or application of ultrasound energy. Gas may be transferred to the cylinder assembly or to the foam-generating mechanism from ambient atmosphere. Gas may be transferred to the cylinder assembly or to the foam-generating mechanism from a second cylinder assembly after compression of the gas within the second cylinder assembly. The foam mass ratio of the foam may be selected from the range of 1 to 4. The void fraction of the foam may be controlled by controlling a rate of transfer of the heat-transfer liquid to the foam-generating mechanism. A pressure and/or a temperature within the cylinder and/or the foam-generating mechanism may be sensed, and the rate of transfer may be controlled in response thereto.

In an aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of a first cylinder assembly for at least one of compression to store energy or expansion to recover energy

and a second cylinder assembly for at least one of compression to store energy or expansion to recover energy. The first cylinder assembly includes or consists essentially of (i) a first cylinder, (ii) at least partially disposed within the first cylinder, a first pumping mechanism for circulating heat-transfer fluid from the first cylinder, and (iii) a first foam-generating mechanism for mingling heat-transfer fluid with gas to form a foam and introducing the foam within the first cylinder. The second cylinder assembly includes or consists essentially of (i) a second cylinder, (ii) at least partially disposed within the second cylinder and selectively fluidly connected to the first foam-generating mechanism, a second pumping mechanism for circulating heat-transfer fluid from the second cylinder, and (iii) a second foam-generating mechanism for mingling heat-transfer fluid with gas to form a foam and introducing the foam within the second cylinder, the second foam-generating mechanism being selectively fluidly connected to the first pumping mechanism.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The first pumping mechanism may include or consist essentially of a first piston disposed within the first cylinder and separating the first cylinder into two compartments, a first piston rod comprising a first cavity and coupled to the first piston, and a first hollow tube disposed at least partially in the first cavity and extending through at least a portion of the first cylinder. Relative motion between the first hollow tube and the first piston rod may circulate heat-transfer fluid into and out of the first cavity. The second pumping mechanism may include or consist essentially of a second piston disposed within the second cylinder and separating the second cylinder into two compartments, a second piston rod comprising a first cavity and coupled to the second piston, and a second hollow tube disposed at least partially in the second cavity and extending through at least a portion of the second cylinder. Relative motion between the second hollow tube and the second piston rod may circulate heat-transfer fluid into and out of the second cavity. The first and second piston rods may be mechanically coupled to a common crankshaft. A first heat-exchange subsystem may thermally condition heat-transfer fluid circulating to the first foam-generating mechanism. The first heat-exchange subsystem may include or consist essentially of a heat exchanger. The first heat-exchange subsystem may be fluidly connected to the first foam-generating mechanism and the second pumping mechanism. A second heat-exchange subsystem may thermally condition heat-transfer fluid circulating to the second foam-generating mechanism. The second heat-exchange subsystem may include or consist essentially of a heat exchanger. The second heat-exchange subsystem may be fluidly connected to the second foam-generating mechanism and the first pumping mechanism. A first storage reservoir for storage of gas and/or heat-transfer fluid may be selectively fluidly connected to the first and second cylinder assemblies. A second storage reservoir for storage of gas and/or heat-transfer fluid may be selectively fluidly connected to the first and second cylinder assemblies. The storage pressure of the first storage reservoir may be higher than the storage pressure of the second storage reservoir (which may be approximately atmospheric pressure). The first and/or second storage reservoirs may be selectively fluidly connected to the first and/or second pumping mechanisms. The first foam-generating mechanism may be disposed within the first cylinder. The first foam-generating mechanism may be disposed outside of the first cylinder and connected thereto via a conduit. The second foam-generating mechanism may be disposed within the second cylinder. The second foam-generating mechanism may be disposed outside

of the second cylinder and connected thereto via a conduit. The first foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger. The second foam-generating mechanism may include or consist essentially of one or more nozzles, a rotating blade, a source of ultrasound energy, and/or a sparger.

In another aspect, embodiments of the invention feature a method of energy recovery utilizing an energy-recovery system including or consisting essentially of (i) a first cylinder assembly comprising a first cylinder, a first pumping mechanism, and a first foam-generating mechanism and (ii) a second cylinder assembly comprising a second cylinder, a second pumping mechanism, and a second foam-generating mechanism. An expansion stroke is performed with the first cylinder assembly and an exhaust stroke is performed with the second cylinder assembly. The expansion stroke includes or consists essentially of (i) mingling heat-transfer fluid and gas at the first foam-generating mechanism to form a foam, (ii) expanding the foam within the first cylinder, and (iii) introducing heat-transfer fluid into the first pumping mechanism. The exhaust stroke includes or consists essentially of (i) exhausting foam or a gaseous component thereof from the second cylinder and (ii) pumping heat-transfer fluid with the second pumping mechanism to the first foam-generating mechanism.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The exhaust stroke may include or consist essentially of thermally conditioning (e.g., heating) the heat-transfer fluid pumped with the second pumping mechanism before it enters the first foam-generating mechanism. An expansion stroke may be performed with the second cylinder assembly, and an exhaust stroke may be performed with the first cylinder assembly. The expansion stroke may include or consist essentially of (i) mingling heat-transfer fluid and gas at the second foam-generating mechanism to form a second foam, (ii) expanding the second foam within the second cylinder, and (iii) introducing heat-transfer fluid into the second pumping mechanism. The exhaust stroke may include or consist essentially of (i) exhausting foam or a gaseous component thereof from the first cylinder and (ii) pumping heat-transfer fluid with the first pumping mechanism to the second foam-generating mechanism.

In yet another aspect, embodiments of the invention feature a method of energy storage utilizing an energy-recovery system including or consisting essentially of (i) a first cylinder assembly comprising a first cylinder, a first pumping mechanism, and a first foam-generating mechanism and (ii) a second cylinder assembly comprising a second cylinder, a second pumping mechanism, and a second foam-generating mechanism. A compression stroke is performed with the first cylinder assembly. The compression stroke includes or consists essentially of (i) within the first cylinder, compressing a foam generated by the first foam-generating mechanism, and (ii) pumping heat-transfer fluid with the first pumping mechanism to the second foam-generating mechanism. A compression stroke is performed with the second cylinder assembly. The compression stroke includes or consists essentially of (i) within the second cylinder, compressing a second foam generated by the second foam-generating mechanism, and (ii) pumping heat-transfer fluid with the second pumping mechanism to the first foam-generating mechanism.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. An intake stroke may be performed with the first cylinder assembly. The intake stroke may include or consist essentially of (i)

receiving gas within the first cylinder and (ii) introducing heat-transfer fluid into the first pumping mechanism. An intake stroke may be performed with the second cylinder assembly. The intake stroke may include or consist essentially of (i) receiving gas within the second cylinder and (ii) introducing heat-transfer fluid into the second pumping mechanism. The compression stroke of the first cylinder assembly may include thermally conditioning (e.g., cooling) the heat-transfer fluid pumped with the first pumping mechanism before it enters the second foam-generating mechanism. The compression stroke of the second cylinder assembly may include thermally conditioning (e.g., cooling) the heat-transfer fluid pumped with the second pumping mechanism before it enters the first foam-generating mechanism.

In an additional aspect, embodiments of the invention feature a system for efficient power demand response. The system includes or consists essentially of (i) a first energy-storage system for supplying power in response to demand up to a first power-demand level, (ii) connected to the first energy-storage system, a second energy-storage system for supplying power in response to demand greater than the first power-demand level, and (iii) a heat-exchange subsystem for thermally conditioning at least a portion of the first and/or second energy-storage systems, thereby increasing a collective efficiency of the first and second energy-storage systems.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The first energy-storage system may include or consist essentially of a battery, a flywheel, and/or an ultracapacitor. The second energy-storage system may include or consist essentially of a compressed-gas energy-storage system that supplies power by expanding compressed gas (e.g., in the form of a foam). The first and second energy-storage systems may be connected in parallel to a power grid. The first power-demand level may be approximately 500 kW. The heat-exchange subsystem may recover thermal energy from the first energy-storage system for thermally conditioning, in the second energy-storage system, (i) heat-transfer fluid for thermally conditioning gas undergoing expansion and/or compression or for mingling with gas to form foam, (ii) gas or foam undergoing expansion and/or compression, and/or (iii) gas or foam stored in a storage reservoir prior to expansion. The heat-exchange subsystem may include or consist essentially of a first heat exchanger associated with the first energy-storage system and a second heat exchanger associated with the second energy-storage system that is (i) separate from the first heat exchanger and (ii) selectively fluidly connectable to the first heat exchanger. The first heat exchanger may be fluidly connected to a first radiator and/or a first thermal well and the second heat exchanger may be fluidly connected to a second radiator and/or a second thermal well.

In yet an additional aspect, embodiments of the invention feature a method of power delivery. A time-varying power-demand level is detected. Power is supplied from a first energy-storage system when the power-demand level is less than or equal to a threshold level. Power is supplied from a second energy-storage system when the power-demand level is greater than the threshold level. At least a portion of the first and/or second energy-storage systems is thermally conditioned (i.e., heated or cooled), thereby increasing a collective efficiency of the first and second energy-storage systems.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. Power may be supplied from the first energy-storage system only when the power-demand level is less than or equal to the threshold level. Power may be supplied from the second energy-storage system only when the power-demand level is

greater than the threshold level. Thermally conditioning may include or consist essentially of recovering thermal energy from the first energy-storage system and thermally conditioning at least a portion of the second energy-storage system with the recovered thermal energy. Thermally conditioning the at least a portion of the second energy-storage system may include or consist essentially of thermally conditioning (i) heat-transfer fluid for thermally conditioning gas undergoing expansion and/or compression or for mingling with gas to form foam, (ii) gas or foam undergoing expansion and/or compression, and/or (iii) gas or foam stored in a compressed-gas reservoir prior to expansion. Power may be supplied from the first and second energy-storage systems over a common bus line. Supplying power from the second energy-storage system may include or consist essentially of expanding gas and/or foam to recover energy therefrom.

In an aspect, embodiments of the invention feature a method of energy storage and recovery utilizing a power unit comprising a cylinder assembly for the compression of gas to store energy and/or the expansion of gas to recover energy. Gas is compressed in the power unit. Heat-transfer liquid from a thermal well is introduced into the gas prior to and/or during compression, the heat-transfer liquid absorbing thermal energy from the gas during compression. At least a portion of the heat-transfer liquid is transferred back to the thermal well to store the thermal energy therein. Thereafter, gas is expanded in the power unit. Heat-transfer liquid from the thermal well is introduced into the gas prior to and/or during expansion, the gas absorbing thermal energy from the heat-transfer liquid during expansion.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The heat-transfer liquid may be introduced into the gas by spraying the heat-transfer liquid into the gas. Introducing the heat-transfer liquid into the gas may form a foam comprising the heat-transfer liquid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid prior to transferring the at least a portion of the heat-transfer liquid back to the thermal well. Introducing the heat-transfer liquid prior to and/or during compression may render the compression substantially isothermal. Introducing the heat-transfer liquid prior to and/or during expansion may render the expansion substantially isothermal. Waste thermal energy produced by the power unit may be stored in the thermal well. Thermal energy may be exchanged between the thermal well and the surrounding environment. Thermal energy may be exchanged between the thermal well and the surrounding environment while the power unit is neither compressing nor expanding. The temperature of the heat-transfer liquid introduced into the gas prior to and/or during compression may be below ambient temperature. The temperature of the heat-transfer liquid introduced into the gas prior to and/or during expansion may be above ambient temperature. Compressed gas may be stored after compression, and stored compressed gas may be expanded during expansion. Storing compressed gas may include storing heat-transfer fluid at an elevated temperature. The stored heat-transfer fluid may be transferred to the thermal well, thereby storing thermal energy therein. Expanded gas may be vented to atmosphere after expansion.

In another aspect, embodiments of the invention feature an energy storage and recovery system configured for use with a thermal well for containing heat-transfer fluid therein. The system includes or consists essentially of (i) a power unit comprising a cylinder assembly for, therewithin, compression of gas to store energy and/or expansion of gas to recover energy, (ii) a mechanism for introducing heat-transfer liquid into the gas prior to and/or during the compression and/or

expansion, the mechanism configured for selective fluid connection to the thermal well, (iii) a conduit for selectively transferring heat-transfer liquid introduced into the gas back into the thermal well, and (iv) thermally connected to the power unit and the thermal well, a waste-heat heat-exchange system for transferring waste thermal energy from the power unit to the thermal well.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The system may include an environmental heat-exchange system configured for thermal connection to the thermal well and the surrounding environment. The system may include a control system for (i) sensing an operating state of the power unit and (ii) operating the environmental heat-exchange system only when the power unit is neither expanding nor compressing gas. A reservoir for storage of compressed gas may be selectively fluidly connected to the power unit. The reservoir may be configured for selective fluid connection to the thermal well for enabling the flow of heat-transfer liquid therebetween. A vent for venting expanded gas to atmosphere may be selectively fluidly connected to the power unit.

In yet another aspect, embodiments of the invention feature a method of energy storage and recovery utilizing a power unit comprising a cylinder assembly for the compression of gas to store energy and/or the expansion of gas to recover energy. Gas is compressed and/or expanded in the power unit. Prior to and/or during the compression and/or expansion, (i) heat-transfer liquid is withdrawn from a thermal well at a first temperature, (ii) the heat-transfer liquid is thermally conditioned, thereby bringing it to a second temperature different from the first temperature, and (iii) the thermally conditioned heat-transfer liquid is introduced into the gas to exchange heat therewith.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The heat exchange between the gas and the thermally conditioned heat-transfer liquid may render the compression and/or expansion substantially isothermal. Introducing the thermally conditioned heat-transfer liquid into the gas may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the thermally conditioned heat-transfer liquid into the gas may form a foam including or consisting essentially of the heat-transfer liquid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid after the compression and/or expansion. Thermally conditioning the heat-transfer liquid may include or consist essentially of transfer of thermal energy between the heat-transfer liquid and a second thermal well discrete from and not fluidly connected to the thermal well. Waste thermal energy produced by the power unit may be stored in the second thermal well. Thermal energy may be exchanged between the second thermal well and the surrounding environment. Thermal energy may be exchanged between the second thermal well and the surrounding environment while the power unit is neither compressing nor expanding.

In an additional aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of (i) a power unit comprising a cylinder assembly for, therewithin, compression of gas to store energy and/or expansion of gas to recover energy, (ii) a mechanism for introducing heat-transfer liquid into the gas prior to and/or during the compression and/or expansion, (iii) selectively fluidly connected to the mechanism, a thermal well for containing heat-transfer liquid therein, (iv) a heat exchanger connected between the thermal well and the power unit for thermally conditioning heat-transfer liquid flowing from the

thermal well to the power unit, and (v) associated with the heat exchanger and discrete from the thermal well, a second thermal well for storing thermal energy from and/or supplying thermal energy to the heat-transfer fluid.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A conduit may transfer heat-transfer liquid introduced into the gas back into the thermal well. A waste-heat heat-exchange system for transferring waste thermal energy from the power unit to the second thermal well may be thermally connected to the power unit and the second thermal well. An environmental heat-exchange system may be thermally connected to the second thermal well and the surrounding environment. The heat exchanger may be disposed within the second thermal well.

In yet an additional aspect, embodiments of the invention feature a method of energy storage and recovery utilizing a power unit comprising a cylinder assembly for the compression of gas to store energy and/or the expansion of gas to recover energy. Gas is compressed or expanded in the power unit. Prior to and/or during the compression and/or expansion, (i) heat-transfer liquid is withdrawn from a first thermal well at a first temperature, and (ii) the heat-transfer liquid is introduced into the gas to exchange heat therewith, the heat exchange bringing the heat-transfer liquid to a second temperature different from the first temperature. Heat-transfer liquid is transferred at the second temperature to a second thermal well discrete from and not fluidly connected to the first thermal well.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The heat exchange between the gas and the heat-transfer liquid may render the compression and/or expansion substantially isothermal. Introducing the heat-transfer liquid into the gas may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the heat-transfer liquid into the gas may form a foam including or consisting essentially of the heat-transfer liquid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid prior to transferring heat-transfer liquid to the second thermal well. Waste thermal energy produced by the power unit may be stored in the second thermal well. Thermal energy may be exchanged between the surrounding environment and the first thermal well and/or the second thermal well. Thermal energy may be exchanged with the surrounding environment while the power unit is neither compressing nor expanding.

In an aspect, embodiments of the invention feature an energy storage and recovery system including (i) a power unit comprising a cylinder assembly for, therewithin, compression of gas to store energy and/or expansion of gas to recover energy, (ii) a mechanism for introducing heat-transfer liquid into the gas prior to and/or during the compression and/or expansion, (iii) selectively fluidly connected to the mechanism, (a) a first thermal well for containing heat-transfer liquid therein at a first temperature and (b) a second thermal well, discrete from the first thermal well, for containing heat-transfer liquid therein at a second temperature different from the first temperature. The system also includes a control system for (i) prior to and/or during compression, routing heat-transfer liquid (a) from the first thermal well into the gas and (b) from the power unit into the second thermal well, and (ii) prior to and/or during expansion, routing heat-transfer liquid (a) from the second thermal well into the gas and (b) from the power unit into the first thermal well.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A

waste-heat heat-exchange system for transferring waste thermal energy from the power unit to the second thermal well may be thermally connected to the power unit and the second thermal well. An environmental heat-exchange system may be thermally connected to the first thermal well and the surrounding environment. An environmental heat-exchange system may be thermally connected to the second thermal well and the surrounding environment.

In another aspect, embodiments of the invention feature a method of energy storage and recovery utilizing a power unit comprising a cylinder assembly for the compression of gas to store energy and/or the expansion of gas to recover energy. Gas is compressed and/or expanded in the power unit. Prior to and/or during the compression and/or expansion, (i) heat-transfer liquid is withdrawn from a reservoir at a first temperature, (ii) the heat-transfer liquid is thermally conditioned, thereby bringing it to a second temperature different from the first temperature, and (iii) the thermally conditioned heat-transfer liquid is introduced into the gas to exchange heat therewith. Thermally conditioning the heat-transfer liquid includes or consists essentially of exchanging thermal energy between the heat-transfer liquid and a heat-storage liquid flowing from a first thermal well having a third temperature to a second thermal well (i) discrete from the first thermal well and (ii) having a fourth temperature different from the third temperature.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The heat-transfer liquid and the heat-storage liquid may not mix during thermal conditioning of the heat-transfer liquid. The heat exchange between the gas and the thermally conditioned heat-transfer liquid may render the compression and/or expansion substantially isothermal. Introducing the thermally conditioned heat-transfer liquid into the gas may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the thermally conditioned heat-transfer liquid into the gas may form a foam including or consisting essentially of the heat-transfer fluid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid after the compression and/or expansion.

In yet another aspect, embodiments of the invention feature an energy storage and recovery system including or consisting essentially of (i) a power unit comprising a cylinder assembly for, therewithin, compression of gas to store energy and/or expansion of gas to recover energy, (ii) a mechanism for introducing heat-transfer liquid into the gas prior to and/or during the compression and/or expansion, (iii) selectively fluidly connected to the mechanism, a reservoir for containing heat-transfer liquid therein, (iv) a heat exchanger connected between the reservoir and the power unit for thermally conditioning heat-transfer liquid flowing from the reservoir to the power unit, and (v) associated with the heat exchanger and not fluidly connected to the reservoir, (a) a first thermal well for containing heat-storage liquid at a first temperature and (b) a second thermal well for containing heat-storage liquid at a second temperature different from the first temperature, the flow of heat-storage liquid between the first and second thermal wells thermally conditioning the heat-transfer fluid.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. A conduit may transfer heat-transfer liquid introduced into the gas back into the reservoir. A waste-heat heat-exchange system for transferring waste thermal energy from the power unit to the second thermal well may be thermally connected to the power unit and the second thermal well. An environmental heat-exchange system may be thermally connected to the first

thermal well and the surrounding environment. An environmental heat-exchange system may be thermally connected to the second thermal well and the surrounding environment.

In an additional aspect, embodiments of the invention feature a method of energy storage and recovery utilizing a power unit comprising a cylinder assembly for the compression of gas to store energy and/or the expansion of gas to recover energy. Gas is compressed in the power unit. Prior to and/or during the compression, (i) heat-transfer liquid is withdrawn from a liquid reservoir at a first temperature, and (ii) the heat-transfer liquid is introduced into the gas to exchange heat therewith, the heat exchange bringing the heat-transfer liquid to a second temperature higher than the first temperature. Both the heat-transfer liquid at the second temperature and the compressed gas are transferred to a compressed-gas store.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. The heat exchange between the gas and the heat-transfer liquid may render the compression substantially isothermal. Introducing the heat-transfer liquid into the gas may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the heat-transfer liquid into the gas may form a foam including or consisting essentially of the heat-transfer liquid and the gas. Transferring both the heat-transfer liquid at the second temperature and the compressed gas to a compressed-gas store may include or consist essentially of transferring the foam to the compressed-gas store.

The method may include (i) transferring compressed gas from the compressed-gas store to the power unit, (ii) expanding the compressed gas in the power unit, (iii) prior to and/or during the expansion, (a) withdrawing heat-transfer liquid from the compressed-gas store at a third temperature and (b) introducing the heat-transfer liquid into the gas to exchange heat therewith, the heat exchange bringing the heat-transfer liquid to a fourth temperature lower than the third temperature, and (iv) transferring the heat-transfer liquid to the liquid reservoir. The heat exchange between the gas and the heat-transfer liquid may render the expansion substantially isothermal. Introducing the heat-transfer liquid into the gas prior to and/or during expansion may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the heat-transfer liquid into the gas prior to and/or during expansion may form a foam including or consisting essentially of the heat-transfer liquid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid prior to transferring the heat-transfer liquid to the liquid reservoir. Waste thermal energy produced by the power unit may be stored in the compressed-gas store. Thermal energy may be exchanged between the surrounding environment and the compressed-gas store. Thermal energy may be exchanged with the surrounding environment while the power unit is neither compressing nor expanding.

In yet an additional aspect, embodiments of the invention feature a method of energy storage and recovery utilizing a power unit comprising a cylinder assembly for the compression of gas to store energy and/or the expansion of gas to recover energy. Gas is compressed in the power unit. Prior to and/or during the compression, (i) heat-transfer liquid is withdrawn from a first thermal well at a first temperature, and (ii) the heat-transfer liquid is introduced into the gas to exchange heat therewith, the heat exchange bringing the heat-transfer liquid to a second temperature higher than the first temperature. The compressed gas is transferred to a compressed-gas store. The heat-transfer liquid at the second temperature is

transferred to the compressed-gas store and/or a second thermal well discrete from the first thermal well.

The method may include (i) transferring compressed gas from the compressed-gas store to the power unit, (ii) expanding the compressed gas in the power unit, (iii) prior to and/or during the expansion, (a) withdrawing heat-transfer liquid from at least one of the compressed-gas store or the second thermal well, and (b) introducing the heat-transfer liquid into the gas to exchange heat therewith, and (iv) transferring the heat-transfer liquid to the first thermal well.

Embodiments of the invention incorporate one or more of the following in any of a variety of different combinations. Expanding the compressed gas in the power unit may include or consist essentially of expanding the compressed gas in a first stage and a second stage each spanning a different pressure range. Heat-transfer liquid may be withdrawn from the compressed-gas store prior to and/or during expansion in the first stage. Heat-transfer liquid may be withdrawn from the second thermal well prior to and/or during expansion in the second stage. The heat exchange between the gas and the heat-transfer liquid prior to and/or during the expansion may render the expansion substantially isothermal. Introducing the heat-transfer liquid into the gas prior to and/or during expansion may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the heat-transfer liquid into the gas may form a foam including or consisting essentially of the heat-transfer liquid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid prior to transferring the heat-transfer liquid to the first thermal well. Compressing the gas in the power unit may include or consist essentially of compressing the gas in a first stage and a second stage each spanning a different pressure range. Heat-transfer liquid may be transferred to the compressed-gas store after or during compression in the first stage. Heat-transfer liquid may be transferred to the second thermal well after or during compression in the second stage. The heat exchange between the gas and the heat-transfer liquid prior to and/or during compression may render the compression substantially isothermal. Introducing the heat-transfer liquid into the gas prior to and/or during compression may include or consist essentially of spraying the thermally conditioned heat-transfer liquid into the gas. Introducing the heat-transfer liquid into the gas prior to and/or during compression may form a foam including or consisting essentially of the heat-transfer liquid and the gas. At least a portion of the foam may be separated into gas and heat-transfer liquid before transferring the heat-transfer liquid at the second temperature to the compressed-gas store and/or a second thermal well discrete from the first thermal well. Waste thermal energy produced by the power unit may be stored in the second thermal well. Thermal energy may be exchanged between the surrounding environment and the first thermal well and/or the second thermal well. Thermal energy may be exchanged with the surrounding environment while the power unit is neither compressing nor expanding.

These and other objects, along with advantages and features of the invention, will become more apparent through reference to the following description, the accompanying drawings, and the claims. Furthermore, it is to be understood that the features of the various embodiments described herein are not mutually exclusive and can exist in various combinations and permutations. Note that as used herein, the terms "pipe," "piping" and the like shall refer to one or more conduits that are rated to carry gas or liquid between two points. Thus, the singular term should be taken to include a plurality of parallel conduits where appropriate. Herein, the terms "liquid" and "water" interchangeably connote any mostly or

substantially incompressible liquid, the terms "gas" and "air" are used interchangeably, and the term "fluid" may refer to a liquid, a gas, or a mixture of liquid and gas (e.g., a foam) unless otherwise indicated. As used herein unless otherwise indicated, the terms "approximately" and "substantially" mean $\pm 10\%$, and, in some embodiments, $\pm 5\%$. A "valve" is any mechanism or component for controlling fluid communication between fluid paths or reservoirs, or for selectively permitting control or venting. The term "cylinder" refers to a chamber, of uniform but not necessarily circular cross-section, which may contain a slidably disposed piston or other mechanism that separates the fluid on one side of the chamber from that on the other, preventing fluid movement from one side of the chamber to the other while allowing the transfer of force/pressure from one side of the chamber to the next or to a mechanism outside the chamber. At least one of the two ends of a chamber may be closed by end caps, also herein termed "heads." As utilized herein, an "end cap" is not necessarily a component distinct or separable from the remaining portion of the cylinder, but may refer to an end portion of the cylinder itself. Rods, valves, and other devices may pass through the end caps. A "cylinder assembly" may be a simple cylinder or include multiple cylinders, and may or may not have additional associated components (such as mechanical linkages among the cylinders). The shaft of a cylinder may be coupled hydraulically or mechanically to a mechanical load (e.g., a hydraulic motor/pump or a crankshaft) that is in turn coupled to an electrical load (e.g., rotary or linear electric motor/generator attached to power electronics and/or directly to the grid or other loads), as described in the '678 and '842 patents. As used herein, "thermal conditioning" of a heat-exchange fluid does not include any modification of the temperature of the heat-exchange fluid resulting from interaction with gas with which the heat-exchange fluid is exchanging thermal energy; rather, such thermal conditioning generally refers to the modification of the temperature of the heat-exchange fluid by other means (e.g., an external heat exchanger). The terms "heat-exchange" and "heat-transfer" are generally utilized interchangeably herein. Unless otherwise indicated, motor/pumps described herein are not required to be configured to function both as a motor and a pump if they are utilized during system operation only as a motor or a pump but not both. Gas expansions described herein may be performed in the absence of combustion (as opposed to the operation of an internal-combustion cylinder, for example).

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, like reference characters generally refer to the same parts throughout the different views. Cylinders, rods, and other components are depicted in cross section in a manner that will be intelligible to all persons familiar with the art of pneumatic and hydraulic cylinders. Also, the drawings are not necessarily to scale, emphasis instead generally being placed upon illustrating the principles of the invention. In the following description, various embodiments of the present invention are described with reference to the following drawings, in which:

FIG. 1 is a schematic drawing of a compressed-gas energy storage system in accordance with various embodiments of the invention;

FIG. 2 is a schematic drawing of various components of a compressed-gas energy storage system in accordance with various embodiments of the invention;

FIG. 3 is a schematic drawing of the major components of a compressed air energy storage and recovery system in accordance with various embodiments of the invention;

FIG. 4 is a schematic drawing of various components of a multi-cylinder compressed-gas energy storage system in accordance with various embodiments of the invention;

FIG. 5 is a schematic drawing of a cylinder assembly with apparatus for the generation of foam external to the cylinder in accordance with various embodiments of the invention;

FIG. 6 is a schematic drawing of a cylinder assembly with apparatus for the generation of foam external to the cylinder and provision for bypassing the foam-generating apparatus in accordance with various embodiments of the invention;

FIG. 7 is a schematic drawing of a cylinder assembly with apparatus for the generation of foam in a vessel external to the cylinder in accordance with various embodiments of the invention;

FIG. 8 is a schematic drawing of a cylinder assembly with apparatus for the generation of foam internal to the cylinder in accordance with various embodiments of the invention;

FIG. 9 is a schematic drawing of a cylinder assembly having two cylinders and apparatus for the generation and separation of foam external to the cylinders in accordance with various embodiments of the invention;

FIG. 10 is a graph of experimental data on the energetic performance of droplet sprays in isothermal gas expansions in accordance with various embodiments of the invention;

FIG. 11 is a graph of experimental data on the energetic performance of foam in isothermal gas expansions in accordance with various embodiments of the invention;

FIG. 12 is a graph of experimental data on the energetic performance of droplet sprays in isothermal gas compressions in accordance with various embodiments of the invention;

FIG. 13 is a graph of experimental data on the energetic performance of foam in isothermal gas compressions in accordance with various embodiments of the invention;

FIG. 14 is a graph of spray pressures calculated for two methods of introducing a foaming liquid into a cylinder during a compression cycle in accordance with various embodiments of the invention;

FIG. 15 is a graph of final liquid temperatures calculated for compressions over a range of heat-exchange foam mass ratios and final compression pressures in accordance with various embodiments of the invention;

FIG. 16 is a graph of the additional storage space calculated as required for a range of heat-exchange foam mass ratios in accordance with various embodiments of the invention;

FIG. 17 is a plot of experimental data on the isothermal efficiencies of a gas-expansion compressions using a foam in accordance with various embodiments of the invention, compared to the isothermal efficiencies of similar compressions with non-foaming spray;

FIG. 18 is a schematic drawing of a cylinder assembly having two cylinders and apparatus for the generation and separation of foams having three different mass ratios in accordance with various embodiments of the invention;

FIG. 19 is a schematic drawing of an apparatus for the generation of foam having a relatively low mass ratio in accordance with various embodiments of the invention;

FIG. 20 is a schematic drawing of an apparatus for the generation and separation of foam having a relatively high mass ratio in accordance with various embodiments of the invention;

FIG. 21 is a schematic drawing of an apparatus for the generation of foam having a relatively low mass ratio in accordance with various embodiments of the invention;

FIG. 22 is a schematic drawing of an apparatus for the generation of foam having an intermediate mass ratio in accordance with various embodiments of the invention;

FIG. 23 is a schematic drawing of various components of a compressed-gas energy storage system in accordance with various embodiments of the invention;

FIGS. 24A and 24B are schematic drawings of various components of a pneumatic cylinder additionally functional as a liquid pump in accordance with various embodiments of the invention;

FIG. 25 is a schematic drawing of various components of a compressed-gas energy storage system employing two pneumatic cylinders additionally functional as liquid pumps in accordance with various embodiments of the invention;

FIG. 26 is a schematic drawing of two poppet valves in a cylinder head in accordance with various embodiments of the invention;

FIG. 27 is a schematic drawing of various components of a compressed-gas energy storage system in accordance with various embodiments of the invention;

FIG. 28 is a schematic drawing of various components of a compressed-gas energy storage system, accompanied by a graph showing selected time and temperature relationships within the system, in accordance with various embodiments of the invention;

FIG. 29 is a schematic drawing of various components of a compressed-gas energy storage system in accordance with various embodiments of the invention;

FIG. 30 is a schematic drawing of compressed-gas storage vessels with an external heat exchanger in accordance with various embodiments of the invention;

FIG. 31 is a schematic drawing of compressed-gas storage vessels with internal heat exchange in accordance with various embodiments of the invention;

FIG. 32 is a schematic drawing of compressed-gas storage vessels warmed or cooled by a fluid circulating around them in accordance with various embodiments of the invention;

FIG. 33 is a schematic drawing of compressed-gas storage vessels warmed or cooled by a liquid circulating around them in accordance with various embodiments of the invention;

FIG. 34 is a schematic drawing of a cavern storing compressed gas and heat-exchange liquid, with external heat exchange in accordance with various embodiments of the invention;

FIG. 35 is a schematic of various components of an energy storage and recovery system in accordance with various embodiments of the invention, illustrating an application where waste heat from a power plant is used to heat stored compressed gas prior to and/or during expansion in the system;

FIGS. 36 and 37 are schematic drawings of energy storage and recovery systems incorporating a cylinder assembly and one or more expanders, compressors, or expander/compressors in accordance with various embodiments of the invention;

FIG. 38 is a schematic drawing of a booster pump equipped for the formation of foam therewithin in accordance with various embodiments of the invention;

FIGS. 39-44 are schematic drawings of various systems featuring cylinder assemblies for expansion and/or compression of gas, as well as one or more thermal wells, in accordance with various embodiments of the invention;

FIGS. 45 and 46 are schematics of various components of energy storage and recovery systems in which high-power, short-duration energy storage devices are connected in parallel with a compressed-gas energy storage system, in accordance with various embodiments of the invention;

FIG. 47 is an illustrative plot of electricity supply and demand for an exemplary 24-hour period;

FIG. 48 is an illustrative plot of the response of a combined high-power, short-duration energy storage device and compressed-gas energy storage system, in accordance with various embodiments of the invention, on electricity supply and demand for the 24-hour period of FIG. 47;

FIG. 49 is an illustrative plot of the state-of-charge of a combined high-power, short-duration energy storage device and compressed gas energy storage system, in accordance with various embodiments of the invention, for the 24-hour period of FIG. 47; and

FIG. 50 is a conceptual drawing of an illustrative power generation and consumption network or grid in accordance with various embodiments of the invention.

DETAILED DESCRIPTION

FIG. 1 depicts an illustrative system 100 that may be part of a larger system, not otherwise depicted, for the storage and release of energy. Subsequent figures will clarify the application of embodiments of the invention to such a system. The system 100 depicted in FIG. 1 features an assembly 101 for compressing and expanding gas. Expansion/compression assembly 101 may include or consist essentially of either one or more individual devices for expanding or compressing gas (e.g., turbines or cylinder assemblies that each may house a moveable boundary mechanism) or a staged series of such devices, as well as ancillary devices (e.g., valves) not depicted explicitly in FIG. 1.

An electric motor/generator 102 (e.g., a rotary or linear electric machine) is in physical communication (e.g., via hydraulic pump, piston shaft, or mechanical crankshaft) with the expansion/compression assembly 101. The motor/generator 102 may be electrically connected to a source and/or sink of electric energy not explicitly depicted in FIG. 1 (e.g., an electrical distribution grid or a source of renewable energy such as one or more wind turbines or solar cells).

The expansion/compression assembly 101 may be in fluid communication with a heat-transfer subsystem 104 that alters the temperature and/or pressure of a fluid (i.e., gas, liquid, or gas-liquid mixture such as a foam) extracted from expansion/compression assembly 101 and, after alteration of the fluid's temperature and/or pressure, returns at least a portion of it to expansion/compression assembly 101. Heat-transfer subsystem 104 may include pumps, valves, and other devices (not depicted explicitly in FIG. 1) ancillary to its heat-transfer function and to the transfer of fluid to and from expansion/compression assembly 101. Operated appropriately, the heat-transfer subsystem 104 enables substantially isothermal compression and/or expansion of gas inside expansion/compression assembly 101.

Connected to the expansion/compression assembly 101 is a pipe 106 with a control valve 108 that controls a flow of fluid (e.g., gas) between assembly 101 and a storage reservoir 112 (e.g., one or more pressure vessels, pipes, and/or caverns). The storage reservoir 112 may be in fluid communication with a heat-transfer subsystem 114 that alters the temperature and/or pressure of fluid removed from storage reservoir 112 and, after alteration of the fluid's temperature and/or pressure, returns it to storage reservoir 112. A second pipe 116 with a control valve 118 may be in fluid communication with the expansion/compression assembly 101 and with a vent 120 that communicates with a body of gas at relatively low pressure (e.g., the ambient atmosphere).

A control system 122 receives information inputs from any of expansion/compression assembly 101, storage reservoir 112, and other components of system 100 and sources external to system 100. These information inputs may include or

consist essentially of pressure, temperature, and/or other telemetered measurements of properties of components of system 101. Such information inputs, here generically denoted by the letter "T," are transmitted to control system 122 either wirelessly or through wires. Such transmission is denoted in FIG. 1 by dotted lines 124, 126.

The control system 122 may selectively control valves 108 and 118 to enable substantially isothermal compression and/or expansion of a gas in assembly 101. Control signals, here generically denoted by the letter "C," are transmitted to valves 108 and 118 either wirelessly or through wires. Such transmission is denoted in FIG. 1 by dashed lines 128, 130. The control system 122 may also control the operation of the heat-transfer assemblies 104, 114 and of other components not explicitly depicted in FIG. 1. The transmission of control and telemetry signals for these purposes is not explicitly depicted in FIG. 1.

The control system 122 may be any acceptable control device with a human-machine interface. For example, the control system 122 may include a computer (for example a PC-type) that executes a stored control application in the form of a computer-readable software medium. More generally, control system 122 may be realized as software, hardware, or some combination thereof. For example, control system 122 may be implemented on one or more computers, such as a PC having a CPU board containing one or more processors such as the Pentium, Core, Atom, or Celeron family of processors manufactured by Intel Corporation of Santa Clara, Calif., the 680x0 and POWER PC family of processors manufactured by Motorola Corporation of Schaumburg, Ill., and/or the ATHLON line of processors manufactured by Advanced Micro Devices, Inc., of Sunnyvale, Calif. The processor may also include a main memory unit for storing programs and/or data relating to the methods described above. The memory may include random access memory (RAM), read only memory (ROM), and/or FLASH memory residing on commonly available hardware such as one or more application specific integrated circuits (ASIC), field programmable gate arrays (FPGA), electrically erasable programmable read-only memories (EEPROM), programmable read-only memories (PROM), programmable logic devices (PLD), or read-only memory devices (ROM). In some embodiments, the programs may be provided using external RAM and/or ROM such as optical disks, magnetic disks, or other storage devices.

For embodiments in which the functions of controller 122 are provided by software, the program may be written in any one of a number of high-level languages such as FORTRAN, PASCAL, JAVA, C, C++, C#, LISP, PERL, BASIC or any suitable programming language. Additionally, the software can be implemented in an assembly language and/or machine language directed to the microprocessor resident on a target device.

As described above, the control system 122 may receive telemetry from sensors monitoring various aspects of the operation of system 100, and may provide signals to control valve actuators, valves, motors, and other electromechanical/electronic devices. Control system 122 may communicate with such sensors and/or other components of system 100 (and other embodiments described herein) via wired or wireless communication. An appropriate interface may be used to convert data from sensors into a form readable by the control system 122 (such as RS-232 or network-based interconnects). Likewise, the interface converts the computer's control signals into a form usable by valves and other actuators to perform an operation. The provision of such interfaces, as

well as suitable control programming, is clear to those of ordinary skill in the art and may be provided without undue experimentation.

System **100** may be operated so as to compress gas admitted through the vent **120** and store the gas thus compressed in reservoir **112**. For example, in an initial state of operation, valve **108** is closed and valve **118** is open, admitting a quantity of gas into expansion/compression assembly **101**. When a desired quantity of gas has been admitted into assembly **101**, valve **118** may be closed. The motor/generator **102**, employing energy supplied by a source not explicitly depicted in FIG. **1** (e.g., the electrical grid), then provides mechanical power to expansion/compression assembly **101**, enabling the gas within assembly **101** to be compressed.

During compression of the gas within assembly **101**, fluid (i.e., gas, liquid, or a gas-liquid mixture) may be circulated between assembly **101** and heat-exchange assembly **104**. Heat-exchange assembly **104** may be operated in such a manner as to enable substantially isothermal compression of the gas within assembly **101**. During or after compression of the gas within assembly **101**, valve **108** may be opened to enable high-pressure fluid (e.g., compressed gas or a mixture of liquid and compressed gas) to flow to reservoir **112**. Heat-exchange assembly **114** may be operated at any time in such a manner as alter the temperature and/or pressure of the fluid within reservoir **112**.

That system **100** may also be operated so as to expand compressed gas from reservoir **112** in expansion/compression assembly **101** in such a manner as to deliver energy to the motor/generator **102** will be apparent to all persons familiar with the operation of pneumatic, hydraulic, and electric machines.

FIG. **2** depicts an illustrative system **200** that features a cylinder assembly **201** (i.e., an embodiment of assembly **101** in FIG. **1**) in communication with a reservoir **222** (**112** in FIG. **1**) and a vent to atmosphere **223** (**120** in FIG. **1**). In the illustrative system **200** shown in FIG. **2**, the cylinder assembly **201** contains a piston **202** slidably disposed therein. In some embodiments the piston **202** is replaced by a different boundary mechanism dividing cylinder assembly **201** into multiple chambers, or piston **202** is absent entirely, and cylinder assembly **201** is a "liquid piston." The cylinder assembly **201** may be divided into, e.g., two pneumatic chambers or one pneumatic chamber and one hydraulic chamber. The piston **202** is connected to a rod **204**, which may contain a center-drilled fluid passageway with fluid outlet **212** extending from the piston **202**. The rod **204** is also attached to, e.g., a mechanical load (e.g., a crankshaft or a hydraulic system) that is not depicted. The cylinder assembly **201** is in liquid communication with a heat-transfer subsystem **224** that includes or consists essentially of a circulation pump **214** and a spray mechanism **210** to enable substantially isothermal compression/expansion of gas. Heat-transfer fluid circulated by pump **214** may be passed through a heat exchanger **203** (e.g., tube-in-shell- or parallel-plate-type heat exchanger). Spray mechanism **210** may include or consist essentially of one or more spray heads (e.g., disposed at one end of cylinder assembly **201**) and/or spray rods (e.g., extending along at least a portion of the central axis of cylinder assembly **201**). In other embodiments, the spray mechanism **210** is omitted and a foam, rather than a spray of droplets, is created to facilitate heat exchange between liquid and gas during compression and expansion of gas within the cylinder assembly **201**. Foam may be generated by foaming gas with heat-exchange liquid in a mechanism (not shown, described in more detail below) external to the cylinder assembly **201** and then injecting the resulting foam into the cylinder assembly **201**. Alternatively

or additionally, foam may be generated inside the cylinder assembly **201** by the injection of heat-exchange liquid into cylinder assembly **201** through a foam-generating mechanism (e.g., spray head, rotating blade, one or more nozzles), partly or entirely filling the pneumatic chamber of cylinder assembly **201**. In some embodiments, droplets and foams may be introduced into cylinder assembly **201** simultaneously and/or sequentially. Various embodiments may feature mechanisms (not shown in FIG. **2**) for controlling the characteristics of foam (e.g., bubble size) and for breaking down, separating, and/or regenerating foam.

System **200** further includes a first control valve **220** (**108** in FIG. **1**) in communication with a storage reservoir **222** and cylinder assembly **201**, and a second control valve **221** (**118** in FIG. **1**) in communication with a vent **223** and cylinder assembly **201**. A control system **226** (**122** in FIG. **1**) may control operation of, e.g., valves **222** and **221** based on various system inputs (e.g., pressure, temperature, piston position, and/or fluid state) from cylinder assembly **201** and/or storage reservoir **222**. Heat-transfer fluid (liquid or circulated by pump **214** enters through pipe **213**. Pipe **213** may be (a) connected to a low-pressure fluid source (e.g., fluid reservoir (not shown) at the pressure to which vent **223** is connected or thermal well **242**); (b) connected to a high-pressure source (e.g., fluid reservoir (not shown) at the pressure of reservoir **222**); (c) selectively connected (using valve arrangement not shown) to low pressure during a compression process and to high pressure during an expansion process; (d) connected to changing-pressure fluid **208** in the cylinder **201** via connection **212**; or (e) some combination of these options.

In an initial state, the cylinder assembly **201** may contain a gas **206** (e.g., air introduced to the cylinder assembly **201** via valve **221** and vent **223**) and a heat-transfer fluid **208** (which may include or consist essentially of, e.g., water or another suitable liquid). When the gas **206** enters the cylinder assembly **201**, piston **202** is operated to compress the gas **206** to an elevated pressure (e.g., approximately 3,000 psi). Heat-transfer fluid (not necessarily the identical body of heat-transfer fluid **208**) flows from pipe **213** to the pump **214**. The pump **214** may raise the pressure of the heat-exchange fluid to a pressure (e.g., up to approximately 3,015 psig) somewhat higher than the pressure within the cylinder assembly **201**, as described in the '409 application. Alternatively or in conjunction, embodiments of the invention add heat (i.e., thermal energy) to, or remove heat from, the high-pressure gas in the cylinder assembly **201** by passing only relatively low-pressure fluids through a heat exchanger or fluid reservoir, as detailed in U.S. patent application Ser. No. 13/211,440, filed Aug. 17, 2011 (the '440 application), the entire disclosure of which is incorporated by reference herein.

Heat-transfer fluid is then sent through a pipe **216**, where it may be passed through a heat exchanger **203** (where its temperature is altered) and then through a pipe **218** to the spray mechanism **210**. The heat-transfer fluid thus circulated may include or consist essentially of liquid or foam. Spray mechanism **210** may be disposed within the cylinder assembly **201**, as shown; located in the storage vessel **222** or vent **223**; or located in piping or manifolding around the cylinder assembly, such as pipe **218** or the pipes connecting the cylinder assembly to storage vessel **222** or vent **223**. The spray mechanism **210** may be operated in the vent **223** or connecting pipes during compression, and a separate spray mechanism may be operated in the storage vessel **222** or connecting pipes during expansion. Heat-transfer spray **211** from spray mechanism **210** (and/or any additional spray mechanisms), and/or foam from mechanisms internal or external to the cylinder assem-

bly **101**, enable substantially isothermal compression of gas **206** within cylinder assembly **201**.

In some embodiments, the heat exchanger **203** is configured to condition heat-transfer fluid at low pressure (e.g., a pressure lower than the maximum pressure of a compression or expansion stroke in cylinder assembly **201**), and heat-transfer fluid is thermally conditioned between strokes or only during portions of strokes, as detailed in the '440 application. Embodiments of the invention are configured for circulation of heat-transfer fluid without the use of hoses that flex during operation through the use of, e.g., tubes or straws configured for non-flexure and/or pumps (e.g., submersible bore pumps, axial flow pumps, or other in-line style pumps) internal to the cylinder assembly (e.g., at least partially disposed within the piston rod thereof), as described in U.S. patent application Ser. No. 13/234,239, filed Sep. 16, 2011 (the '239 application), the entire disclosure of which is incorporated by reference herein.

At or near the end of the compression stroke, control system **226** opens valve **220** to admit the compressed gas **206** to the storage reservoir **222**. Operation of valves **220** and **221** may be controlled by various inputs to control system **226**, such as piston position in cylinder assembly **201**, pressure in storage vessel **222**, pressure in cylinder assembly **201**, and/or temperature in cylinder assembly **201**.

As mentioned above, the control system **226** may enforce substantially isothermal operation, i.e., expansion and/or compression of gas in cylinder assembly **201**, via control over, e.g., the introduction of gas into and the exhausting of gas out of cylinder assembly **201**, the rates of compression and/or expansion, and/or the operation of the heat-exchange subsystem in response to sensed conditions. For example, control system **226** may be responsive to one or more sensors disposed in or on cylinder assembly **201** for measuring the temperature of the gas and/or the heat-exchange fluid within cylinder assembly **201**, responding to deviations in temperature by issuing control signals that operate one or more of the system components noted above to compensate, in real time, for the sensed temperature deviations. For example, in response to a temperature increase within cylinder assembly **201**, control system **226** may issue commands to increase the flow rate of spray **211** of heat-exchange fluid **208**.

Furthermore, embodiments of the invention may be applied to systems in which cylinder assembly **201** (or a chamber thereof) is in fluid communication with a pneumatic chamber of a second cylinder (e.g., as shown in FIG. 4). That second cylinder, in turn, may communicate similarly with a third cylinder, and so forth. Any number of cylinders may be linked in this way. These cylinders may be connected in parallel or in a series configuration, where the compression and expansion is done in multiple stages.

The fluid circuit of heat exchanger **203** may be filled with water, a coolant mixture, an aqueous foam, or any other acceptable heat-exchange medium. In alternative embodiments, a gas, such as air or refrigerant, is used as the heat-exchange medium. In general, the fluid is routed by conduits to a large reservoir of such fluid in a closed or open loop. One example of an open loop is a well or body of water from which ambient water is drawn and the exhaust water is delivered to a different location, for example, downstream in a river. In a closed-loop embodiment, a cooling tower may cycle the water through the air for return to the heat exchanger. Likewise, water may pass through a submerged or buried coil of continuous piping where a counter heat-exchange occurs to return the fluid flow to ambient temperature before it returns to the heat exchanger for another cycle.

In various embodiments, the heat-exchange fluid is conditioned (i.e., pre-heated and/or pre-chilled) or used for heating or cooling needs by connecting the fluid inlet **238** and fluid outlet **240** of the external heat-exchange side of the heat exchanger **203** to an installation such as a heat-engine power plant, an industrial process with waste heat, a heat pump, and/or a building needing space heating or cooling, as described in the '731 patent. Alternatively, the external heat-exchange side of the heat exchanger **203** may be connected to a thermal well **242** as depicted in FIG. 2. The thermal well **242** may include or consist essentially of a large water reservoir that acts as a constant-temperature thermal fluid source for use with the system. Alternatively, the water reservoir may be thermally linked to waste heat from an industrial process or the like, as described above, via another heat exchanger contained within the installation. This allows the heat-exchange fluid to acquire or expel heat from/to the linked process, depending on configuration, for later use as a heating/cooling medium in the energy storage/conversion system. Alternatively, the thermal well **242** may include two or more bodies of energy-storage medium, e.g., a hot-water thermal well and a cold-water thermal well, that are typically maintained in contrasting energy states in order to increase the energy of system **200** compared with a system in which thermal well **242** includes a single body of energy-storage medium. Storage media other than water may be utilized in the thermal well **242**; temperature changes, phase changes, or both may be employed by storage media of thermal well **242** to store and release energy. Thermal or fluid links (not shown) to the atmosphere, ground, and/or other components of the environment may also be included in system **200**, allowing mass, thermal energy, or both to be added to or removed from the thermal well **242**. Moreover, as depicted in FIG. 2, the heat-transfer subsystem **224** does not interchange fluid directly with the thermal well **242**, but in other embodiments, fluid is passed directly between the heat-transfer subsystem **224** and the thermal well **242** with no heat exchanger maintaining separation between fluids.

FIG. 3 is a schematic of the major components of an illustrative system **300** that employs a pneumatic cylinder **302** to efficiently convert (i.e., store) mechanical energy into the potential energy of compressed gas and, in another mode of operation, efficiently convert (i.e., recover) the potential energy of compressed gas into mechanical work. The pneumatic cylinder **302** may contain a slidably disposed piston **304** that divides the interior of the cylinder **302** into a distal chamber **306** and a proximal chamber **308**. A port or ports (not shown) with associated pipes **312** and a bidirectional valve **316** enables gas from a high-pressure storage reservoir **320** to be admitted to chamber **306** as desired. A port or ports (not shown) with associated pipes **322** and a bidirectional valve **324** enables gas from the chamber **306** to be exhausted through a vent **326** to the ambient atmosphere as desired. In alternate embodiments, vent **326** is replaced by additional lower-pressure pneumatic cylinders (or pneumatic chambers of cylinders). A port or ports (not shown) enables the interior of the chamber **308** to communicate freely at all times with the ambient atmosphere. In alternate embodiments, cylinder **302** is double-acting and chamber **308** is, like chamber **306**, equipped to admit and exhaust fluids in various states of operation. The distal end of a rod **330** is coupled to the piston **304**. The rod **330** may be connected to a crankshaft, hydraulic cylinder, or other mechanisms for converting linear mechanical motion to useful work as described in the '678 and '842 patents.

In the energy recovery or expansion mode of operation, storage reservoir **320** is filled with high-pressure air (or other

gas) **332** and a quantity of heat-transfer fluid **334**. The heat-transfer fluid **334** may be an aqueous foam or a liquid that tends to foam when sprayed or otherwise acted upon. The liquid component of the aqueous foam, or the liquid that tends to foam, may include or consist essentially of water with 2% to 5% of certain additives; these additives may also provide functions of anti-corrosion, anti-wear (lubricity), anti-bio-growth (biocide), freezing-point modification (anti-freeze), and/or surface-tension modification. Additives may include a micro-emulsion of a lubricating fluid such as mineral oil, a solution of agents such as glycols (e.g. propylene glycol), or soluble synthetics (e.g. ethanolamines). Such additives tend to reduce liquid surface tension and lead to substantial foaming when sprayed. Commercially available fluids may be used at an approximately 5% solution in water, such as Mecagreen 127 (available from the Condat Corporation of Michigan), which consists in part of a micro-emulsion of mineral oil, and Quintolubric 807-WP (available from the Quaker Chemical Corporation of Pennsylvania), which consists in part of a soluble ethanolamine. Other additives may be used at higher concentrations (such as at a 50% solution in water), including Cryo-tek 100/Al (available from the Hercules Chemical Company of New Jersey), which consists in part of a propylene glycol. These fluids may be further modified to enhance foaming while being sprayed and to speed defoaming when in a reservoir.

The heat-transfer fluid **334** may be circulated within the storage reservoir **320** via high-inlet-pressure, low-power-consumption pump **336** (such as described in the '731 patent). In various embodiments, the fluid **334** may be removed from the bottom of the storage reservoir **320** via piping **338**, circulated via pump **336** through a heat exchanger **340**, and introduced (e.g., sprayed) back into the top of storage reservoir **320** via piping **342** and spray head **344** (or other suitable mechanism). Any changes in pressure within reservoir **320** due to removal or addition of gas (e.g., via pipe **312**) generally tend to result in changes in temperature of the gas **332** within reservoir **320**. By spraying and/or foaming the fluid **334** throughout the storage reservoir gas **332**, heat may be added to or removed from the gas **332** via heat exchange with the heat-transfer fluid **334**. By circulating the heat-transfer fluid **334** through heat exchanger **340**, the temperature of the fluid **334** and gas **332** may be kept substantially constant (i.e., isothermal). Counterflow heat-exchange fluid **346** at near-ambient pressure may be circulated from a near-ambient-temperature thermal well (not shown) or source (e.g., waste heat source) or sink (e.g., cold water source) of thermal energy, as described in more detail below.

In various embodiments of the invention, reservoir **320** contains an aqueous foam, either unseparated or partially separated into its gaseous and liquid components. In such embodiments, pump **336** may circulate either the foam itself, or the separated liquid component of the foam, or both, and recirculation of fluid into reservoir **320** may include regeneration of foam by apparatus not shown in FIG. 3.

In the energy recovery or expansion mode of operation, a quantity of gas may be introduced via valve **316** and pipe **312** into the upper chamber **306** of cylinder **302** when piston **304** is near or at the top of its stroke (i.e., "top dead center" of cylinder **302**). The piston **304** and its rod **330** will then be moving downward (the cylinder **302** may be oriented arbitrarily but is shown vertically oriented in this illustrative embodiment). Heat-exchange fluid **334** may be introduced into chamber **306** concurrently via optional pump **350** (alternatively, a pressure drop may be introduced in line **312** such that pump **350** is not needed) through pipe **352** and directional valve **354**. This heat-exchange fluid **334** may be sprayed into

chamber **306** via one or more spray nozzles **356** in such a manner as to generate foam **360**. (In some embodiments, foam **360** is introduced directly into chamber **306** in foam form.) The foam **360** may entirely fill the entire chamber **306**, but is shown in FIG. 3, for illustrative purposes only, as only partially filling chamber **306**. Herein, the term "foam" denotes either (a) foam only or (b) any of a variety of mixtures of foam and heat-exchange liquid in other, non-foaming states (e.g., droplets). Moreover, some non-foamed liquid (not shown) may accumulate at the bottom of chamber **306**; any such liquid is generally included in references herein to the foam **360** within chamber **306**.

System **300** is instrumented with pressure, piston position, and/or temperature sensors (not shown) and controlled via control system **362**. At a predetermined position of piston **304**, an amount of gas **332** and heat-transfer fluid **334** have been admitted into chamber **306** and valve **316** and valve **354** are closed. (Valves **316** and **354** may close at the same time or at different times, as each has a control value based on quantity of fluid desired.) The gas in chamber **306** then undergoes free expansion, continuing to drive piston **304** downward. During this expansion, in the absence of foam **360**, the gas would tend to decrease substantially in temperature. With foam **360** largely or entirely filling the chamber, the temperature of the gas in chamber **306** and the temperature of the heat-transfer fluid **360** tend to approximate to each other via heat exchange. The heat capacity of the liquid component of the foam **360** (e.g., water with one or more additives) may be much higher than that of the gas (e.g., air) such that the temperature of the gas and liquid do not change substantially (i.e., are substantially isothermal) even over a many-times gas expansion (e.g., from 250 psig to near atmospheric pressure, or in other embodiments from 3,000 psig to 250 psig).

When the piston **304** reaches the end of its stroke (bottom dead center), the gas within chamber **306** will have expanded to a predetermined lower pressure (e.g., near atmospheric). Valve **324** will then be opened, allowing gas from chamber **306** to be vented, whether to atmosphere through pipe **322** and vent **326** (as illustrated here) or, in other embodiments, to a next stage in the expansion process (e.g., chamber in a separate cylinder), via pipe **322**. Valve **324** remains open as the piston undergoes an upward (i.e., return) stroke, emptying chamber **306**. Part or substantially all of foam **360** is also forced out of chamber **306** via pipe **322**. A separator (not shown) or other means such as gravity separation is used to recover heat-transfer fluid, preferably de-foamed (i.e., as a simple liquid with or without additives), and to direct it into a storage reservoir **364** via pipe **366**.

When piston **304** reaches top of stroke again, the process repeats with gas **332** and heat-transfer fluid **334** admitted from vessel **320** via valves **316** and **354**. If additional heat-transfer fluid is needed in reservoir **320**, it may be pumped back into reservoir **320** from reservoir **364** via piping **367** and optional pump/motor **368**. In one mode of operation, pump **368** may be used to continuously refill reservoir **320** such that the pressure in reservoir **320** is held substantially constant. That is, as gas is removed from reservoir **320**, heat-transfer fluid **334** is added to maintain constant pressure in reservoir **320**. In other embodiments, pump **368** is not used or is used intermittently, the pressure in reservoir **320** continues to decrease during an energy-recovery process (i.e., involving removal of gas from reservoir **320**), and the control system **362** changes the timing of valves **316** and **354** accordingly so as to reach approximately the same ending pressure when the piston **304** reaches the end of its stroke. An energy-recovery process may continue until the storage reservoir **320** is nearly empty of pressurized gas **332**, at which time an energy-stor-

age process may be used to recharge the storage reservoir **320** with pressurized gas **332**. In other embodiments, the energy-recovery and energy-storage processes are alternated based on operator requirements.

In either the energy-storage or energy-compression mode of operation, storage reservoir **320** is typically at least partially depleted of high-pressure gas **332**, as storage reservoir **320** also typically contains a quantity of heat-transfer fluid **334**. Reservoir **364** is at low pressure (e.g., atmospheric or some other low pressure that serves as the intake pressure for the compression phase of cylinder **302**) and contains a quantity of heat-transfer fluid **370**.

The heat-transfer fluid **370** may be circulated within the reservoir **364** via low-power-consumption pump **372**. In various embodiments, the fluid **370** may be removed from the bottom of the reservoir **364** via piping **367**, circulated via pump **372** through a heat exchanger **374**, and introduced (e.g., sprayed) back into the top of reservoir **364** via piping **376** and spray head **378** (or other suitable mechanism). By spraying the fluid **370** throughout the reservoir gas **380**, heat may be added or removed from the gas via the heat-transfer fluid **370**. By circulating the heat-transfer fluid **370** through heat exchanger **374**, the temperature of the fluid **370** and gas **380** may be kept near constant (i.e., isothermal). Counterflow heat-exchange fluid **382** at near-ambient pressure may be circulated from a near-ambient-temperature thermal well (not shown) or source (e.g., waste heat source) or sink (e.g., cold water source) of thermal energy. In one embodiment, counterflow heat-exchange fluid **382** is at high temperature to increase energy recovery during expansion and/or counterflow heat-exchange fluid **382** is at low temperature to decrease energy usage during compression.

In the energy-storage or compression mode of operation, a quantity of low-pressure gas is introduced via valve **324** and pipe **322** into the upper chamber **306** of cylinder **302** starting when piston **304** is near top dead center of cylinder **302**. The low-pressure gas may be from the ambient atmosphere (e.g., may be admitted through vent **326** as illustrated herein) or may be from a source of pressurized gas such as a previous compression stage. During the intake stroke, the piston **304** and its rod **330** will move downward, drawing in gas. Heat-exchange fluid **370** may be introduced into chamber **306** concurrently via optional pump **384** (alternatively, a pressure drop may be introduced in line **386** such that pump **384** is not needed) through pipe **386** and directional valve **388**. This heat exchange fluid **370** may be introduced (e.g., sprayed) into chamber **306** via one or more spray nozzles **390** in such a manner as to generate foam **360**. This foam **360** may fill the chamber **306** partially or entirely by the end of the intake stroke; for illustrative purposes only, foam **360** is shown in FIG. 3 as only partially filling chamber **306**. At the end of the intake stroke, piston **304** reaches the end-of-stroke position (bottom dead center) and chamber **306** is filled with foam **360** generated from air at a low pressure (e.g., atmospheric) and heat-exchange liquid.

At the end of the stroke, with piston **304** at the end-of-stroke position, valve **324** is closed. Valve **388** is also closed, not necessarily at the same time as valve **324**, but after a predetermined amount of heat-transfer fluid **370** has been admitted, creating foam **360**. The amount of heat-transfer fluid **370** may be based upon the volume of air to be compressed, the ratio of compression, and/or the heat capacity of the heat-transfer fluid. Next, piston **304** and rod **330** are driven upwards via mechanical means (e.g., hydraulic fluid, hydraulic cylinder, mechanical crankshaft) to compress the gas within chamber **306**.

During this compression, in the absence of foam **360**, the gas in chamber **306** would tend to increase substantially in temperature. With foam **360** at least partially filling the chamber, the temperature of the gas in chamber **306** and the temperature of the liquid component of foam **360** will tend to equilibrate via heat exchange. The heat capacity of the fluid component of foam **360** (e.g., water with one or more additives) may be much higher than that of the gas (e.g., air) such that the temperature of the gas and fluid do not change substantially and are near-isothermal even over a many-times gas compression (e.g., from near atmospheric pressure to 250 psig, or in other embodiments from 250 psig to 3,000 psig).

The gas in chamber **306** (which includes, or consists essentially of, the gaseous component of foam **360**) is compressed to a suitable pressure, e.g., a pressure approximately equal to the pressure within storage reservoir **320**, at which time valve **316** is opened. The foam **360**, including both its gaseous and liquid components, is then transferred into storage reservoir **320** through valve **316** and pipe **312** by continued upward movement of piston **304** and rod **330**.

When piston **304** reaches top of stroke again, the process repeats, with low-pressure gas and heat-transfer fluid **370** admitted from vent **326** and reservoir **364** via valves **324** and **388**. If additional heat-transfer fluid is needed in reservoir **364**, it may be returned to reservoir **364** from reservoir **320** via piping **367** and optional pump/motor **368**. Power recovered from motor **368** may be used to help drive the mechanical mechanism for driving piston **304** and rod **330** or may be converted to electrical power via an electric motor/generator (not shown). In one mode of operation, motor **368** may be run continuously, while reservoir **320** is being filled with gas, in such a manner that the pressure in reservoir **320** is held substantially constant. That is, as gas is added to reservoir **320**, heat-transfer fluid **334** is removed from reservoir **320** to maintain substantially constant pressure within reservoir **320**. In other embodiments, motor **368** is not used or is used intermittently; the pressure in reservoir **320** continues to increase during an energy-storage process and the control system **362** changes the timing of valves **316** and **388** accordingly so that the desired ending pressure (e.g., atmospheric) is attained within chamber **306** when the piston **304** reaches bottom of stroke. An energy-storage process may continue until the storage reservoir **320** is full of pressurized gas **332** at the maximum storage pressure (e.g., 3,000 psig), after which time the system is ready to perform an energy-recovery process. In various embodiments, the system may commence an energy-recovery process when the storage reservoir **320** is only partly full of pressurized gas **332**, whether at the maximum storage pressure or at some storage pressure intermediate between atmospheric pressure and the maximum storage pressure. In other embodiments, the energy-recovery and energy-storage processes are alternated based on operator requirements.

FIG. 4 depicts an illustrative system **400** that features at least two cylinder assemblies **402**, **406** (i.e., an embodiment of assembly **101** in FIG. 1; e.g., cylinder assembly **201** in FIG. 2) and a heat-transfer subsystem **404**, **408** (e.g., subsystem **224** in FIG. 2) associated with each cylinder assembly **402**, **406**. Additionally, the system includes a thermal well **410** (e.g., thermal well **242** in FIG. 2) which may be associated with either or both of the heat-transfer subsystems **404**, **408** as indicated by the dashed lines.

Assembly **402** is in selective fluid communication with a storage reservoir **412** (e.g., **112** in FIG. 1, **222** in FIG. 2) capable of holding fluid at relatively high pressure (e.g., approximately 3,000 psig). Assembly **406** is in selective fluid communication with assembly **402** and/or with optional addi-

tional cylinder assemblies between assemblies **402** and **406** as indicated by ellipsis marks **422**. Assembly **406** is in selective fluid communication with an atmospheric vent **420** (e.g., **120** in FIG. 1, **223** in FIG. 2).

System **400** may compress air at atmospheric pressure (admitted to system **400** through the vent **420**) stagewise through assemblies **406** and **402** to high pressure for storage in reservoir **412**. System **400** may also expand air from high pressure in reservoir **412** stagewise through assemblies **402** and **406** to a low pressure (e.g., approximately 5 psig) for venting to the atmosphere through vent **420**.

As described in U.S. patent application Ser. No. 13/080,914, filed Apr. 6, 2011 (the '914 application), the entire disclosure of which is incorporated by reference herein, in a group of N cylinder assemblies used for expansion or compression of gas between a high pressure (e.g., approximately 3,000 psig) and a low pressure (e.g., approximately 5 psig), the system will contain gas at N-1 pressures intermediate between the high-pressure extreme and the low pressure. Herein each such intermediate pressure is termed a "mid-pressure." In illustrative system **400**, N=2 and N-1=1, so there is one mid-pressure (e.g., approximately 250 psig during expansion) in the system **400**. In various states of operation of the system, mid-pressures may occur in any of the chambers of a series-connected cylinder group (e.g., the cylinders of assemblies **402** and **406**) and within any valves, piping, and other devices in fluid communication with those chambers. In illustrative system **400**, the mid-pressure, herein denoted "mid-pressure P1," occurs primarily in valves, piping, and other devices intermediate between assemblies **402** and **406**.

Assembly **402** is a high-pressure assembly: i.e., assembly **402** may admit gas at high pressure from reservoir **412** to expand the gas to mid-pressure P1 for transfer to assembly **402**, and/or may admit gas at mid-pressure P1 from assembly **406** to compress the gas to high pressure for transfer to reservoir **412**. Assembly **406** is a low-pressure assembly: i.e., assembly **406** may admit gas at mid-pressure P1 from assembly **402** to expand the gas to low pressure for transfer to the vent **420**, and/or may admit gas at low pressure from vent **420** to compress the gas to mid-pressure P1 for transfer to assembly **402**.

In system **400**, extended cylinder assembly **402** communicates with extended cylinder assembly **406** via a mid-pressure assembly **414**. Herein, a "mid-pressure assembly" includes or consists essentially of a reservoir of gas that is placed in fluid communication with the valves, piping, chambers, and other components through or into which gas passes. The gas in the reservoir is at approximately at the mid-pressure which the particular mid-pressure assembly is intended to provide. The reservoir is large enough so that a volume of mid-pressure gas approximately equal to that within the valves, piping, chambers, and other components with which the reservoir is in fluid communication may enter or leave the reservoir without substantially changing its pressure. Additionally, the mid-pressure assembly may provide pulsation damping, additional heat-transfer capability, fluid separation, and/or house one or more heat-transfer sub-systems such as part or all of sub-systems **404** and/or **408**. As described in the '914 application, a mid-pressure assembly may substantially reduce the amount of dead space in various components of a system employing pneumatic cylinder assemblies, e.g., system **400** in FIG. 4. Reduction of dead space tends to increase overall system efficiency.

Alternatively or in conjunction, pipes and valves (not shown in FIG. 4) bypassing mid-pressure assembly **414** may enable fluid to pass directly between assembly **402** and

assembly **406**. Valves **416**, **418**, **424**, and **426** control the passage of fluids between the assemblies **402**, **406**, **412**, and **414**.

A control system **428** (e.g., **122** in FIG. 1, **226** in FIG. 2, **362** in FIG. 3) may control operation of, e.g., all valves of system **400** based on various system inputs (e.g., pressure, temperature, piston position, and/or fluid state) from assemblies **402** and **406**, mid-pressure assembly **414**, storage reservoir **412**, thermal well **410**, heat transfer sub-systems **404**, **408**, and/or the environment surrounding system **420**.

It will be clear to persons reasonably familiar with the art of pneumatic machines that a system similar to system **400** but differing by the incorporation of one, two or more mid-pressure extended cylinder assemblies may be devised without additional undue experimentation. It will also be clear that all remarks herein pertaining to system **400** may be applied to such an N-cylinder system without substantial revision, as indicated by elliptical marks **422**. Such N-cylinder systems, though not discussed further herein, are contemplated and within the scope of the invention. As shown and described in the '678 patent, N appropriately sized cylinders, where $N \geq 2$, may reduce an original (single-cylinder) operating fluid pressure range R to $R^{1/N}$ and correspondingly reduce the range of force acting on each cylinder in the N-cylinder system as compared to the range of force acting in a single-cylinder system. This and other advantages, as set forth in the '678 patent, may be realized in N-cylinder systems. Additionally, multiple identical cylinders may be added in parallel and attached to a common or separate drive mechanism (not shown) with the cylinder assemblies **402**, **406** as indicated by ellipsis marks **432**, **436**, enabling higher power and air-flow rates.

FIG. 5 is a schematic diagram showing components of a system **500** for achieving approximately isothermal compression and expansion of a gas for energy storage and recovery using a pneumatic cylinder **502** (shown in partial cross-section) according to embodiments of the invention. The cylinder **502** typically contains a slideably disposed piston **504** that divides the cylinder **502** into two chambers **506**, **508**. A reservoir **510** contains gas at high pressure (e.g., 3,000 psi); the reservoir **510** may also contain a quantity of heat-exchange liquid **512**. The heat-exchange liquid **512** may contain an additive that increases the liquid's tendency to foam (e.g., by lowering the surface tension of the liquid **512**). Additives may include surfactants (e.g., sulfonates), a micro-emulsion of a lubricating fluid such as mineral oil, a solution of agents such as glycols (e.g., propylene glycol), or soluble synthetics (e.g., ethanolamines). Foaming agents such as sulfonates (e.g., linear alkyl benzene sulfonate such as Bio-Soft D-40 available from Stepan Company of Illinois) may be added, or commercially available foaming concentrates such as firefighting foam concentrates (e.g., fluorosurfactant products such as those available from ChemGuard of Texas) may be used. Such additives tend to reduce liquid surface tension of water and lead to substantial foaming when sprayed. Commercially available fluids may be used at an approximately 5% solution in water, such as Mecagreen 127 (available from the Condat Corporation of Michigan), which consists in part of a micro-emulsion of mineral oil, and Quintolubric 807-WP (available from the Quaker Chemical Corporation of Pennsylvania), which consists in part of a soluble ethanolamine. Other additives may be used at higher concentrations (such as at a 50% solution in water), including Cryo-tek 100/Al (available from the Hercules Chemical Company of New Jersey), which consists in part of a propylene glycol. These fluids may be further modified to enhance foaming while being sprayed and to speed defoaming when in a reservoir.

A pump **514** and piping **516** may convey the heat-exchange liquid to a device herein termed a “mixing chamber” (**518**). Gas from the reservoir **510** may also be conveyed (via piping **520**) to the mixing chamber **518**. Within the mixing chamber **518**, a foam-generating mechanism **522** combines the gas from the reservoir **510** and the liquid conveyed by piping **516** to create foam **524** of a certain grade (i.e., bubble size variance, average bubble size, void fraction), herein termed Foam A, inside the mixing chamber **518**.

The mixing chamber **518** may contain a screen **526** or other mechanism (e.g., source of ultrasound) to vary or homogenize foam structure. Screen **526** may be located, e.g., at or near the exit of mixing chamber **518**. Foam that has passed through the screen **526** may have a different bubble size and other characteristics from Foam A and is herein termed Foam B (**528**). In other embodiments, the screen **526** is omitted, so that Foam A is transferred without deliberate alteration to chamber **506**.

The exit of the mixing chamber **518** is connected by piping **530** to a port in the cylinder **502** that is gated by a valve **532** (e.g., a poppet-style valve) that permits fluid from piping **530** to enter the upper chamber (air chamber) **506** of the cylinder **502**. Valves (not shown) may control the flow of gas from the reservoir **510** through piping **520** to the mixing chamber **518**, and from the mixing chamber **518** through piping **528** to the upper chamber **506** of the cylinder **502**. Another valve **534** (e.g., a poppet-style valve) permits the upper chamber **506** to communicate with other components of the system **500**, e.g., an additional separator device (not shown), the upper chamber of another cylinder (not shown), or a vent to the ambient atmosphere (not shown).

The volume of reservoir **510** may be large (e.g., at least approximately four times larger) relative to the volume of the mixing chamber **518** and cylinder **502**. Foam A and Foam B are preferably statically stable foams over a portion or all of the time-scale of typical cyclic operation of system **500**: e.g., for a 120 RPM system (i.e., 0.5 seconds per revolution), the foam may remain substantially unchanged (e.g., less than 10% drainage) after 5.5 seconds or a time approximately five times greater than the revolution time.

In an initial state of operation of a procedure whereby gas stored in the reservoir **510** is expanded to release energy, the valve **532** is open, the valve **534** is closed, and the piston **504** is near top dead center of cylinder **502** (i.e., toward the top of the cylinder **502**). Gas from the reservoir **510** is allowed to flow through piping **520** to the mixing chamber **518** while liquid from the reservoir **510** is pumped by pump **514** to the mixing chamber **518**. The gas and liquid thus conveyed to the mixing chamber **518** are combined by the foam-generating mechanism **522** to form Foam A (**524**), which partly or substantially fills the main chamber of the mixing chamber **518**. Exiting the mixing chamber **518**, Foam A passes through the screen **526**, being altered thereby to Foam B. Foam B, which is at approximately the same pressure as the gas stored in reservoir **510**, passes through valve **532** into chamber **506**. In chamber **506**, Foam B exerts a force on the piston **504** that may be communicated to a mechanism (e.g., an electric generator, not shown) external to the cylinder **502** by a rod **536** that is connected to piston **504** and that passes slideably through the lower end cap of the cylinder **502**.

The gas component of the foam in chamber **506** expands as the piston **504** and rod **536** move downward. At some point in the downward motion of piston **504**, the flow of gas from reservoir **510** into the mixing chamber **518** and thence (as the gas component of Foam B) into chamber **506** may be ended by appropriate operation of valves (not shown). As the gas component of the foam in chamber **506** expands, it will tend,

unless heat is transferred to it, to decrease in temperature according to the Ideal Gas Law; however, if the liquid component of the foam in chamber **506** is at a higher temperature than the gas component of the foam in chamber **506**, heat will tend to be transferred from the liquid component to the gas component. Therefore, the temperature of the gas component of the foam within chamber **506** will tend to remain constant (approximately isothermal) as the gas component expands.

When the piston **504** approaches bottom dead center of cylinder **502** (i.e., has moved down to approximately its limit of motion), valve **532** may be closed and valve **534** may be opened, allowing the expanded gas in chamber **506** to pass from cylinder **502** to some other component of the system **500**, e.g., a vent or a chamber of another cylinder for further expansion.

In some embodiments, pump **514** is a variable-speed pump, i.e., may be operated so as to transfer liquid **512** at a slower or faster rate from the reservoir **510** to the foam-generating mechanism **522** and may be responsive to signals from the control system (not shown). If the rate at which liquid **512** is transferred by the pump **514** to the foam-mechanism **522** is increased relative to the rate at which gas is conveyed from reservoir **510** through piping **520** to the mechanism **522**, the void fraction of the foam produced by the mechanism **522** may be decreased. If the foam generated by the mechanism **522** (Foam A) has a relatively low void fraction, the foam conveyed to chamber **506** (Foam B) will generally also tend to have a relatively low void fraction. When the void fraction of a foam is lower, more of the foam consists of liquid, so more thermal energy may be exchanged between the gas component of the foam and the liquid component of the foam before the gas and liquid components come into thermal equilibrium with each other (i.e., cease to change in relative temperature). When gas at relatively high density (e.g., ambient temperature, high pressure) is being transferred from the reservoir **510** to chamber **506**, it may be advantageous to generate foam having a lower void fraction, enabling the liquid fraction of the foam to exchange a correspondingly larger quantity of thermal energy with the gas fraction of the foam.

All pumps shown in subsequent figures herein may also be variable-speed pumps and may be controlled based on signals from the control system. Signals from the control system may be based on system-performance (e.g., gas temperature and/or pressure, cycle time, etc.) measurements from one or more previous cycles of compression and/or expansion.

Embodiments of the invention increase the efficiency of a system **500** for the storage and retrieval of energy using compressed gas by enabling the surface area of a given quantity of heat-exchange liquid **512** to be greatly increased (with correspondingly accelerated heat transfer between liquid **512** and gas undergoing expansion or compression within cylinder **502**) with less investment of energy than would be required by alternative methods of increasing the surface of area of the liquid, e.g., the conversion of the liquid **512** to a spray.

In other embodiments, the reservoir **510** is a separator rather than a high-pressure storage reservoir as depicted in FIG. **5**. In such embodiments, piping, valves, and other components not shown in FIG. **5** are supplied that allow the separator to be placed in fluid communication with a high-pressure gas storage reservoir as well as with the mixing chamber **518**. An arrangement of this type will be shown in and described with reference to FIG. **9**.

FIG. **6** is a schematic diagram showing components of a system **600** for achieving approximately isothermal compression and expansion of a gas for energy storage and recovery

51

using a pneumatic cylinder **604** (shown in partial cross-section) according to embodiments of the invention. System **600** is similar to system **500** in FIG. **5**, except that system **600** includes a bypass pipe **638**. Moreover, two valves **640**, **642** are explicitly depicted in FIG. **6**. Bypass pipe **638** may be employed as follows: (1) when gas is being released from the storage reservoir **610**, mixed with heat-exchange liquid **612** in the mixing chamber **618**, and conveyed to chamber **606** of cylinder **604** to be expanded therein, valve **640** will be closed and valve **642** open; (2) when gas has been compressed in chamber **606** of cylinder **604** and is to be conveyed to the reservoir **610** for storage, valve **640** will be open and valve **642** closed. Less friction will tend to be encountered by fluids passing through valve **640** and bypass pipe **638** than by fluids passing through valve **642** and screen **626** and around the foam-generating mechanism **622**. In other embodiments, valve **642** is omitted, allowing fluid to be routed through the bypass pipe **638** by the higher resistance presented by the mixing chamber **618**, and valve **640** is a check valve preventing fluid flow when gas is being released in expansion mode. The direction of fluid flow from chamber **606** to the reservoir **610** via a lower-resistance pathway (i.e., the bypass pipe **638**) will tend to result in lower frictional losses during such flow and therefore higher efficiency for system **600**.

In other embodiments, the reservoir **610** is a separator rather than a high-pressure storage reservoir as depicted in FIG. **6**. In such embodiments, piping, valves, and other components not shown in FIG. **6** are supplied that allow the separator to be placed in fluid communication with a high-pressure gas storage reservoir as well as with the mixing chamber **618** and bypass pipe **638**.

FIG. **7** is a schematic diagram showing components of a system **700** for achieving approximately isothermal compression and expansion of a gas for energy storage and recovery using a pneumatic cylinder **702** (shown in partial cross-section) according to embodiments of the invention. System **700** is similar to system **500** in FIG. **5**, except that system **700** omits the mixing chamber **518** and instead generates foam inside the storage reservoir **710**. In system **700**, a pump **714** circulates heat-exchange liquid **712** to a foam-generating mechanism **722** (e.g., one or more spray nozzles) inside the reservoir **710**. The reservoir **710** may, by means of the pump **714** and mechanism **722**, be filled partly or entirely by foam of an initial or original character, Foam A (**724**). The reservoir **710** may be placed in fluid communication via pipe **720** with a valve-gated port **744** in cylinder **702**. Valves (not shown) may govern the flow of fluid through pipe **720**. An optional screen **726** (or other suitable mechanism such as an ultrasound source), shown in FIG. **7** inside pipe **720** but locatable anywhere in the path of fluid flow between reservoir **710** and chamber **706** of the cylinder **702**, serves to alter Foam A (**724**) to Foam B (**728**), regulating characteristics such as bubble-size variance and average bubble size.

In other embodiments, the reservoir **710** is a separator rather than a high-pressure storage reservoir as depicted in FIG. **7**. In such embodiments, piping, valves, and other components not shown in FIG. **7** will be supplied that allow the separator to be placed in fluid communication with a high-pressure gas storage reservoir as well as with the cylinder **702**. In other embodiments, a bypass pipe similar to that depicted in FIG. **6** is added to system **700** in order to allow fluid to pass from cylinder **702** to reservoir **710** without passing through the screen **726**.

FIG. **8** is a schematic diagram showing components of a system **800** for achieving approximately isothermal compression and expansion of a gas for energy storage and recovery using a pneumatic cylinder **802** (shown in partial cross-section)

52

according to embodiments of the invention. System **800** is similar to system **500** in FIG. **5**, except that system **800** omits the mixing chamber **518** and instead generates foam inside the air chamber **806** of the cylinder **802**. In system **800**, a pump **814** circulates heat-exchange liquid **812** to a foam-generating mechanism **822** (e.g., one or more spray nozzles injecting into cylinder and/or onto a screen through which admitted air passes) either located within, or communicating with (e.g., through a port), chamber **806**. The chamber **806** may, by means of the pump **814** and mechanism **822** (and by means of gas supplied from reservoir **810** via pipe **820** through a port **844**), be filled partly or substantially entirely by foam. The reservoir **810** may be placed in fluid communication via pipe **820** with valve-gated port **844** in cylinder **802**. Valves (not shown) may govern the flow of fluid through pipe **820**.

FIG. **9** is a schematic diagram showing components of a system for achieving approximately isothermal compression and expansion of a gas for energy storage and recovery using two pneumatic cylinder stages **902**, **904** (shown in partial cross-section) according to embodiments of the invention. The higher-pressure cylinder **902** may be placed in fluid communication with a first separator **906** and/or a second separator **908**; the lower-pressure cylinder **904** may be placed in fluid communication with the second separator **908** and/or a third separator **910**. The first separator **906** may be placed in fluid communication with a high-pressure gas storage reservoir (not shown). The third separator **910** may be placed in fluid communication with a vent (not shown) that allows air to be exchanged with the environment. Fluid passing between the first separator **906** and the high-pressure cylinder **902**, or between the high-pressure cylinder **902** and the second separator **908**, or between the second separator **908** and the low-pressure cylinder **904**, or between the low-pressure cylinder **904** and the third separator **910**, may be routed through mixing chambers **912**, **914**, **916**, **918** or bypass pipes **920**, **922**, **924**, **926**. Arrangements for controlling fluid communication between the high-pressure reservoir, the vent, the cylinders **902**, **904**, the mixing chambers **912**, **914**, **916**, **918**, and the bypass pipes **920**, **922**, **924**, **926** may include valves, piping, and other components not depicted in FIG. **9**. In various embodiments, the bypass pipes **920**, **922**, **924**, **926**, and/or additional bypass pipes not depicted in FIG. **9** may allow fluid to bypass the separators **906**, **908**, **910**.

During expansion of gas from storage, gas may first be partly expanded in a high-pressure cylinder **902**, allowing some of its potential elastic energy to be recovered by mechanisms (not shown) external to the cylinder **902**, and then further expanded in the low-pressure cylinder **904**, allowing most or substantially all of the remainder of its potential elastic energy to be recovered. During compression of gas for storage, gas may be partly compressed in the lower-pressure cylinder **904** and then further compressed in the higher-pressure cylinder **902**.

The system **900** includes arrangements similar to those depicted in FIG. **5** and/or FIG. **6** for achieving approximately isothermal compression and expansion of gas using foam to facilitate heat exchange between the gas and a heat-exchange liquid.

Each of the three separators (e.g., the first separator **906**) may contain baffles (e.g., baffle **928**) or other internal mechanisms for encouraging the breakdown or separation of a fluid foam into its gas and liquid components. Other techniques (not shown), such as spraying into the foam or mechanical shearing the foam, may be employed to encourage foam degradation in a separator. Separated liquid **930**, **932**, **934** may be conveyed by pumps **936**, **938**, **940**, **942** to the mixing

chambers **912, 914, 916, 918** (which preferably have integral screens) to be used in the formation of fresh foam.

Valves **944, 946, 948, 950, 952, 954, 956, 958** may be used to direct liquid passing between the separators **906, 908, 910** and the cylinders **902, 904** either through the mixing chambers **912, 914, 916, 918** or the bypass pipes **920, 922, 924, 926**. In cylinders **902, 904**, valves **964, 966, 968, and 970** (e.g., poppet-type valves) control the ingress and egress of fluids. Preferably, the pumps **936, 938, 940, 942** run only when foam is to be generated in their respective mixing chambers **912, 914, 916, 918**.

In general, gas that is to be conveyed to an air chamber **960, 962** of a cylinder **902, 904**, there to be either expanded or compressed, is routed through a mixing chamber in order to be foamed with heat-exchange liquid, enabling heat exchange to occur between the liquid and the gas during expansion or compression for the purpose of approximating an isothermal process.

In an initial state of operation of a procedure whereby gas stored in the high-pressure reservoir (not shown) is expanded in system **900** to release energy, piston **972** of the high-pressure cylinder **902** may be approximately at top dead center, piston **974** of the low-pressure cylinder **904** may be at bottom dead center (although the relative piston positions **972** and **974** may be arbitrarily phased), and the upper chamber **962** of the lower-pressure cylinder **904** is wholly or partly filled with foam at low pressure; in expansion mode, optional bypass valves **944** and **952** are closed and optional bypass valves **948** and **956** are open, allowing flow through mixing chambers **912** and **916** and optional valves **946** and **954**, but bypassing flow through mixing chambers **914** and **918** by the closing of optional valves **950** and **958**. Gas at high pressure is permitted to flow from the high-pressure reservoir, through the separator **906**, and into the mixing chamber **912**, where it is combined with heat-exchange liquid **930** to form foam. This foam, after optionally passing through a screen internal to the mixing chamber **912**, flows through valve **946** and valve **964** into chamber **960** of the high-pressure cylinder **902**, which it partly or substantially fills. In chamber **960**, the foam exerts a force on the piston **972** that may be communicated to a mechanism external to the cylinder **902**.

The gas component of the foam in chamber **960** expands as the piston **972** moves downward. At some point in the downward motion of piston **972**, the flow of gas from the storage reservoir, through the separator **906**, into the mixing chamber **912**, and thence (as the gas component of the foam) into chamber **960** may be ended by closure of valve **964**. As in the expanding foam in the cylinder of system **500** in FIG. **5**, the temperature of the gas component of the foam within chamber **960** will tend to remain constant (approximately isothermal) as the gas component expands.

The piston **974** of the low-pressure cylinder **904** may be moved upward from bottom dead center concurrently with the downward motion of piston **972** described above, expelling the low-pressure foam within chamber **962** through the bypass valve **956** and pipe **926** into the separator **910**. In the separator **910**, the liquid component of the foam settles and accumulates as a body of liquid **934**. The gas component of the foam passing from chamber **962** to the separator **910** proceeds out of the separator to the external vent (not shown) and is released to the environment. Additional mechanisms (not shown) for speeding the settling time of the foam into separate liquid and air, and for removing liquid from the venting air, may also be included. In brief, the high-pressure cylinder **902** may perform an intake stroke while the low-pressure cylinder **904** performs an exhaust stroke.

When the piston **972** of the high-pressure cylinder **902** has reached bottom dead center of cylinder **902** and the piston **974** has reached top dead center of the low-pressure cylinder **904**, the chamber **960** of the high-pressure cylinder **902** contains gas at a mid-pressure (e.g., 300 psi). Subsequently valve **966** may be opened, and the piston **972** of the high-pressure cylinder **902** may begin to move upward, and valve **968** may be opened and the piston **974** of the low-pressure cylinder **904** may begin to move downward. Concurrently, the pump **940** runs, conveying heat-exchange liquid **932** to the mixing chamber **916** to be foamed. Under these conditions, gas at mid-pressure flows from the chamber **960** of the high-pressure cylinder **902**, through the bypass pipe **922** and into the separator **908**. While the cylinders **902** and **904** do not need to be out-of-phase, in an out-of-phase scenario, mid-pressure gas flows from the separator **908** through the mixing chamber **916**, and (foamed with heat-exchange liquid) into chamber **962** of the low-pressure cylinder **904**, where it performs work on the piston **974** that is moving downward. In brief, the high-pressure cylinder **902** may perform an exhaust stroke while the low-pressure cylinder **904** performs an intake stroke.

It will be clear to persons reasonably familiar with the art of pneumatic and hydraulic machines that the series of operations described above may be repeated cyclically, expanding any desired quantity of gas from storage in an approximately isothermal manner. It will also be clear that the system **900** may assume a series of states of operation that isothermally compress gas admitted through the vent and deliver the compressed gas to the high-pressure storage reservoir, and that this series of states may also be repeated cyclically, compressing any desired quantity of gas into storage. Such operations (as well as those described in connection with FIG. **9**) may be performed via larger numbers of cylinders; multiple cylinders may expand or compress gas in parallel, or three or more stages (each of one or more cylinders) may be utilized to serially expand or compress gas.

In general, during both compression and expansion, system **900** may be operated so that fluids being exhausted from cylinders will be routed through the bypass tubes **920, 922, 924, 926**, and fluids being taken in by cylinders will be routed through the mixing chambers **912, 914, 916, 918** in order that foams may be admitted to the air chambers **960, 962**. Moreover, the screens (or other suitable foam-altering mechanisms) internal to the mixing chambers **912, 914, 916, 918** and the pumps **936, 938, 940, 942** may be operated in a manner that optimizes the efficiency of system **900** (e.g., continuous flow at a minimal pressure drop). Mixing chambers may be used for fine droplet spray as opposed to foam mixing in some or all of the mixing chambers, e.g., the low pressure chamber **918** may be used to suspend a mist of small droplets (e.g., 100 micron mean diameter or smaller) within the air in the chamber, whereas the other chambers **912, 914, 916** may be used to generate a suspension of aqueous foam. Some or all of the mixing chambers **912, 914, 916, 918** may be replaced with direct injection into the cylinder as shown in FIG. **8**. Some or all of the direct-injection foam generators (e.g., **822** in FIG. **8**) may be replaced with direct-injection spray generators such as an array of nozzles, e.g., a direct-injection mechanism (not shown) in the low pressure cylinder **904** may be used to suspend a mist of small droplets (e.g., 100-micron mean diameter or smaller) whereas a direct-injection mechanism (not shown) in the high pressure cylinder **902** may be used to generate an aqueous foam. Cylinders **902** and/or **904** may have two direct-injection mechanisms, one for compression and one for expansion, and one such mechanism may be for spray and one for foam generation.

FIG. 10 is a plot of experimental data on the isothermal efficiency of a gas-expansion process using a spray of tap water without foaming additives. All expansions plotted in FIG. 10 began at 3,000 psig and ended at 250 psig and took place in a 10-gallon cylinder with an 8-inch interior diameter and a 52-inch stroke length. Each symbol (i.e., circle, triangle, or square) plots the isothermal efficiency of a single run of the energy-conversion system incorporating the cylinder. Expansions at three different rates of output power (37 kW, 50 kW, and 70 kW) are plotted in FIG. 10. The vertical axis corresponds to isothermal efficiency of expansion, i.e., the fraction of the energy that is extracted during a single actual expansion compared with the energy theoretically extractable from a given quantity of gas via isothermal expansion. Expansions that decrease in temperature generally yield less energy than an ideal isothermal expansion and thus result in less than 100% isothermal efficiency. For example, an adiabatic expansion over the same pressure range would result in approximately 50% of the energy of an ideal isothermal expansion, and thus have approximately 50% isothermal efficiency.

In the expansions for which isothermal efficiency is plotted in FIG. 10, the heat-exchange spray commences at the beginning of expansion and is stopped when the expanding gas reaches a predetermined threshold pressure or "spray end pressure." The horizontal axis of FIG. 10 corresponds to this spray end pressure. Since the beginning gas pressures are the same for all expansions in FIG. 10, lower pressures tend to be attained within the cylinder at later times; thus, for each output power level, lower spray end pressure (leftward on horizontal axis) typically corresponds to a longer period of spraying (increased spray time).

As FIG. 10 shows, and as the arrow labeled "Increasing spray time" highlights, there is a clear tendency, for this experimental setup, and using tap water without foaming additive as a heat-exchange spray liquid, for efficiency to decrease with spray end pressure (i.e., to increase with spray time). Without limiting the scope of the present invention, it is believed that this trend occurs because heat transfer between the heat-exchange liquid and the gas within the cylinder occurs at a significant rate only while the liquid and gas are in contact with each other over a large surface area. For a non-foaming spray, the liquid and gas are in contact over a large surface area only while the spray is being generated and the droplets are falling through the gas. Heat exchange slows greatly soon after the spray ceases to be generated. Spraying throughout the whole expansion or most of the expansion therefore allows closer approximation to an isothermal expansion and thus higher isothermal efficiency.

FIG. 11 is a plot of experimental data on the isothermal efficiency of a gas-expansion process using a spray of tap water with 2.5% by volume of a foaming additive (which in this exemplary experiment includes, at least in part, an ethanolamine). The axes of the plot are as described above for FIG. 10. Expansions at two different rates of output power (50 kW and 70 kW) are plotted in FIG. 11.

As FIG. 11 shows, and as the arrow labeled "Increasing spray time" highlights, there is, if any, a slight tendency, at least for this experimental setup and using tap water with 2.5% foaming additive as a heat-exchange spray liquid, for efficiency to increase with spray end pressure (i.e., to decrease with spray time). Furthermore, the isothermal efficiencies obtained utilizing foaming heat-exchange sprays tend to be higher than those obtained with non-foaming sprays (FIG. 10). Without limiting the scope of the present invention, it is believed that the physical basis of this trend is that for a foaming spray, the liquid and gas are in contact over a large surface area not only while the spray is being actively

generated, but for as long as the resulting liquid-gas mixture persists substantially as a foam within the cylinder. Significant heat exchange thus may continue after the spray ceases to be generated. For the 2.5% water-plus-additive mixture used in the experiments whose results are plotted in FIG. 11, the entire volume of the expansion chamber within the cylinder is filled with foam soon (i.e., a small fraction of the duration of the expansion stroke) after the commencement of spraying. Longer spray times (lower spray end pressures) may be associated with lower isothermal efficiencies because they consume additional energy while producing relatively little additional heat transfer. Thus, under the experimental conditions pertaining to the data plotted in FIG. 11, the highest-efficiency cycle is achieved with the shortest period of spraying. Notably, the highest efficiency attained under the conditions illustrated in FIG. 11 (approximately 97%) is higher than the highest efficiency attained under the conditions illustrated in FIG. 10, i.e., with non-foaming spray (approximately 95.6%). With larger or smaller concentrations of one or more foaming additives (e.g., additives other than that utilized in this exemplary embodiment), other trends may be observed: e.g., at very low additive concentrations, foaming may be so slight as to not produce the effects observed with 2.5% concentration, in which case data more closely resembling those of FIG. 10 may be obtained.

FIG. 12 is a plot of experimental data on the isothermal efficiency of a gas-compression process using a spray of tap water without foaming additives. All compressions plotted in FIG. 12 began at 250 psig and ended at 3,000 psig and took place in a 10-gallon cylinder with an 8-inch interior diameter and a 52-inch stroke length. Each symbol (i.e., diamond, square, or triangle) plots the isothermal efficiency of a single run of the energy-conversion system. Compressions at three different rates of output power (37 kW, 50 kW, and 70 kW) are plotted in FIG. 12. The vertical axis corresponds to isothermal efficiency of compression, i.e., the fraction of the energy that is required to compress a given quantity of gas to a certain volume (from a given starting pressure and volume) via isothermal compression compared with the actual measured energy to compress that same quantity of gas to the same volume. Compressions that increase in temperature generally require more energy than an ideal isothermal compression and thus result in less than 100% isothermal efficiency. For example, an adiabatic compression of 10 gallons of 250 psig gas to a volume of 2 gallons would typically require approximately 170% of the energy of an ideal isothermal compression to the same volume, and thus have approximately 60% (i.e., 100/170) isothermal efficiency.

In the compressions for which isothermal efficiency is plotted in FIG. 12, the heat-exchange spray commences at the beginning of compression and is stopped at some predetermined threshold pressure or "spray end pressure." The horizontal axis of FIG. 12 represents this spray end pressure. Since the beginning and end gas pressures are the same for all expansions in FIG. 12, lower pressures are attained within the cylinder at earlier times; thus, lower spray end pressure (leftward on horizontal axis) corresponds to a shorter period of spraying (decreased spray time).

As the data plotted in FIG. 12 show, and the arrow labeled "Increasing spray time" highlights, there is a tendency, using tap water without foaming additives as a heat-exchange spray liquid, for efficiency to increase with spray end pressure (i.e., to increase with spray time) up to a spray pressure of about 2,000 psi. Without limiting the scope of the present invention, it is believed that the physical basis of this trend is that heat transfer between the heat-exchange liquid and the gas within the cylinder occurs at a significant rate only while the liquid

and gas are in contact over a large surface area. For a non-foaming spray, the liquid and gas are typically in contact over a large surface area only while the spray is being generated and its droplets are falling through the gas. Significant heat exchange ceases soon after the spray ceases to be generated. Spraying throughout the whole compression (or, for the compressions plotted in FIG. 12, most of the compression) allows closer approximation to an isothermal compression and thus higher isothermal efficiency.

FIG. 13 is a plot of experimental data on the isothermal efficiency of a gas-compression process using a spray of tap water with 2.5% by volume of foaming additives (i.e., the same foaming additives utilized to generate the data of FIG. 11). The axes of the plot are as described above for FIGS. 10, 11, and 12. Compressions at two different rates of output (50 kW and 70 kW) are plotted in FIG. 13.

As the data plot in FIG. 13 shows, and the arrow labeled "Increasing spray time" highlights, isothermal compression efficiency is approximately independent of spray end pressure using tap water with 2.5% foaming additives as a heat-exchange spray liquid in this experimental system. Without limiting the scope of the present invention, it is believed that the physical basis of this independence is that for a foaming spray, the liquid and gas are in contact over a large surface area not only while the spray is being generated, but for as long as the liquid-gas mixture persists in the form of a foam within the cylinder. Significant heat exchange thus continues after the spray ceases to be generated. For the 2.5% mixture utilized in the experiments whose results are plotted in FIG. 13, the entire volume of the expansion chamber within the cylinder is filled with foam soon (i.e., a small fraction of the stroke) after the commencement of spraying. Under the experimental conditions illustrated in FIG. 13, the highest-efficiency cycle is achieved with the shortest period of spraying, as well as with the longest. Notably, the highest efficiency attained under the conditions illustrated in FIG. 13 (over 98%) is significantly higher than the highest efficiency attained under the conditions illustrated in FIG. 12, non-foaming spray (approximately 96%). With larger or smaller concentration of one or more foaming additives, other trends may be observed: e.g., at very low concentrations (or other concentrations of other additives), foaming may be so slight as to not produce the effects observed with 2.5% concentration, in which case data more closely resembling of FIG. 12 may be obtained.

Achieving high isothermal efficiency by using foaming spray liquid with relatively short spray time has the advantage that the parasitic energy devoted to spray generation is reduced relative to a more prolonged spraying period. During compressions, a short, initial period of spraying in general must overcome low gas pressure in the cylinder chamber being sprayed compared to the pressure in later parts of the compression, which also saves spraying energy. During expansions, when water warmer than the gas in the chamber is generally sprayed to achieve isothermal expansion, spraying when the gas is at the initial pressure requires only a small pressure increase for water at that initial pressure (e.g., water in the storage reservoir 320 in FIG. 3) and thus a low pumping power; whereas if water is sprayed from that initial pressure (e.g., the storage-reservoir pressure) into a much lower cylinder pressure, energy may be lost in the throttling of fluid during the spraying process. Additives that produce foaming may simultaneously produce one or more other benefits, such as increasing lubricity or preventing corrosion.

Other considerations in the energy-efficient generation of foam are (1) whether, to minimize energy lost in circulation of liquids across pressure differentials, foam should be gener-

ated before admission to the air chamber of a pneumatic cylinder for compression or expansion (herein termed the "pre-foam" or "port injection" approach), or directly into the air chamber of the pneumatic cylinder (herein termed the "foam-during" or "direct injection" approach), and (2) what the liquid-to-gas mass ratio of the foam should be to optimize heat exchange, pumping energy, and other efficiency considerations. The illustrative systems shown in FIG. 5, FIG. 6, and FIG. 7 are pre-foam systems; the illustrative systems shown in FIG. 8 is a foam-during system.

FIG. 14 is an illustrative graph of calculated energy expended in the generation and injection of foam or foaming liquid into the air chamber of a pneumatic cylinder as a function of time, comparing the pre-foam approach to the foam-during approach. By basic principles of hydraulics, the foaming energy W_{foam} (i.e., where mechanical agitation is employed to induce foaming, the energy required to produce a given amount of foam by forcing foaming liquid through a device that mingles the liquid with gas to form a foam) is determined by the volume of foamed liquid V_{liquid} multiplied by the change in pressure $\Delta P_{foaming}$ undergone by the foamed liquid in its passage through the foaming device: $W_{foam} = V_{liquid} \times \Delta P_{foaming}$. Where V_{liquid} and $\Delta P_{foaming}$ vary with time, total foaming energy W_{foam} over a given time interval is given by the integral of $V_{liquid} \times \Delta P_{foaming}$ over that interval: $W_{foam} = \int V_{liquid} \times \Delta P_{foaming} dt$ (where the limits of integration are not explicitly indicated). If V_{liquid} is constant and $\Delta P_{foaming}$ varies with time, $W_{foam} = V_{liquid} \times \int \Delta P_{foaming} dt$. For a given gas-to-liquid mass ratio for a given quantity of gas, V_{liquid} is fixed; therefore, to minimize W_{foam} , average $\Delta P_{foaming}$ must be minimized.

In general, for the foam-during (i.e., direct-injection) approach, $\Delta P_{foaming}$ varies throughout a piston stroke within a cylinder assembly, as $\Delta P_{foaming}$ is given by the difference between the source pressure of the foaming liquid and the pressure of the gas into which the foaming liquid is injected. The pressure of the source of foaming liquid is in general approximately constant, while the pressure of a gas undergoing compression or expansion within a cylinder assembly changes substantially. Creation of a foam within a cylinder assembly during, e.g., a compression stroke, thus entails forcing foaming liquid into the air chamber of the cylinder assembly against an increasing pressure difference (increasing $\Delta P_{foaming}$).

In the graph in FIG. 14, the vertical axis, "Differential Spray Pressure," corresponds to $\Delta P_{foaming}$ and the horizontal axis corresponds to time. The area under a curve plotting $\Delta P_{foaming}$ versus time is $\int \Delta P_{foaming} dt$. Therefore, since $W_{foam} = V_{liquid} \times \int \Delta P_{foaming} dt$, if V_{liquid} is presumed constant, foaming energy W_{foam} for a given gas expansion or compression process will be proportional to the area under the $\Delta P_{foaming}$ versus time curve for that process.

The solid line in the graph in FIG. 14 shows $\Delta P_{foaming}$ for a foam-during (i.e., direct-injection) compression of a quantity of gas beginning at approximately 0 psig. As the pressure within the air chamber of the cylinder assembly increases, $\Delta P_{foaming}$ increases (rising curve in graph). If foam creation continues during a period of time after compression is complete, $\Delta P_{foaming}$ will be approximately constant for that period of time (flat portion of solid curve in graph from time equals approximately 0.8 unit to time equals 1.0 unit). The area under the solid line in the graph in FIG. 14 is $\int \Delta P_{foaming} dt$; therefore, by $W_{foam} = V_{liquid} \times \int \Delta P_{foaming} dt$, foaming energy W_{foam} for this illustrative compression process is proportional to the area under the solid line.

Similarly, the dotted line in the graph in FIG. 14 shows $\Delta P_{foaming}$ for a pre-foam (i.e., port-injection) compression of

a quantity of gas beginning at approximately 0 psig. The quantity of gas and other features of the compression process are the same as those for the compression represented by the solid line in the graph. In the pre-foam process, foam is generated at low pressure as the gas to be compressed is admitted into the air chamber of cylinder assembly. $\Delta P_{foaming}$ is low and constant throughout foam generation (horizontal dotted line in the graph) for the pre-foam process. Manifestly, the area under the dotted line in the graph (i.e., $\int \Delta P_{foaming} dt$, which equals the foaming energy W_{foam} for this illustrative pre-foam compression process) is smaller than the area under the solid line in the graph. Therefore, foaming energy W_{foam} is smaller for a pre-foam compression process than for a comparable foam-during compression process.

For a pre-foam process in which foam is created in a foam generator external to the cylinder assembly (as, e.g., in FIG. 5), the generated foam must be admitted through a valve (e.g., a poppet valve) into the air chamber of the cylinder assembly. During either expansion or compression, passage through the valve into the cylinder assembly will entail some pressure drop for the foam and therefore some energy loss. However, the pressure drop through a valve (e.g., poppet valve) governing the entrance or exit of fluid from the air chamber of the cylinder assembly will generally be lower than the pressure drop through a foam-generating device. Therefore, pre-foam processes will in general realize lower energy losses, and thus higher efficiency, than foam-during processes.

Moreover, for a spray-during process, either of compression or expansion, foam generation must occur in episodes or time intervals whose duration and timing are determined by the action of the cylinder assembly. For a pre-spray process, foam may be generated or regenerated continuously (e.g., within a large foam generator or a reservoir attached to the foam generator), not only during each compression or expansion stroke of the cylinder assembly. Performing foam generation over a longer time period is likely to further lower $\Delta P_{foaming}$ compared to more rapid foaming, allowing further efficiency gains to be realized.

The graph in FIG. 15 plots calculated temperature changes of the liquid component of a foam undergoing a set of illustrative compression processes for a range of foam mass ratios and a set of illustrative compression processes. The vertical axis of the graph in FIG. 15 corresponds to the temperature change of the liquid component of a foam undergoing compression, and the horizontal axis of the graph corresponds to the mass ratio of the foam undergoing compression, i.e., the ratio of the mass of liquid m_w per unit volume of foam to the mass of gas m_a per unit volume of foam. (The mass ratio m_w/m_a does not vary with pressure, except as some fraction of the gas component may dissolve into or evaporate from the liquid component, altering m_a , or as some fraction of the liquid component may evaporate into or condense out of the gas component, altering m_w . The illustrative graph in FIG. 15 neglects the effects of dissolved gas and vapor-liquid phase changes of the liquid component, as these are relatively minor effects.)

When a foam including or consisting essentially of a compressible gas and an approximately incompressible liquid is compressed, the change in volume of the foam is due to the compression of the gas component. As noted earlier, gas undergoing compression tends to heat. The rising temperature of the gas component of a foam undergoing compression will cause thermal energy to be transferred to the liquid component of the foam. The larger the mass ratio m_w/m_a , the greater the mass of liquid available to absorb thermal energy for each mass unit of gas, and the lower the resulting change in temperature T of the liquid for a given overall change in

pressure of the foam. Final T of the liquid is in general a function of initial foam temperature, the heat transfer coefficients of the gas and liquid components of the foam, the heat capacity of the gas and of the liquid, the foam mass ratio, the foam start pressure, and the foam end pressure. In the graph in FIG. 15, only mass ratio and foam end pressure vary.

The change in temperature (ΔT) of the liquid component of a variety of hypothetical foams undergoing compression is represented by the series of curves in the graph in FIG. 15. Compressions are shown for a low-pressure cylinder (LP) and a second-stage high-pressure cylinder (HP). For the LP cylinder, compressions begin, for a first compression stage, at approximately 0 psig and end at approximately 180 psig (shown and labeled as T_{LP}). For the subsequent high-pressure second compression stage, three scenarios are shown: (1) a compression from 180 psig to a first high pressure of 850 psig ($T_{HP(P=850 \text{ psi})}$), (2) a compression from 180 psig to a first high pressure of 3000 psig ($T_{HP(P=3000 \text{ psi})}$), and (3) the average of (1) and (2). For simplicity, the liquid is presumed not to boil or freeze under any of the pressure-and-temperature conditions encountered in the hypothetical compressions. The first (lower) solid line of the graph represents the final temperature of an LP compression across a range of mass ratios m_w/m_a ; the dotted line represents the final liquid temperature after foam compression to 850 psig; the dashed line represents the final liquid temperature after foam compression to 3,000 psig; and the solid line between the dashed line and the dotted line represents the average of the 850 psig and 3,000 psig final temperatures.

All four curves in the graph in FIG. 15 are of an approximately hyperbolic character, approaching adiabatic conditions as m_w/m_a goes to zero and approaching zero as m_w/m_a goes to infinity. It will be apparent to persons reasonably familiar with the principles of thermodynamics, liquids, and mixed-phase systems that low m_w/m_a (approaching zero) is undesirable because of the temperature extremes that will be encountered. High temperatures may lead to boiling of liquid (e.g., when the liquid is separated from the foam and its pressure is reduced), to breakdown of surfactant compounds, or to other undesirable effects. Similarly, large m_w/m_a (approaching infinity) requires the pumping of larger fractions of liquid in which no potential energy of pressure is stored; further, as m_w/m_a increases, a point will be reached where a "foam" is no longer tenable, but rather a mass of liquid is produced in which bubbles of gas are present. Among other disadvantages of excessively high m_w/m_a , pistons would be capable of effecting only slight compression of such a mixture. Efficient operation of a compressed-gas energy storage system is generally not feasible where the working fluid (e.g., two-phase mixture) is not significantly compressible. Therefore, the graph in FIG. 15 supports the conclusion that foams having moderate mass ratios m_w/m_a , e.g., in the vicinity of $m_w/m_a=2$, are likely to be the most efficient when utilized in compressed-gas energy storage system. Such mass ratios include, for example, mass ratios of 1 to 4, and, more preferably, 1.5 to 3.

Employment of two fluid phases (e.g., liquid and gas in a foam) in a compressed-gas energy storage system may entail storage of liquid as well as of compressed gas, either commingled as foam or separated into liquid, foam, and gas fractions, although only the compressed gas stores significant pressure potential energy. Storage of liquid may constitute an additional or parasitic cost for the energy storage system; if excessive heat-exchange liquid is stored, the cost-effectiveness of the energy storage system may be reduced. For storage of large quantities of compressed gas, storage cost may even dominate total system cost, and in such a case, the cost of

storing large quantities of liquid may be prohibitive. The graph in FIG. 16 shows additional liquid volume as a fraction of gas storage volume (i.e., additional storage volume for a two-phase system where the liquid is stored in the pressure storage reservoir with the gas relative to storage reservoir volume for gas-only in the storage reservoir) as a function of foam mass ratio m_w/m_g for a compressed gas energy storage system with a maximum pressure of 3,000 psig. For mass ratio of zero, there is zero liquid storage. For mass ratio of 5, approximately 1.2 times more liquid volume than gas volume must be stored. For a mass ratio of approximately 2, a volume of liquid must be stored that is about half as large as the amount of gas that must be stored. FIG. 16, like FIG. 15, supports the conclusion that mass ratios in the vicinity of 2 are likely to support the operation of an efficient, cost-effective compressed-gas energy storage system.

FIG. 17 is a graph of experimental data comparing the energetic performance of aqueous foams and droplet sprays in maintaining substantially isothermal gas cycling during rapid gas expansions between approximately 3,000 psig and approximately 250 psig. Data are shown for isothermal gas expansions occurring in a high-pressure test stand. Each symbol on the graph represents a single isothermal expansion. Heat exchange between the liquid and air is achieved by four methods in these experiments: (1) water droplet spray in the gas during compression (filled circles), (2) water droplet spray in the gas prior to expansion (filled triangles), (3) aqueous foam spray in the gas during expansion (open circles), and (4) aqueous foam spray in the gas prior to expansion (open triangles), also termed "foam pre-spray."

The vertical axis of the graph in FIG. 17 is isothermal efficiency, i.e., work performed by the expanding gas divided by the work expected by an ideal isothermal expansion. The horizontal axis of the graph in FIG. 17 is relative spray work, i.e., the work required to produce the spray of droplets or foam (e.g., by forcing liquid through a spray head) divided by the total work performed by the gas during the expansion. For example, in a given expansion experiment, if 300 kJ of work are performed by the isothermally expanding gas, and 3 kJ of work are required to produce the foam generated during that expansion, then the relative spray work for that experiment is 0.01 (3 kJ divided by 300 kJ). Lower relative spray work is desirable because it increases overall system efficiency; spray work is in general a parasitic load for an isothermal energy storage and recovery system. Spray pumping work is related to sprayed volume multiplied by pressure drop and is the work required to force the fluid through, e.g., pipes and nozzles to generate a high-quality spray or aqueous foam that promotes rapid heat transfer between the sprayed liquid and the expanding or compressing gas by maximizing surface area and proximity between the liquid and gas.

A third experimental variable in the graph in FIG. 17 is indicated for foam pre-spray experiments (open triangles) by associating numbers with plotted experimental points. The number by each pre-spray point specifies the foam mass ratio for that experiment. Herein, the foam mass ratio is defined as the ratio of liquid mass to gaseous mass in a given volume of aqueous foam. For example, if a cubic meter of a given foam contains 2 kg of liquid and 1 kg of gas, then the mass ratio of that foam is 2.0 (2 kg divided by 1 kg). Mass ratios could be indicated for all points in the graph, but for simplicity are only shown for foam pre-spray.

The graph in FIG. 17 supports several statements about the employment of foams for heat transfer in isothermal compressed-gas energy storage and generation systems. First, higher isothermal efficiencies (e.g., by approximately 2 to 5 isothermal efficiency percentage points) are achievable using

foam pre-spray than for water spray techniques for a similar set of experimental conditions. (This statement is also supported by the graph in FIG. 15.) Second, the majority of foam pre-spray experiments have low relative spray work as well as high isothermal efficiency: note the cluster of foam pre-spray experimental points clustered in the vicinity of relative spray work 0.02 and isothermal efficiencies clustered between 0.92 and 0.95. Third, relatively high isothermal efficiencies (approximately 0.94) are achieved by foam pre-spray, in most cases, by relatively low mass ratios (1.8 to 5.5); again, note the cluster in the vicinity of relative spray work 0.2, isothermal efficiency 0.92 to 0.95.

A foam contains a large liquid-gas surface contact area, facilitating heat transfer between the two phases (liquid and gas). Use of foam for heat transfer during isothermal gas expansion or compression offers a number of advantages over non-foam-based techniques such as droplet sprays. These advantages include the following: (1) For a given liquid-gas surface contact area (and corresponding heat-transfer rate), a foam may typically be generated using significantly less energy than a spray. (2) Anti-corrosive and/or other agents that may be advantageous to add to a heat-exchange liquid may have intrinsic surfactant (foaming) properties. Thus, multiple advantages, including foaming for heat transfer, may be achieved using a heat-exchange liquid containing only a few additives (or merely one). (3) Droplets tend to settle (rain out) of a gas rapidly, whereas foams may be relatively persistent, depending on the properties of the surfactants or other substances responsible for foaming behavior. Therefore, unlike droplets, foams may be injected into a gas either while the gas is undergoing expansion or compression within a cylinder chamber or prior to, and/or concurrently with, the transfer of the gas into the chamber. Foam generation may thus be located externally to the cylinder, as compared to, for example, placement of spray heads within the cylinder for generating a droplet spray. Location of foam generation outside the cylinder has several advantages, including increasing cylinder interior volume and relaxing size constraints on the foam generation mechanism. Locating foam generation outside the cylinder also enables continuous or episodic foam generation, not necessarily synchronized with the operation of the cylinder, whereas foam or spray generation inside the cylinder tends to be synchronized with the operation of the cylinder. A quantity of foaming liquid may be added to a quantity of gas either during or prior to admission of the gas into a cylinder chamber, substantially filling the cylinder chamber with foam. As the gas is expanded or compressed in the cylinder chamber, the foam is expanded or compressed correspondingly, continuing to substantially fill the cylinder chamber throughout the expansion or compression. Herein, we assume that foams persistent relative to cylinder stroke time are employed, i.e., foams that do not significantly drain over the time-scale on which expansions and compressions take place in a given system. Foam persistence throughout expansion or compression facilitates isothermality by enabling heat transfer between the gas and liquid phases to occur throughout expansion or compression. (4) In the experiments whose results are depicted in FIG. 17, only foam experiments achieve simultaneously high isothermal efficiency, low relative spray work, and low mass ratio: the spray droplet experiments with highest isothermal efficiency (approximately 0.935) have mass ratio above 10 (not shown on graph) and relative spray work between approximately 0.035-0.095, whereas many foam pre-spray experiments have comparable or higher isothermal efficiencies with relative spray work less than 0.035 and mass ratios of 3.6-5.5. In general, foam pre-spray achieves higher isothermal efficiency and

lower relative spray work with lower mass ratio than do other methods examined in the series of experiments graphed in FIG. 17. Lower mass ratio is advantageous because for a given isothermal efficiency and given start pressure (in expansions) or end pressure (in compressions), in a cylinder of a given volume, a lower mass ratio allows more gas to be compressed or expanded in a single cycle than does a higher mass ratio, as there is less incompressible liquid and more gas in the cylinder chamber. Processing more gas per cylinder cycle raises overall system power density. An additional advantage of lower mass ratio arises as follows: during the injection of fluid into a cylinder chamber or during the expulsion of fluid from a cylinder chamber, pressure drops occur through valves, with attendant system inefficiency. For a given flow rate through a valve, pressure drop is approximately proportional to the mass density of the fluid passing through the valve. The average mass density of a foam is lower for a foam with lower mass ratio. Thus, throttling losses during the passage of foam into and out of a cylinder are lower for a foam with lower mass ratio.

Mass ratio remains approximately constant within a closed cylinder during expansion or compression of a foam. Bubbles in a foam tend to grow during expansion and shrink during compression, but the masses of the liquid and gas components generally remain fixed, apart from effects arising from the dissolving or coming out of solution of gas and vapor-liquid phase changes of the liquid component.

FIG. 18 is a schematic drawing of a system 1800 that may be part of a larger system for energy storage and generation not otherwise depicted. System 1800 has two cylinders 1802 and 1804 and apparatuses 1806, 1808, 1810 for the generation and separation of foams 1812, 1814, 1816 having three different expansion ratios. Herein, the "expansion ratio" of a foam is the total volume of a given quantity of the foam divided by the volume of the liquid component of that volume of foam. For example, if 1 cubic meter of a foam contains 0.1 cubic meter of liquid, the expansion ratio of the foam is 10.0 (1 cubic meter divided by 0.1 cubic meter). Unlike mass ratio, expansion ratio does not tend to remain constant as a foam is expanded or compressed. Rather, expansion ratio tends to decrease as a foam is compressed and increase as it is expanded.

Each foam-generation apparatus 1806, 1808, 1810 features a foam vessel (1818, 1820, and 1822, respectively) and a recirculation pump (1824, 1826, and 1828, respectively). Cylinder 1802 operates in a range of relatively high pressures (e.g., between approximately 300 psig and approximately 3,000 psig), and cylinder 1804 operates in a range of relatively low pressures (e.g., between approximately 300 psig and approximately 0 psig). Each foam vessel 1818, 1820, 1822 may include or consist essentially of a separate pressure vessel (as depicted in FIG. 18), piping connected to a cylinder (or a portion thereof), and/or a manifold connected to a cylinder (or a portion thereof).

When system 1800 is operated as an expander, gas from storage (not shown) may be admitted to high-pressure foam vessel 1818 at high pressure. There the gas is combined with heat-exchange liquid to form an aqueous foam (or enhance an already present foam) having a desired mass ratio. Foam may accumulate in high-pressure foam vessel 1818 prior to transfer to cylinder 1802, be passed to high-pressure cylinder 1802 as it is generated, or both. A mechanism for combining gas with heat-exchange liquid to form an aqueous foam is not depicted in FIG. 18; illustrative mechanisms will be depicted in subsequent figures. Liquid accumulating in high-pressure foam vessel 1818 due to foam breakdown may be recirculated into vessel 1818 by the pump 1824. In other embodiments,

pump 1824 may be reversed and air or less dense foam from nearer the top of vessel 1818 may be pumped into the bottom of vessel 1818 to regenerate foam (e.g., a sparging process). When system 1800 is operated as an expander, foam at high pressure from high-pressure vessel 1818 is admitted to the upper chamber 1830 of cylinder 1802. The foam expands in the chamber 1830, retaining a constant mass ratio but increasing its expansion ratio (e.g., by a factor between approximately 5 and approximately 15). After expansion of the gas in chamber 1830 to a mid-pressure (e.g., approximately 300 psig), the foam is pushed from chamber 1830 by a return stroke of the piston 1832. The foam exiting chamber 1830 passes into foam vessel 1820. In foam vessel 1820, the foam may be reconstituted by an appropriate mechanism such as one including recirculation pump 1826. The foam may accumulate in mid-pressure vessel 1820 prior to transfer to cylinder 1804, be passed to cylinder 1804 as it is generated/maintained, or both. The mid-pressure foam vessel 1820 contains and generates foam at the mid-pressure of system 1800 (e.g., approximately 300 psig).

Foam from mid-pressure foam vessel 1820 is admitted to the upper chamber 1834 of low-pressure cylinder 1804. The foam expands in the chamber 1834, retaining a constant mass ratio during expansion but increasing its expansion ratio (e.g., by a factor of approximately 10 to approximately 15). After expansion of the gas in chamber 1834 to low pressure (e.g., approximately 5 psig), the foam is pushed from chamber 1834 by a return stroke of the piston 1836. The foam exiting chamber 1830 passes into low-pressure foam vessel 1822. In low-pressure foam vessel 1822, the foam is separated into its liquid and gaseous components so that low-pressure gas may be exhausted through vent 1838 substantially without loss of heat-exchange liquid from the system 1800.

When system 1800 is operated as a compressor, gas from the environment may be admitted to low-pressure foam vessel 1822 at low pressure (e.g., atmospheric pressure). There the gas is combined with heat-exchange liquid to form an aqueous foam having a desired mass ratio. Foam may accumulate in the low-pressure foam vessel 1822 prior to transfer to cylinder 1804, be passed to low-pressure cylinder 1804 as it is generated, or both. Liquid accumulating in low-pressure foam vessel 1822 due to foam breakdown may be recirculated into vessel 1822 by the pump 1828. When system 1800 is operated as a compressor, foam at low pressure from vessel 1822 is admitted to the upper chamber 1834 of cylinder 1804. The foam is compressed in the chamber 1834, retaining a constant mass ratio but decreasing its expansion ratio. After compression of the gas in chamber 1834 to a mid-pressure (e.g., approximately 300 psig), the foam is exhausted from chamber 1834. The foam exiting chamber 1834 passes into mid-pressure foam vessel 1820. In foam vessel 1820, the foam may be reconstituted by an appropriate mechanism, e.g., one including recirculation pump 1826. The foam may accumulate in mid-pressure vessel 1820 prior to transfer to cylinder 1802, be passed to cylinder 1802 as it is generated/maintained, or both.

Foam from mid-pressure foam vessel 1820 is admitted to the upper chamber 1830 of high-pressure cylinder 1802. The foam is compressed in the chamber 1830, retaining a constant mass ratio during compression but decreasing its expansion ratio. During or after compression of the gas in chamber 1830 to high pressure (e.g., approximately 3,000 psig), the foam exits chamber 1830 and passes into high-pressure storage (not shown in FIG. 18) via high-pressure foam vessel 1818. In high-pressure foam vessel 1818, the foam may be separated into its liquid and gaseous components so that high-pressure gas may be transferred to high-pressure storage substantially

without loss of heat-exchange liquid from the system **1800**. Alternatively or in conjunction, foam may be passed to high-pressure storage from vessel **1818** and there stored as an aqueous foam, separated into its liquid and gas components, or under a partial such separation.

The cylinders **1802**, **1804** and the foam-generation apparatuses **1806**, **1808**, **1810** may circulate fluid through heat-exchange subsystems, not depicted in FIG. **18**, and/or may communicate with a single or multiple thermal wells, not depicted in FIG. **18**.

FIG. **19** is a schematic drawing of an illustrative system **1900** that includes an apparatus for the generation of foam at low pressure (e.g., approximately atmospheric pressure) having a high expansion ratio (e.g., 400:1) corresponding to a moderate liquid-to-air mass ratio (e.g., 2:1). System **1900** includes three two-cylinder subsystems (**1902**, **1904**, **1906**), depicted in cross-section as viewed from above in a vertically oriented cylinder arrangement, for the isothermal expansion and compression of gas. The depiction in the illustrative system **1900** of three two-cylinder subsystems is illustrative: other numbers of subsystems, where each subsystem includes one, three, or more cylinders, are also contemplated and within the scope of the invention. Each of the two-cylinder systems **1902**, **1904**, and **1906** includes or consists essentially of a high-pressure cylinder (**1908**, **1910**, and **1912**, respectively) and a low-pressure cylinder (**1914**, **1916**, and **1918**, respectively). The apparatus for the generation of foam may include or consist essentially of a spray chamber **1920**, a screen **1922**, a manifold **1924** that conducts foam (typically represented in FIG. **19** and elsewhere herein by stippling) to the low-pressure cylinders **1914**, **1916**, and **1918**, a fan **1926**, and an optional vent and ball valve **1928** whose function shall be described below. During the generation of foam in the apparatus, air at low (e.g., approximately atmospheric) pressure is admitted to the spray chamber **1920** through an inlet **1930**. The air is accelerated toward the screen **1922** by the fan **1926** (or other suitable mechanism). Fluid from a reservoir **1932**, foam vessel, or other source is pumped by a pump **1934** to one or more spray heads **1936** (or other suitable dispersal mechanisms), which are placed in the flow of gas accelerated by the fan **1930**. The spray **1938** from the spray heads **1936** is directed toward the screen **1922** (e.g., metal mesh, netting, solid foam material). Passing through the screen **1922**, the air and spray **1938** combine to form an aqueous foam **1940**. The foam **1940** may be directed via suitable valves and pipes (not depicted) into chambers of the low-pressure cylinders **1914**, **1916**, and **1918**.

In a start-up mode of operation where the manifold **1924** initially contains no foam, gas may be directed out the valve **1928** (rather than into the low-pressure cylinders **1914**, **1916**, and **1918**) during generation of foam until the manifold **1924** is substantially or entirely filled with foam **1940**, whereupon the valve **1928** may be closed and the foam **1940** may be directed into the low-pressure cylinders **1914**, **1916**, and **1918**. Valve **1928**, in various embodiments, may be connected to a vent (not shown), have connections that allow any liquid intake to return to the fluid reservoir **1932**, and/or may be connected back to the inlet **1930**.

The generation capacity of the foam generation apparatus (including spray chamber **1920**, screen **1922**, and manifold **1924**) depicted in FIG. **19** may be sized to correspond to an average foam intake flow for the cylinder or cylinders to which the apparatus supplies foam, or to a peak foam intake flow. Herein, the generation capacity of a foam generator is the volume of foam that it can produce per unit time (m^3/sec). Rapid foam flow from a reservoir or pre-generated body of foam may entail shear forces that break down the flowing

foam, partly or wholly; generating foam at a sufficient rate may mitigate such shear forces. Other foam generators, both those depicted herein and in embodiments not depicted herein, may also be sized in order to accommodate peak flow rates and mitigate separation of foams due to shear forces.

FIG. **20** is a schematic drawing of an illustrative system **2000** that features an apparatus for the generation and separation of aqueous foam at low pressure (e.g., approximately atmospheric pressure) having a high expansion ratio (e.g., 400:1) corresponding to a moderate liquid-to-air mass ratio (e.g., 2:1). System **2000** includes three two-cylinder subsystems (**2002**, **2004**, **2006**), depicted in cross-section as viewed from above in a vertically oriented cylinder arrangement, for the isothermal expansion and compression of gas. The depiction in the illustrative system **2000** of three two-cylinder subsystems is illustrative: other numbers of subsystems, where each subsystem includes one, three, or more cylinders, are also contemplated and within the scope of the invention.

Each of the two-cylinder systems **2002**, **2004**, and **2006** includes a high-pressure cylinder (**2008**, **2010**, and **2012**, respectively) and a low-pressure cylinder (**2014**, **2016**, and **2018**, respectively). The apparatus for the generation of foam includes three chambers: a spray chamber **2020**; a manifold **2022** that conducts foam to the low-pressure cylinders **2014**, **2016**, and **2018**; and a separation chamber **2024**. The spray chamber **2020** is divided from the manifold **2022** by a screen **2024** and may contain a fan **2026**, one or more spray heads **2028**, and a louvre or flap **2030** capable of either blocking or allowing the passage of gas into the spray chamber **2020**. Louvre **2030** may act as an air check valve, preventing backflow in the opposite direction of the arrows shown on manifold **2022**. The manifold **2022** is separated from the separation chamber **2024** by a louvre or flap **2032** capable of either blocking or allowing the passage of gas and/or foam **2034** from the manifold **2022** into the separation chamber **2024**. The separation chamber **2024** contains a foam breakup mechanism **2036** that separates foam **2034** into a gas component and a liquid component **2038**. In FIG. **20**, the foam breakup mechanism **2036** is a rotating whisk; other methods and mechanisms for the breakup of foam (e.g., other forms of mechanical agitation, screens, filters, ultrasound) are contemplated and within the scope of the invention. The liquid **2038** within the separation chamber **2024** is conveyed by piping **2040** to a reservoir **2042**, from whence it may be pumped by a pump **2044** through piping **2046** to the spray heads **2028** for recycling into fresh foam **2034**. An atmospheric vent or opening **2048** permits ingress of low-pressure gas into the spray chamber **2020** during generation of foam **2034** and egress of low-pressure gas from the separation chamber **2024** during the breakup of foam **2034**. During ingress of gas into the spray chamber **2020**, an optional cleaning filter **2050** prevents the admission into the spray chamber **2020** of particulates and/or other contaminants in the atmospheric air. During egress of gas from the separation chamber **2024**, an optional coalescing filter **2052** removes remaining liquid from foam, water droplets, and vapor, assuring that nearly no liquid will be passed to the vent **2048**. In various other embodiments, separate vents may be provided for ingress of gas into and egress of gas out of the system **2000**. Also in various other embodiments, the filters **2050**, **2052** may be located outside the apparatus depicted in FIG. **20** (e.g., in pipes leading to the separate vents provided in various other embodiments).

During operation of system **2000** as a compressor (e.g., to store energy as the pressure potential energy of compressed air), air is admitted through vent **2048**, passes through a filter **2050**, and is accelerated by fan **2026** toward the spray heads

2028 and the screen 2024. Liquid is pumped through the spray heads 2028. (Optionally, fan 2026 may be omitted and air flow may be generated via cylinder piston motion.) Spray 2054 mingled with air strikes the screen 2024. A foam 2034 having a relatively high expansion ratio is generated by the passage of mingled air and liquid through the screen 2024. The manifold 2022 conducts the foam 2034 to the low-pressure cylinders 2014, 2016, and 2018, into which the foam 2034 is admitted by appropriate valves (not depicted in FIG. 20). The foam 2034 inside the low-pressure cylinders 2014, 2016, and 2018 is then compressed to a mid-pressure (e.g., approximately 300 psig), after which the foam is transferred to the high-pressure cylinders 2008, 2010, and 2012 and possibly to, or through, other apparatus not depicted in FIG. 20. Additionally, the amount of foam flow generated by fan 2026, spray 2054, and screen 2024 may exceed the required flow rate of the cylinders 2014, 2016, and 2018 (e.g., by sizing the flow rate to the peak required intake flow of the cylinders) such that excess foam may be generated. This excess foam may be recycled by running through louver 2032, foam breakdown mechanism 2036, and separation chamber 2024.

During operation of system 2000 as an expander (e.g., to generate energy from the pressure potential energy of compressed air), louver 2030 will typically be closed to prevent backflow through the foam generation equipment 2024, 2028, 2026. After expansion of air in the cylinder pairs 2002, 2004, and 2006, foam 2034 at low pressure (e.g., approximately 5 psig for an instant and then approximately atmospheric thereafter) exits the low-pressure cylinders 2014, 2016, and 2018, passes through the manifold 2022, and enters the separation chamber 2024. In the separation chamber 2024, the low-pressure foam 2034 encounters the foam breakdown mechanism 2036 and is separated into its gas and liquid 2038 components. This separation may not be complete, but at minimum the foam expansion ratio will be drastically reduced (e.g., from a 400:1 expansion ratio foam to a 2:1 expansion ratio foam and air). The liquid 2038 (or low expansion-ratio foam) is conveyed to the reservoir 2042 and the gas component passes through coalescing filter 2052 and is vented through vent 2048.

FIG. 21 is a schematic drawing of an illustrative system 2100 featuring an apparatus for the generation of foam at high pressure (e.g., 750 to 3,000 psig) having a low expansion ratio (e.g., 8:1 to 2:1) corresponding to a moderate liquid-to-air mass ratio (e.g., 2:1). System 2100 includes three two-cylinder subsystems (2102, 2104, 2106), depicted in cross-section as viewed from above in a vertically oriented cylinder arrangement, for the isothermal expansion and compression of gas. The depiction in the illustrative system 2100 of three two-cylinder subsystems is illustrative: other numbers of subsystems, where each subsystem includes one, three, or more cylinders, are also contemplated and within the scope of the invention. Each of the two-cylinder systems 2102, 2104, and 2106 includes a high-pressure cylinder (2108, 2110, and 2112, respectively) and a low-pressure cylinder (2114, 2116, and 2118, respectively). The apparatus for the generation of foam includes or consists essentially of a spray chamber 2120, an optional vent and ball valve 2122, and a manifold 2124 that conducts aqueous foam 2126 to the high-pressure cylinders 2108, 2110, and 2112. A pump 2128 pumps liquid (or optionally air or liquid and air) from a reservoir or other source 2130 to one or more spray heads or other suitable dispersal mechanisms (not depicted) in the spray chamber 2120. Air at high pressure is conducted to the spray chamber 2120 by piping 2132. The passage of high-pressure air through the spray chamber mingles the air with the spray 2134, forming foam 2126. Foam generation at high pressure

and low expansion ratio is robust and the foam may be generated with or without (i) the use of a screen (such as screen 1224 shown in FIG. 12) and/or (ii) the forced flow of air (e.g., foam may be generated in the absence of cylinder 2108, 2110, 2112 piston movement and/or a fan). Spray 2134 may be all liquid, all air, or a mixture of liquid and air and may be sprayed horizontally, vertically upward, vertically downward, or according to other arrangements within the spray chamber 2120. In other embodiments, the high-pressure and low expansion-ratio foam may be generated by mechanical agitation of the liquid and air, such as through the use of a rotating impeller embedded in spray chamber 2120. The foam 2126 may be directed via suitable valves and pipes (not depicted) into chambers of the high-pressure cylinders 2108, 2110, and 2112. Reservoir 2130 may be the same apparatus as the source for high-pressure air (at piping 2132), perhaps separated only by location of the piping (e.g., 2132 is connected to the top of a storage reservoir and 2130 is at the bottom of the reservoir such that mostly high-pressure air is directed through 2132 and mostly high-pressure liquid is directed through pump 2128). The fluid flowing through 2132 may be mostly foam and chamber 2120 may act only to refresh, homogenize, change the expansion ratio of, or otherwise refine the aqueous foam.

In a start-up mode of operation where the manifold 2124 initially contains no foam, gas may be directed out the valve 2122 (rather than into the high-pressure cylinders 2108, 2110, and 2112) during generation of foam until the manifold 2124 is substantially or entirely filled with foam 2126, whereupon the valve 2122 may be closed and the foam 2126 may be directed into the high-pressure cylinders 2108, 2110, and 2112. The high-pressure gas or foam directed out of the valve 2122 may be recirculated back into storage reservoir 2130, into pipe 2132, spray chamber 2120, or otherwise recycled. A pump (not shown) may be used to draw fluid from pipe 2132 through valve 2122 and then return the fluid to reservoir 2130, pipe 2132, or spray chamber 2120 in a recycling loop.

FIG. 22 is a schematic drawing of an illustrative system 2200 featuring an apparatus for the generation of foam at mid pressure (e.g., 200 to 300 psig) having a medium expansion ratio (e.g., 36:1 to 28:1) corresponding to a moderate liquid-to-air mass ratio (e.g., 2:1). System 2200 includes three two-cylinder subsystems (2202, 2204, 2206), depicted in cross-section as viewed from above in a vertically oriented cylinder arrangement, for the isothermal expansion and compression of gas. The depiction in the illustrative system 2200 of three two-cylinder subsystems is illustrative: other numbers of subsystems, where each subsystem includes one, three, or more cylinders, are also contemplated and within the scope of the invention. Each of the two-cylinder systems 2202, 2204, and 2206 includes a high-pressure cylinder (2208, 2210, and 2212, respectively) and a low-pressure cylinder (2214, 2216, and 2218, respectively). The apparatus for the generation of foam includes or consists essentially of a combined spray chamber and manifold 2220 in which foam 2222 is generated or regenerated and which conducts foam 2222 from the high-pressure cylinders 2208, 2210, and 2212 to the low-pressure cylinders 2214, 2216, 2218 (during expansion) or from the low-pressure cylinders 2214, 2216, 2218 to the high-pressure cylinders 2208, 2210, and 2212 (during compression).

During expansion or compression, foam having an intermediate expansion ratio at intermediate pressure enters the chamber/manifold 2220. A pump 2224 draws fluid (e.g., air, foam, or liquid separated from foam in chamber/manifold 2220) and injects the fluid back into chamber/manifold 2220 through nozzles or heads 2226 (or other suitable dispersal mechanisms). The injected fluid 2228 takes up residence in

the chamber/manifold **2220** in the form of a sufficiently stable aqueous foam **2222** that may be directed via suitable valves and pipes (not depicted) into chambers of either the high-pressure cylinders **2208**, **2210**, and **2212** or the low-pressure cylinders **2214**, **2216**, **2218**. Additional components, not shown, may be used to aid in the generation of foam, such as screens, meshes, or solid foams.

Various embodiments employ efficient pumping schemes for the circulation of foam or of heat-exchange liquid that may be foamed. FIG. **23** depicts an illustrative system **2300** that compresses or expands gas. The system **2300** employs a pneumatic cylinder **2304** that contains a slidably disposed piston **2306** that divides the interior of the cylinder **2304** into a distal chamber **2308** and a proximal chamber **2310**. A port or ports (not shown) with associated pipes **2312** and a bidirectional valve **2314** enables gas from a high-pressure storage reservoir **2316** to be exchanged with chamber **2308** as desired. The high-pressure storage reservoir may act as a separator, in which the liquid component of a foam may be separated from the gas component of the foam. In an alternative embodiment, a distinct separator (not shown) component may be employed to separate liquid and gas, and may contain elements to facilitate separation and foam breakdown including baffles, mechanical shear elements, meshes, ultrasonic shear elements, and/or other such elements. A port or ports (not shown) in the end-cap of the air chamber of the cylinder **2304**, with associated pipe **2318** and a bidirectional valve **2320**, enables fluid from the chamber **2308** to be admitted from or exhausted to the ambient atmosphere as desired through a vent **2322**. In alternate embodiments, not shown, vent **2322** is replaced by one or more additional pneumatic cylinders. A port or ports, not shown, enables the interior of the lower chamber **2310** of the pneumatic cylinder **2304** to communicate freely at all times with the ambient atmosphere. In alternate embodiments, cylinder **2304** is double-acting and chamber **2310** is, like chamber **2308**, equipped to exchange, in various states of operation, fluids with either high- or low-pressure reservoirs and/or additional cylinders.

The distal end (i.e., upper end, for the illustrative vertical orientation of cylinder **2304** in FIG. **23**) of a rod **2324** is coupled to the piston **2306**. The proximal (lower) end of rod **2324** may be connected to some mechanism, such as one or more hydraulic cylinders or a crankshaft (not shown), for interconverting linear mechanical power and rotary mechanical power.

In an energy-recovery or expansion mode of operation, storage reservoir **2316** is filled with high-pressure fluid **2326** and a quantity of heat-transfer fluid **2328**. The fluid **2326** may consist essentially or primarily either of gas or of foam. The heat-exchange fluid **2328** may be a liquid that tends to foam when sprayed or acted upon in some other manner. The accumulation of heat-exchange fluid **2328** depicted at the bottom of vessel **2316** may consist essentially or primarily either of liquid or of foam. A quantity of gas may begin to be introduced via valve **2314** and pipe **2312** into the upper chamber **2308** of cylinder **2304** when piston **2306** is near or at the top of its stroke (i.e., “top dead center” of cylinder **2304**). The piston **2306** and its rod **2324** will then be moving downward (the cylinder **2304** may be oriented arbitrarily but is shown vertically oriented in this illustrative embodiment). Heat-exchange fluid **2328** may be injected into chamber **2308** via one or more spray heads **2330**. The spray-head **2330** depicted in FIG. **23** is illustrative only; other devices (e.g., one or more nozzles or a rotating blade) may be used to introduce heat-exchange fluid into the air chamber **2308**. In the illustrative embodiment of FIG. **23**, foam can be generated or regenerated within cylinder **2304** by injection of fluid through a

mechanism (e.g., the spray head **2330**); in various other embodiments, foam is generated externally to cylinder **2304** (by a mechanism not depicted in FIG. **23**). Heat-exchange fluid (liquid or foam) may partially or entirely fill the chamber **2308**. An accumulation of fluid **2332** (liquid or foam) may occur on the upper surface of the piston **2306**.

The system **2300** is instrumented with pressure, piston position, and/or temperature sensors (not shown) and controlled via a control system (not shown). The system **2300** also features a pump cylinder **2334** for supply of pressurized heat-exchange fluid to the spray head **2330**. The pump cylinder **2334** contains a slidably disposed piston **2336** that divides the interior of the cylinder **2334** into an upper chamber **2338** and a lower chamber **2340**. Heat-exchange fluid may partially or entirely fill the upper chamber **2338** of the pump cylinder **2334**. A port or ports (not shown), with associated pipe **2342** and a bidirectional valve **2344**, enables fluid **2346** from a low-pressure reservoir **2348** to be exchanged with chamber **2338** as desired. The reservoir may act as a foam reservoir and/or as separator that divides the liquid component of a foam from the gas component of the foam. A port or ports, not shown, enables the interior of the lower chamber **2340** of the pump cylinder **2334** to communicate freely at all times with the ambient atmosphere. The piston **2336** is coupled to a rod **2350**. The rod **2324** of the pneumatic cylinder **2304** and the rod **2350** of the pump cylinder **2334** may be joined to a single mechanical device (not shown), e.g. a crankshaft, which maintains them in a fixed phase relationship (e.g., rod **2350** may reach its maximum upward displacement whenever rod **2324** reaches its maximum downward displacement). The pump cylinder **2334** may be oriented arbitrarily but is shown vertically oriented in this illustrative embodiment.

Heat-exchange fluid **2346** in the low-pressure reservoir **2348** is mixable and/or exchangeable with heat-exchange fluid **2328** in the high-pressure store **2316**, the accumulation of fluid **2332** in the pneumatic cylinder **2304**, and the fluid within the upper chamber **2338** of the pump cylinder **2334**. That is, all these bodies of fluid are labeled separately for clarity in FIG. **23**, but in the course of operation of the system **2300** may be mingled and exchanged with each other as well as with any heat-exchange fluid present in pipes, valves, and other components of the system **2300**. Preferably, the accumulations **2328**, **2346** of heat-exchange fluid in the two reservoirs **2316**, **2348** in FIG. **23** include or consist essentially of un-foamed (but foamable) heat-exchange liquid.

Two methods of operation of the system **2300**, namely the “open-loop method” and the “closed-loop method,” are described hereinbelow. The two methods described herein are illustrative, not exhaustive, of the methods according to which system **2300** may be operated. Also, the relative timing or phasing of various steps in these two methods of operation as described herein are illustrative: other patterns of relative timing or phasing are contemplated and within the scope of the invention.

Each of these two methods of operation of system **2300** described herein (i.e., closed-loop method and open-loop method) has a compression mode, in which gas is compressed in order to store energy, and an expansion mode, in which gas is expanded to release energy.

Open-Loop Method of Operation: Compression Mode

In an initial state of one mode of operation of the system **2300**, herein termed the “open-loop compression” method of operation, piston **2306** is at top dead center of pneumatic cylinder **2304** and piston **2336** is top dead center of pump cylinder **2334**. Valves **2314**, **2346**, and **2352** are closed, and valves **2320** and **2344** are open. Piston **2306** and piston **2336** move downward, admitting a quantity of low-pressure gas

into chamber 2308 of the pneumatic cylinder 2304 and a quantity of heat-exchange fluid 2346 (preferably liquid) from low-pressure reservoir 2348 into chamber 2338 of the pump cylinder 2334. Downward motion of the piston 2306 to its nethermost limit of motion (i.e., “bottom dead center” position), with filling of chamber 2308 with gas, constitutes an “intake stroke” of cylinder 2304. Downward motion of the piston 2336 to its nethermost limit of motion (i.e., “bottom dead center” position), with filling of chamber 2338 with heat-exchange fluid, constitutes an “intake stroke” of the pump cylinder 2334.

Valves 2320 and 2344 may then be closed and valve 2346 opened, and the pistons 2306 and 2336 may begin upward strokes in their respective cylinders. The upward motion of piston 2306 tends to compress the fluid within chamber 2308 of the pneumatic cylinder 2304, and the upward motion of piston 2336 tends to expel fluid from chamber 2338 of the pump cylinder 2334. Fluid expelled from chamber 2338 of the pump cylinder 2334 passes through valve 2346 and an optional heat exchanger 2354 that may alter the temperature of the fluid. The fluid then passes into chamber 2308 of cylinder 2304 through the spray head 2330, forming a spray 2356. The fluid 2356 either enters the chamber 2308 as a foam or forms a foam by mingling with the gas within chamber 2308. The fluid 2356 may partially or entirely fill chamber 2308 and may form an accumulation of fluid 2332 atop piston 2306. The accumulation of fluid 2332 may include or consist essentially of foam or of liquid separated from foam within chamber 2308.

At a predetermined point in the upward (compression) stroke of piston 2306, valve 2314 may be opened, allowing pressurized fluid, possibly including heat-exchange fluid 2332 (e.g., as the liquid component of a foam), to flow through piping 2312 into the high-pressure store 2316. Heat-exchange fluid 2332 expelled from chamber 2308 by piston 2306 may form or add to the accumulation of fluid 2328 within the high-pressure store 2316. The accumulation of fluid 2328 may include or consist essentially of heat-exchange liquid separated from foam in reservoir 2316.

Upward motion of the piston 2306 to its limit of motion (top dead center), with expulsion of pressurized gas and fluid into store 2316, constitutes a “compression stroke” of pneumatic cylinder 2304. A complete compression stroke in the open-loop method of operation of system 2300 entails one-way or “open-loop” passage of heat-exchange fluid (preferably liquid) 2346 out of the low-pressure reservoir 2348, through chamber 2338 of the pump cylinder 2334, through the optional heat exchanger 2354, into chamber 2308 of the pneumatic cylinder 2304, and into the high-pressure store 2316, successively. During one or more successive cycles of system 2300 in open-loop compression mode as described hereinabove, heat-exchange liquid 2328 may accumulate in the high-pressure store 2316.

The sequence of operations described above for the compression mode of the closed-loop method of operation is illustrative, and may be varied in this and other embodiments. Sequences of operations described for other modes and methods of operation below are also illustrative and might be varied in other embodiments.

Open-Loop Method of Operation: Expansion Mode

In an initial state of another mode of operation of the system 2300, herein termed the “open-loop expansion” mode of operation, piston 2306 is at top dead center of pneumatic cylinder 2304 and piston 2336 is at bottom dead center of pump cylinder 2334. Chamber 2338 of pump cylinder 2334 is filled with heat-exchange fluid (preferably liquid). Valves 2320, 2344, and 2352 are closed and valves 2314 and 2346 are

open. Piston 2306 moves downward, admitting a quantity of high-pressure gas into chamber 2308 of the pneumatic cylinder 2304. Simultaneously, piston 2336 of the pump cylinder 2334 moves upward. Heat-exchange fluid from chamber 2338 passes through valve 2346, optional heat exchanger 2354, and spray head 2330 to enter chamber 2308 of the pneumatic cylinder. At some subsequent, predetermined point, valve 2314 may be closed while piston 2306 continues its downward motion and piston 2336 continues its upward motion.

The motion of piston 2306 from top dead center to bottom dead center of pneumatic cylinder 2304 during and after the introduction into chamber 2308 of high-pressure gas (or foam) from store 2316 is herein termed an “expansion stroke” of pneumatic cylinder 2304. The motion of piston 2336 from bottom dead center to top dead center of pump cylinder 2334 is herein termed a “pumping stroke” of pump cylinder 2334. The expansion stroke of pneumatic cylinder 2304 and the pumping stroke of pump cylinder 2334, as well as other cylinder strokes of this and other embodiments described herein, may be of equal duration and may begin and end simultaneously, or they may be of different durations and may not begin or end simultaneously.

Subsequent to the completion of the expansion stroke and pumping stroke, valves 2314 and 2346 may be closed and valves 2320 and 2352 opened. Piston 2306 of the pneumatic cylinder then moves from bottom dead center to top dead center while the fluid within chamber 2308 is expelled. Preferably, the expelled fluid includes or consists essentially of foam and enters vessel 2348, where it is separated into its gas and liquid components so that its gas component may be exhausted through vent 2322 and its liquid component 2332 may accumulate as liquid 2346 in the low-pressure reservoir 2348. Upward motion of the piston 2306 from bottom dead center to top dead center with expulsion of low-pressure gas and liquid from chamber 2308 constitutes an “exhaust stroke” of cylinder 2304. Concurrently, cylinder 2334 performs an intake stroke, i.e., piston 2336 moves from top dead center to bottom dead center and chamber 2336 fills with heat-exchange fluid (preferably liquid) 2328 from the high-pressure store 2316.

An expansion stroke of cylinder 2304 in the open-loop method of operation of system 2300 entails one-way or “open-loop” passage of heat-exchange fluid 2328 out of the high-pressure store 2316, through chamber 2338 of the pump cylinder 2334, through the optional heat exchanger 2354, into chamber 2308 of the pneumatic cylinder 2304, and into the low-pressure reservoir 2348, successively. During one or more successive cycles of system 2300 in open-loop expansion mode, heat-exchange fluid 2328 is removed from the high-pressure store 2316 and accumulates as liquid 2346 in the low-pressure reservoir 2348. A period of operation of system 2300 in open-loop compression mode will tend to cause an accumulation 2328 of heat-exchange liquid in the high-pressure store 2316; a subsequent period of operation of system 2300 in open-loop expansion mode will tend to remove the accumulation 2328 of heat-exchange liquid from the high-pressure store 2316 and return it to the low-pressure reservoir 2348.

Closed-Loop Method of Operation: Compression Mode

In an initial state of another mode of operation of the system 2300, herein termed the “closed-loop compression” method of operation, piston 2306 is at top dead center of pneumatic cylinder 2304 and piston 2336 is top dead center of pump cylinder 2334. Valves 2314, 2344, and 2346 are closed, and valves 2320 and 2352 are open. Piston 2306 and piston 2336 move downward, admitting a quantity of low-pressure

fluid (gas or foam) into chamber **2308** of the pneumatic cylinder **2304** and a quantity of heat-exchange fluid (preferably liquid) **2328** from high-pressure store **2316** into chamber **2338** of the pump cylinder **2334**. Pneumatic cylinder **2304** performs an intake stroke and pump cylinder **2334** performs an intake stroke.

Valves **2320** and **2352** may then be closed and valve **2346** opened, and the pistons **2306** and **2336** may begin upward strokes in their respective cylinders. The upward motion of piston **2306** tends to compress the fluid within chamber **2308** of the pneumatic cylinder **2304**, and the upward motion of piston **2336** tends to expel fluid from chamber **2338** of the pump cylinder **2334**. Fluid expelled from chamber **2338** of the pump cylinder **2334** passes through valve **2346** and an optional heat exchanger **2354** that may alter the temperature of the fluid. The fluid then passes into chamber **2308** of cylinder **2304** through spray head **2330**. The fluid may partially or entirely fill chamber **2308** with foam. An accumulation **2332** of fluid may form on top of piston **2306**. At a predetermined point in the upward (compression) stroke of piston **2306**, valve **2314** may be opened, allowing pressurized gas and/or foam to flow through piping **2312** into the high-pressure store **2316**. Heat-exchange fluid **2332** expelled from chamber **2308** by piston **2306** may form an accumulation of fluid **2328** within the high-pressure store **2316**. The accumulation of fluid **2328** may include or consist essentially of foam or of liquid separated from foam within reservoir **2316**.

Upward motion of the piston **2306** to its limit of motion (top dead center), with expulsion of pressurized fluid into store **2316**, constitutes a “compression stroke” of pneumatic cylinder **2304**. A compression stroke in the closed-loop method of operation of system **2300** entails cyclic or closed-loop passage of heat-exchange fluid (preferably liquid) **2328** out of chamber **2308** of the pneumatic cylinder **2304**, into the high-pressure store **2316**, into chamber **2338** of the pump cylinder **2334**, through the optional heat exchanger **2354**, and into chamber **2308** of the pneumatic cylinder **2304** successively.

Closed-Loop Method of Operation: Expansion Mode

In an initial state of another mode of operation of the system **2300**, herein termed the “closed-loop expansion” mode of operation, piston **2306** is at top dead center of pneumatic cylinder **2304** and piston **2336** is at bottom dead center of pump cylinder **2334**. Chamber **2338** of pump cylinder **2334** is filled with heat-exchange fluid. Valves **2320**, **2344**, and **2352** are closed and valves **2314** and **2346** are open. Piston **2306** moves downward, admitting a quantity of high-pressure gas (or foam) into chamber **2308** of the pneumatic cylinder. Simultaneously, piston **2336** moves upward. Heat-exchange fluid (preferably liquid) from chamber **2338** passes through valve **2346**, optional heat exchanger **2354**, and spray head **2330** to enter chamber **2308** of the pneumatic cylinder. At some subsequent, predetermined point, valve **2314** may be closed while piston **2306** continues its downward motion and piston **2336** continues its upward motion. Pneumatic cylinder **2304** performs an expansion stroke and pump cylinder **2334** performs a pumping stroke.

Subsequent to the completion of the expansion stroke of cylinder **2304** and the pumping stroke of pump cylinder **2334**, valves **2314** and **2346** may be closed and valves **2320** and **2352** opened. Piston **2306** of the pneumatic cylinder **2304** then moves from bottom dead center to top dead center while the low-pressure fluid within chamber **2308** is expelled through pipe **2318**. Preferably, the expelled fluid includes or consists essentially of foam and enters vessel **2348**, where it is separated into its gas and liquid components so that its gas component may be exhausted through vent **2322** and its liquid

component **2332** may accumulate as liquid **2346** in the low-pressure reservoir **2348**. Pneumatic cylinder **2304** performs an exhaust stroke. Simultaneously, the pump cylinder **2334** performs an intake stroke.

An expansion stroke in the closed-loop method of operation of system **2300** entails cyclic or “closed-loop” passage of heat-exchange fluid **2332** out of chamber **2308** of the pneumatic cylinder **2304**, into the low-pressure reservoir **2348**, through chamber **2338** of the pump cylinder **2334**, through the optional heat exchanger **2354**, and into chamber **2308** of the pneumatic cylinder **2304** successively.

Various other embodiments employ a pneumatic cylinder that also acts as a pump in order to efficiently circulate heat-exchange fluid (e.g., foam or a foaming liquid) in an energy storage system. FIGS. **24A** and **24B** depict a pneumatic cylinder **2400** that compresses or expands gas and simultaneously acts as a liquid pump. FIG. **24A** depicts one state of operation of cylinder **2400**; FIG. **24B** depicts another state of operation of cylinder **2400**.

The cylinder **2400** contains a slidably disposed piston **2406** that divides the interior of the cylinder **2400** into a distal (upper) chamber **2408** and a proximal (lower) chamber **2410**. A port or ports (not shown) with associated piping **2412** and bidirectional valves **2414**, **2416** enables the upper chamber **2408** to be placed in fluid communication with either (a) a high-pressure fluid storage reservoir (not shown, but indicated by the letters “HP”) or (b) a low-pressure fluid reservoir (not shown, but indicated by the letters “LP”). The LP reservoir may contain liquid at low pressure and its gaseous portion may communicate freely with the ambient atmosphere through a vent (not shown). A port or ports (not shown) places the lower chamber **2410** of the first cylinder in continuous fluid communication with gas at low pressure (e.g., the ambient atmosphere). Cylinder **2400** incorporates a tube **2418** that may be cylindrical in cross-section and is connected at its upper end to the upper end-cap of the cylinder **2400**. The tube **2418** is hollow and may be filled with heat-exchange liquid.

The piston **2406** is connected to a rod **2422** that contains a center-drilled hollow or cavity **2420**, herein termed the rod cavity **2420**, that may be filled with heat-exchange liquid. The tube **2418** is open at its proximal (lower) end, and is long enough so that the cavity within the tube **2418** is in constant fluid communication with the rod cavity **2420** (e.g., even when piston **2406** is at bottom dead center). Gasketing **2424** allows the tube **2418** to telescope within the rod **2422** as the rod **2422** and piston **2406** move and prevents fluid communication between the upper chamber **2408** and the communicating cavities of the tube **2418** and rod **2422**. When piston **2406** and rod **2422** move upward, as depicted in FIG. **24A**, the total volume of the communicating cavities within the tube **2418** and the rod **2422** decreases, tending to pressurize the fluid within the communicating cavities and to expel it from the communicating cavities through the tube **2418**. When piston **2406** and rod **2422** move downward, as depicted in FIG. **24B**, the total volume of the communicating cavities within the tube **2418** and the rod **2422** will increase, tending to lower the pressure of the fluid within the communicating cavities and/or to admit fluid into the communicating cavities through the tube **2418**. By integrating the pump into a rod of a cylinder, higher efficiency may be achieved by eliminating separate or additional crankshaft throws or other mechanical drive connections.

FIG. **25** depicts a system **2500** that employs two cylinders of the type depicted in FIGS. **24A** and **24B** to compress and/or expand gas. Unlike system **2300** in FIG. **23**, system **2500** does

not employ a discrete or separate water pump (e.g., pump cylinder 2334 in FIG. 23) in order to efficiently circulate heat-exchange liquid.

The system 2500 employs two cylinders 2402, 2404 (hereinafter termed the first cylinder and the second cylinder), both cylinders 2402, 2404 being similar to the cylinder 2400 depicted in FIGS. 24A and 24B. The second cylinder 2404 contains a slidably disposed piston 2426 that divides the interior of the second cylinder 2404 into a distal (upper) chamber 2428 and a proximal (lower) chamber 2430. A port or ports (not shown) with associated pipe 2432 and bidirectional valves 2434, 2436 enables the upper chamber 2428 to be placed in fluid communication with either (a) a high-pressure fluid storage reservoir (not shown, but indicated by the letters "HP"), preferably the same as that to which the first cylinder 2402 may be connected through valve 2414, or (b) a low-pressure fluid reservoir (not shown, but indicated by the letters "LP"), preferably the same as that to which the first cylinder 2402 may be connected through valve 2416. The LP reservoir may contain liquid at low pressure and its gaseous portion may communicate freely with the ambient atmosphere through a vent (not shown). A port or ports (not shown) places the lower chamber 2430 in continuous fluid communication with gas at low pressure (e.g., the ambient atmosphere).

Cylinder 2404 also, like cylinder 2402, incorporates a hollow tube 2438 that may be cylindrical in cross-section and is connected at its upper end to the distal end-cap of the cylinder 2404. The interior of the tube 2438 may be filled with heat-exchange liquid. The piston 2426 is connected to a rod 2442 that contains a center-drilled rod cavity 2440 that may be filled with heat-exchange liquid. The tube 2438 is open at its lower end and the cavity within the tube 2438 is in fluid communication with the rod cavity 2440. Gasketing 2443 allows the tube 2438 to telescope within the rod 2442 and piston 2426 move and prevents fluid communication between the upper chamber 2428 and the communicating cavities of the tube 2438 and rod 2442. When piston 2426 and rod 2442 move upward, the total volume of the communicating cavities within the tube 2438 and the rod 2442 will decrease, tending to pressurize the fluid therein.

The upper end of tube 2418 in the first cylinder 2402 is connected to bidirectional valves 2444, 2446, 2448. Valve 2444 may place the interior of tube 2418 in fluid communication with a high-pressure storage reservoir (HP); valve 2446 may place the interior of tube 2418 in fluid communication with a low-pressure reservoir (LP); and valve 2448 may permit fluid to flow from the interior of the tube 2418, through optional heat exchanger 2450, and thence to a spray head 2452 within chamber 2428 of the second cylinder 2404. Foaming liquid 2454 passing through spray head 2452 enters chamber 2428. The spray heads 2452, 2464 depicted in FIG. 25 are illustrative only: other devices (e.g., rotating blades) may be used to introduce heat-exchange fluid into the air chambers 2408, 2428. In the illustrative embodiment of FIG. 25, foam may be generated or regenerated within cylinders 2402, 2404 by injection of fluid through an appropriate mechanism (e.g., the spray heads 2452, 2464); in various other embodiments, foam is generated externally to the cylinders 2402, 2404 (as described elsewhere herein) by mechanisms not depicted in FIG. 25.

Similarly, the upper end of tube 2438 in cylinder 2404 is connected to bidirectional valves 2456, 2458, 2460. Valve 2456 may place the interior of tube 2438 in fluid communication with a high-pressure storage reservoir (HP), preferably the same as that with which tube 2418 communicates via valve 2444; valve 2458 may place the interior of tube 2438 in

fluid communication with a low-pressure reservoir (LP), preferably the same as that with which tube 2418 communicates via 2446; and valve 2460 may permit fluid to flow from the interior of the tube 2438, through optional heat exchanger 2462, and thence to spray head 2464 within chamber 2408 of cylinder 2402. Liquid passing through spray head 2464 enters chamber 2408, preferably forming a foam within the chamber 2408.

The valves 2444, 2456 permit fluid communication with that portion of the HP store to which heat-exchange liquid may settle (e.g., separate from a foam) under the influence of gravity, and therefore tend to control the passage of liquid rather than of gas or foam.

The system 2500 is instrumented with pressure, piston position, and/or temperature sensors (not shown) and controlled via a control system (not shown). The proximal (lower) ends of the rods 2422, 2442 may be connected to a mechanism, such as one or more hydraulic cylinders or a common crankshaft (not shown), for interconverting linear mechanical power and rotary mechanical power, as described in the '678 and '842 patents.

System 2500 may be operated in such a way that the cavity 2420 within rod 2422 of the first cylinder 2402 acts as a pump driving heat-exchange fluid into chamber 2428 of second cylinder 2404 during expansion or compression of gas in chamber 2428, and the cavity 2440 within rod 2442 of second cylinder 2404 acts as a pump driving heat-exchange liquid into chamber 2408 of first cylinder 2402 during expansion or compression of gas in chamber 2408. A discrete or separate pump for circulating heat-exchange liquid is rendered unnecessary by this method.

Like system 2300 in FIG. 23, system 2500 may be operated according to at least two methods of operation, namely the "open-loop method" and the "closed-loop method." These two methods of operation are exemplary, not exhaustive, of the methods according to which system 2500 may be operated. Each of these two methods of operation of system 2500 (i.e., closed-loop method and open-loop method) has a compression mode, in which gas is compressed in order to store energy, and an expansion mode, in which gas is expanded to release energy.

Open-Loop Method of Operation: Expansion Mode

In one mode of operation of the system 2500, herein termed the "open-loop expansion" method of operation, the second cylinder 2404 performs an expansion stroke while the first cylinder 2402 performs an exhaust stroke and sprays foaming heat-exchange liquid into the second cylinder 2404: the two cylinders may then reverse roles, and may alternate intake and expansion strokes for as long as expansion of gas by system 2500 is desired.

In an initial state of operation of the open-loop expansion method of operation, piston 2406 of the first cylinder 2402 is at bottom dead center and piston 2426 of the second cylinder 2404 is at top dead center. Valves 2416, 2448, 2458, and 2434 are open and all other valves are closed. Valve 2416 allows low-pressure air to exit chamber 2408 of the first cylinder 2402 while piston 2406 performs an upward (exhaust) stroke; valve 2448 allows heat-exchange liquid to flow from the rod cavity 2420 of the first cylinder 2402, through optional heat exchanger 2450, and through the spray head 2452 of the second cylinder 2404, preferably forming a foam 2454 therein; valve 2458 allows heat-exchange fluid from the low-pressure (LP) reservoir to enter the rod cavity 2440 of the second cylinder 2404; and valve 2434 allows gas from the high-pressure store to enter the upper chamber 2428 of the second cylinder 2404. In this initial state of operation, a liquid accumulation 2466 may be present atop piston 2406 and a

liquid accumulation **2468** atop piston **2426** is slight or absent. Subsequent to this initial state of operation, the foam **2454** may enable isothermal expansion of the gas within chamber **2428** and may form a fluid accumulation **2468** atop the piston **2426**.

At a predetermined point during the expansion stroke of the second cylinder **2404**, valve **2434** may be closed, preventing the admission of more high-pressure gas to the upper chamber **2428**. Gas already admitted to the chamber **2428** will continue to expand, and piston **2426** and its associated rod **2442** move downward until they reach bottom dead center. Concurrently, piston **2406** and its associated rod **2422** move to top dead center, performing an exhaust stroke. Any liquid accumulation **2466** atop piston **2406** of the first cylinder **2402** will be expelled into the LP reservoir during the latter portion of the exhaust stroke.

By opening valves **2414**, **2460**, **2436**, and **2446** and closing all other valves, system **2500** may then be placed in a state of operation similar to the initial state of operation of the open-loop expansion method of operation described above, except that the roles of the two cylinders are reversed: i.e., first cylinder **2402** is prepared to execute an expansion stroke and the second cylinder **2404** is prepared to execute an exhaust stroke. Expansion cycles in which the first cylinder **2402** expands gas may alternate indefinitely (limited by the capacity of the HP store) with expansion cycles in which the second cylinder **2404** expands gas.

While the second cylinder **2404** performs an expansion stroke, heat-exchange fluid at low pressure fills the rod cavity **2440** of the second cylinder **2404** through valve **2458**. Concurrently, heat-exchange fluid in the rod cavity **2420** of the first cylinder **2402** is pressurized and expelled through valve **2448**. Thus, the first cylinder **2402**, during its exhaust stroke, acts as a pump supplying heat-exchange liquid to the second cylinder **2402** as the latter performs an expansion stroke. Similarly, when the second cylinder **2404** performs an exhaust stroke while the first cylinder **2402** performs a concurrent expansion stroke, the second cylinder **2404** acts as a pump supplying heat-exchange liquid to the first cylinder **2402**.

Open-Loop Method of Operation: Compression Mode

In another mode of operation of the system **2500**, herein termed the “open-loop compression” method of operation, the two cylinders **2402**, **2404** perform concurrent compression strokes while injecting heat-exchange fluid into each other’s upper chambers **2408**, **2428**. The two cylinders then perform concurrent gas intake strokes while refilling their rod chambers **2420**, **2440** with heat-exchange liquid.

In an initial state of operation in open-loop compression mode, pistons **2406**, **2426** are both at bottom dead center of their respective cylinders **2402**, **2404**, and any liquid accumulations **2466**, **2468** atop the pistons **2406**, **2426** are slight or absent. Valves **2448** and **2460** are open and all other valves are closed. The upper chambers **2408**, **2428** of the cylinder contain gas at low pressure. Pistons **2406**, **2426** and their associated rods **2422**, **2442** begin to move upward, tending to pressurize the fluid in the upper chambers **2408**, **2428** of the cylinders **2402**, **2404**. Heat-exchange liquid expelled from the rod cavities **2420**, **2440** passes through the tubes **2418**, **2438**, valves **2448**, **2460**, optional heat exchangers **2450**, **2462**, and spray heads **2464**, **2452**, injecting fluid (preferably as foam, e.g., foam **2454**) into the chambers **2408**, **2428**. This foam may enable isothermal expansion of the gas within chambers **2408**, **2428** and may form fluid (foam and/or liquid) accumulations **2466**, **2468** atop the pistons **2406**, **2426**. At a predetermined point in the concurrent compression strokes of the pistons **2406**, **2426**, valves **2414**, **2434** may be opened,

allowing pressurized fluid (gas or foam) to flow into the high-pressure (HP) store (not shown). Heat-exchange fluid **2466**, **2468** expelled from chambers **2408**, **2428** by pistons **2406**, **2426** may cause an accumulation of fluid (e.g., separated liquid) to form within the HP store.

Pistons **2406**, **2426** move upward during the concurrent compression strokes executed by the two cylinders **2402**, **2404** until the pistons **2406**, **2426** are at top dead center of their respective cylinders **2402**, **2404**. In a subsequent state of operation, valves **2416**, **2446**, **2458**, and **2436** are opened and all other valves are closed, and the pistons **2406**, **2426** and their associated rods **2422**, **2442** move downward until they reach bottom dead center of their respective cylinders **2402**, **2404**, filling the upper chambers **2408**, **2428** with low-pressure gas and the rod cavities **2420**, **2440** with low-pressure heat-exchange liquid from the low-pressure (LP) reservoir, thus preparing the system for another concurrent compression stroke.

A compression stroke in the open-loop method of operation of system **2500** entails one-way or “open-loop” passage of heat-exchange fluid out of the LP reservoir, into the rod cavities **2420**, **2440** of the cylinders **2402**, **2404**, through the spray heads **2464**, **2452** into the upper chambers **2408**, **2428** of the cylinders **2402**, **2404**, and thence into the HP store, successively. During one or more successive cycles of system **2500** in open-loop compression mode, heat-exchange liquid is thus removed from the LP reservoir and accumulates in the HP store. A period of operation of system **2500** in open-loop compression mode (e.g., a number of such cycles) will tend to cause an accumulation of heat-exchange liquid in the HP store; a subsequent period of operation of system **2500** in open-loop expansion mode will tend to remove the accumulation of heat-exchange liquid from the HP store and return it to the LP reservoir.

It will be apparent to any person reasonably well acquainted with the art of hydraulic machinery that system **2500** may also be operated according to a closed-loop method having both expansion and compression modes. Such a method of operation will (i) shift accumulated heat-exchange liquid **2466**, **2468** into the HP store during each compression and refill the rod cavities **2420**, **2440** of the cylinders **2402**, **2404** from the HP store rather than from the LP reservoir, and/or (ii) shift accumulated heat-exchange liquid **2466**, **2468** into the LP reservoir during each expansion and refill the rod cavities **2420**, **2440** of the cylinders **2402**, **2404** from the LP reservoir rather than from the HP store.

The use of cylinders **2402**, **2404** for both gas expansion/compression and heat-exchange fluid pumping may increase system efficiency and reliability as compared to a system employing a discrete or separate pump for the circulation of heat-exchange fluid, due to the reduction in the number of mechanisms within the energy storage and recovery system.

When a fluid (e.g., foam) is to either enter or exit the air chamber of a pneumatic cylinder through a valve, it is desirable, as discussed earlier, that pressure drop through the valve be minimal, in order that energy losses entailed by passing through may be minimized. Furthermore, if the fluid to be passed through the valve is a foam, it may be advantageous to minimize shear forces acting on the foam, in order to prevent the foam from being separated into its liquid and gas components, or in order to prevent the sizes of bubbles within the foam from being inadvertently altered. Moreover, where a liquid phase is present in the air chamber of a pneumatic cylinder as well as a gas phase (e.g., in cylinders employing foams for heat exchange between liquid and gas), it is desirable that valve check passively open to prevent damage to components from overpressure in the cylinder, i.e., hydrolock

events. Valve designs that enable high-efficiency, low-shear flow of foam with hydrolock protection are described in U.S. patent application Ser. No. 13/307,163, filed Nov. 30, 2011 (the '163 application), the entire disclosure of which is incorporated by reference herein, and may be utilized in embodiments of the present invention.

FIG. 26 is a schematic representation of a pneumatic cylinder head 2600 featuring two valves 2602, 2604 of types described in the '163 application, a high-side valve 2602 and a low-side valve 2604. The high-side valve 2602 is a pull-to-open valve that passively checks open to mitigate overpressure within the cylinder air chamber (i.e., hydrolock). The low-side valve 2604 is a push-to-open valve that passively checks open when pressure is lower inside the cylinder than outside (e.g., during an intake stroke). Valves 2602 and 2604 may be designed for rapid action and with high lift (i.e., with a large area permitting flow between the valve member and valve seat in the open position) in order to minimize pressure drop through the valve (and thus energy losses). High lift also reduces shear forces on foam flowing into or out of the air chamber of the cylinder, preserving foam integrity.

FIG. 27 is a schematic diagram of portions of an illustrative compressed-air energy-storage system 2700 that incorporates various embodiments of the invention. The system 2700 includes a high-pressure pneumatic cylinder assembly 2702 (labeled HP in FIG. 27) that expands and compresses gas between some mid pressure (e.g., approximately 200 psig) and some high pressure (e.g., approximately 3,000 psig); a low-pressure pneumatic cylinder assembly 2704 that expands and compresses gas between some low pressure (e.g., approximately 0 psig) and some mid pressure (e.g., approximately 200 psig); a mid-pressure vessel 2706 (labeled MPV in FIG. 27) that typically contains fluid (e.g., gas, heat-exchange liquid, foam, or separated gas and liquid) at the mid pressure of the system; a storage reservoir 2708 or intercommunicating set of storage reservoirs (e.g., sealed lengths of piping rated for storage or transport of high-pressure gas) and capable of storing fluid at high pressure and mildly elevated temperature (e.g., 50° C.), and thus of acting as both a store of pressure potential energy and thermal energy; a storage vessel/spray reservoir 2710 (e.g., a tank) capable of holding an appropriate quantity of heat-exchange liquid at a relatively low temperature (e.g., 20° C.). The spray reservoir 2710 preferably includes mechanisms for separating a low-pressure foam into liquid and gas components and venting the gas component to the atmosphere (indicated by dashed arrow 2712). In FIG. 27, dashed arrows represent the bidirectional movement of gas through appropriate piping and solid arrows represent the bidirectional movement of liquid through appropriate piping; pairs of dashed and solid arrows (2714, 2716, 2718, 2720) indicate movement of gas and liquid between various components of system 2700. The spray reservoir 2710 may exchange both liquid and gas (e.g., as separate flows of liquid and gas or as a single flow of aqueous foam) with the low-pressure cylinder 2704, the low-pressure cylinder 2704 may exchange liquid and gas with the mid-pressure vessel 2706, the mid-pressure vessel 2706 may exchange liquid and gas with the high-pressure cylinder 2702, and the high-pressure cylinder 2702 may exchange liquid and gas with the high-pressure store 2708.

In FIG. 27, the high-pressure cylinder 2702, the mid-pressure vessel 2706, and the low-pressure vessel 2704 are portions of a "power unit," i.e., that subsystem of energy storage system 2700 which interconverts thermal and pressure potential energy with mechanical work and electrical energy. In a mode of operation where thermal and pressure potential energy from warm, high-pressure fluid in the high-pressure

store 2708 are converted to electrical energy, a quantity of fluid is transferred from the high-pressure store 2708 to the high-pressure cylinder 2702. The fluid typically includes or consists essentially of both gas and liquid that are at approximately identical temperature and pressure. The gas and liquid may be combined into a foam prior to admission to the high-pressure cylinder 2702 or may be foamed within the cylinder 2702. The cylinder 2702 expands its contents (e.g., foam substantially or entirely filling the air chamber of cylinder 2702) from the original high pressure (e.g., approximately 3,000 psig) to a mid-pressure (e.g., 200 psig). As the gas component of the foam with the cylinder 2702 expands, performing work upon a moving piston within cylinder 2702, it tends to cool; however, as a temperature difference appears between the gas and liquid components of the foam, thermal energy flows from the liquid to the gas component. The larger the temperature difference, the faster the flow of thermal energy from liquid to gas will tend to be. Thus, the mingling of liquid and gas in an aqueous foam structure within cylinder 2702 will tend to allow substantially isothermal expansion of the gas component of the foam, effectively transforming a portion of the thermal energy in the liquid admitted to cylinder 2702 into mechanical work.

When the contents of the cylinder 2702 have reached the mid-pressure of the system 2700, liquid and gas (e.g., as foam) at the mid-pressure are transferred (arrows 2718) to the mid-pressure vessel 2706. The mid-pressure vessel stores the liquid and gas and may include provisions for regenerating foam or for separating foam into its gas and liquid components. Whenever the mid-pressure vessel 2706 contains a sufficient quantity of gas at the mid-pressure, a quantity of gas is transferred from the mid-pressure vessel 2706 to the low-pressure cylinder 2704. The gas is mingled with heat-exchange liquid from the mid-pressure vessel 2706 to form a foam that substantially or entirely fills the air chamber of the low-pressure cylinder 2704. As in the high-pressure cylinder 2702, only across a different pressure range, the gas within the low-pressure cylinder 2704 is expanded, performing work upon a moving piston with the cylinder 2704, as the liquid component of the foam tends to make the expansion of the gas approximately isothermal. After expansion of the gas in the low-pressure cylinder 2704, the liquid and gas within the cylinder 2704 are at relatively low temperature and approximately atmospheric pressure, and are then transferred (arrows 2714) to the spray reservoir and foam separator 2710. The low-pressure gas component of the foam is vented to the atmosphere (arrow 2712) and the low-pressure liquid component of the foam is retained. If the retained liquid is cooler than the ambient (environmental) temperature of the system 2700 at a time when the system 2700 is to be operated in an energy-generating mode, then the liquid in the spray reservoir 2710 constitutes a store of exergy (potential work), as does the store of hot liquid in the high-pressure store 2708. The storage reservoirs 2708 and 2710 may be insulated in order to slow the loss of exergy that occurs as their contents warm or cool toward the temperature of the ambient environment. The number of compression and/or expansion stages, i.e., 2 stages, depicted in FIG. 27 is illustrative. Additional expansion and compression stages and mid-pressure vessels may be added to further divide the pressure ranges (e.g., 3 compression/expansion stages—0 to 80 psig, 80 psig to 500 psig, and 500 to 3000 psig, with mid-pressure vessels at approximately 80 psig and 500 psig).

Similarly, system 2700 may store energy by admitting atmospheric air (arrow 2712) and compressing it sequentially in cylinders 2704 and 2702. FIG. 28 shows a schematic representation of portions of the system 2700 already depicted in

FIG. 27, and attaches a time-versus-temperature graph 2800 to partially describe the stages of a hypothetical two-stage compression. Pairs of thin lines converging from portions of graph 2800 to portions of the schematic representation of system 2700 indicate which portions of graph 2800 represent changes in temperature occurring in which portions of system 2700. In graph 2800, dashed lines represent the temperature of gas, and solid lines represent the temperature of heat-exchange liquid.

The graph 2800 begins at time $T=0$, the beginning of a compression stroke in the low-pressure cylinder 2704. The cylinder contains a foam of which the gas and liquid components are both at the same low pressure (approximately atmospheric) and the same relatively low temperature (approximately 25° C.). From $T=0$ milliseconds (ms) to approximately $T=290$ ms, the foam is compressed in the cylinder 2704. The rising temperature of the gas is represented by the dashed curve 2804. As the temperature of the gas rises, heat is transferred to the liquid component of the foam, whose temperature is represented by the solid curve 2806. The curve 2804 clearly shows that the temperature of the gas is not constant, that is, that the compression of the gas is not purely isothermal; however, it is substantially or approximately isothermal in comparison to the temperature change that would occur if the gas underwent the compression adiabatically. In the adiabatic case, the temperature of the gas would rise not to approximately 55° C., but to approximately 295° C. Thus, the compression process undergone by the gas in cylinder 2704 may reasonably be termed "substantially isothermal," with polytropic coefficient less than $n=1.05$, and realizes significant efficiency gains over the adiabatic case. These gains are not as large as they would be for a perfectly isothermal compression (which would take infinite time).

The difference between the solid line 2806 and dashed line 2805 (liquid and gas temperatures, respectively) represents lost exergy that cannot be recovered during a subsequent expansion. The minimization of this lost exergy is achieved when the process time constant (in this case, a compression occurs in about 290 ms) is considerably less than the heat-transfer time constant. The heat-transfer time constant depends in part on the surface area and proximity between the compressing or expanding gas and the liquid. Small droplets or a foam matrix maximize this surface area. In general, spheroidal droplets will have a lower surface area than a matrix of foam cells; thus a foam matrix may result in a lower heat transfer time constant, less lost exergy, and a more efficient energy storage system.

Graph 2800 in FIG. 28 shows that compression ceases at approximately $T=290$ ms, as the gas and liquid mixture is transferred to the mid-pressure vessel. The gas quickly approximates the temperature of the liquid, as shown by the precipitous drop of dashed curve 2804 from approximately $T=290$ ms to approximately $T=300$ ms. The foam (and any separated liquid) in cylinder 2704 are then contained in the mid-pressure vessel 2706. The foam may be regenerated within the mid-pressure vessel at approximately constant pressure and temperature (depending on the size of the mid-pressure vessel, presumably sized sufficiently large to prevent large fluctuations in pressure during a single intake or exhaust from a LP or HP cylinder) and transferred to the HP cylinder 2702. By approximately $T=700$ ms, the air chamber of the HP cylinder 2702 is filled substantially or entirely with foam and a compression stroke begins. Similarly to the compression in the LP cylinder 2704, the temperature of the gas component of the foam rises as shown by dashed curve 2810 (such temperature rise being significantly mitigated compared to

the case of adiabatic compression), the temperature of the liquid component of the foam rises as shown by solid curve 2812, and the temperatures of the gas and liquid components of the foam quickly equilibrate after compression ceases, as shown by the precipitous drop in the dashed curve 2810 from approximately $T=950$ ms to approximately $T=1000$ ms. The difference between the solid line 2812 and dashed line 2810 (liquid and gas temperatures, respectively) represents lost exergy that cannot be recovered during a subsequent expansion. Thereafter, the liquid and gas contents of the HP cylinder 2702 are stored within the high-pressure storage and thermal well 2708, remaining at approximately constant temperature and pressure as shown by solid curve 2814.

The system 2700 thus uses heat-exchange liquid, foamed with gas during expansion and compression of the gas, both as an exergy storage medium and to enable rapid, approximately isothermal expansion and compression of gas. Moreover, heat from a variety of external sources (e.g., solar heat, waste heat from fuel-burning power plants) may be transferred to the fluid in reservoir 2708. Thermal energy thus added to fluid in reservoir 2708 may be partly realized as useful work in the cylinders 2702 and 2704, and thus as electrical power output from the system 2700. In another embodiment, additional thermal energy may be transferred to the fluid in storage 2708 in the form of low-grade heat from sources such as power plants that would otherwise be wasted to the environment as a form of cogeneration, further increasing or maintaining energy available during a subsequent expansion. Additionally, thermal energy from such sources of low-grade heat (not shown) may be transferred to the mid-pressure vessel 2706 during expansion via heat exchanger (not shown) to increase recoverable energy.

FIG. 29 is a schematic diagram of portions of an illustrative compressed-air energy-storage system 2900, similar in some respects to system 2700 in FIG. 27 and FIG. 28, that incorporates embodiments of the invention. The system 2900 includes a high-pressure pneumatic cylinder assembly 2902 (labeled HP in FIG. 29) that expands and compresses gas between some mid pressure (e.g., approximately 200 psig) and some high pressure (e.g., approximately 3,000 psig); a low-pressure pneumatic cylinder assembly 2904 that expands and compresses gas between some low pressure (e.g., approximately 0 psig) and some mid pressure (e.g., approximately 200 psig); a mid-pressure vessel 2906 (labeled MPV in FIG. 29) that typically contains fluid (e.g., gas, heat-exchange liquid, foam, or separated gas and liquid) at the mid pressure of the system; a storage reservoir 2908 or intercommunicating set of storage vessels (e.g., sealed lengths of piping rated for the storage or transport of high-pressure gas) capable of storing fluid at high pressure and elevated temperature (e.g., 50° C.), and thus of acting as both a store of pressure potential energy and thermal energy; a storage vessel/spray reservoir 2910 (e.g., a tank) capable of holding an appropriate quantity of heat-exchange liquid at a relatively low temperature (e.g., 20° C.). The spray reservoir 2910 preferably includes mechanisms for separating a low-pressure foam into liquid and gas components and venting the gas to the atmosphere (indicated by dashed arrow 2912). In FIG. 29, dashed arrows represent the bidirectional movement of gas through appropriate piping and solid arrows represent the bidirectional movement of liquid through appropriate piping.

System 2900 also includes a high-pressure separation vessel 2922, which features one or more mechanisms for separating a foam (e.g., a high-pressure foam) into liquid and gas components. The storage reservoirs 2908, 2910, and 2926 may be insulated in order to slow the loss of exergy that occurs as their contents warm or cool toward the temperature of the

ambient environment. The spray reservoir **2910** may exchange both liquid and gas (e.g., as separate flows of liquid and gas or as a single flow of aqueous foam) with the low-pressure cylinder **2904**, the low-pressure cylinder **2904** may exchange liquid and gas with the mid-pressure vessel **2906**, the mid-pressure vessel **2906** may exchange liquid and gas with the high-pressure cylinder **2902**, the high-pressure cylinder **2702** may exchange gas with the high-pressure store **2908** and (via pump/motor **2924**) liquid with the low-pressure thermal well **2926** (e.g., insulated atmospheric pressure tank).

Like system **2700**, system **2900** may be operated in either compression (energy-storage) or expansion (energy-generating) modes. During a compression mode of operation of system **2900**, gas is compressed stagewise through the low-pressure cylinder **2904**, the mid-pressure vessel **2906**, and the high-pressure vessel **2902** as described above for system **2700**. After compression in the HP cylinder **2902**, liquid and gas (partly or substantially in the form of a foam) from the high-pressure cylinder **2902** are directed to the separation vessel **2922**, where the liquid and gas components of the foam are separated by an appropriate mechanism (e.g., baffles, gravity, rotating blades, ultrasound, centrifuging, and/or other such mechanism). The separated gas component of the foam is directed from the separation vessel **2922** to the storage vessel **2908**; the separated heat-exchange liquid component, at relatively high pressure (e.g., 3,000 psig) and high temperature (e.g., 50° C.) is directed from the separation vessel **2922** through a pump/motor **2924** to a low-pressure storage vessel **2926** (e.g., a tank) capable of holding an appropriate quantity of heat-exchange liquid at elevated temperature and low pressure. The pressure of the heat-exchange liquid is decreased during passage from the separation vessel **2922** through the pump/motor **2924** to the storage vessel **2926**, driving the pump/motor as a motor and thus generating useful energy (recovering this portion of the energy used during the compression of the liquid to elevated pressure). In an alternative embodiment, the high-pressure storage reservoir **2908** may be used both as gas storage and as the liquid/gas separator, where liquid is removed from the low point of the gas storage reservoir after gravity drainage of the liquid portion of the aqueous foam. In this embodiment, separation vessel **2922** is not a separate element from reservoir **2908**. In one embodiment, the storage reservoir **2908** is a horizontal pipe field with large horizontal surface area which facilitates relatively rapid gravity drainage of an aqueous foam.

During an energy-generating (expansion) mode of operation of system **2900**, heat-exchange liquid at low pressure and possibly at elevated temperature from vessel **2926** is directed through pump/motor **2924**. Pump/motor **2924**, operated in pump mode, raises the pressure of the liquid to a level sufficient to permit the liquid's combination with gas at high pressure (e.g., approximately 3,000 psig) from the storage reservoir **2908** as a foam. The foam may be formed in the reservoir **2908**, vessel **2922**, in a mechanism distinct from the vessel **2922** and external to the high-pressure cylinder **2902**, or inside the high-pressure cylinder **2902**. Staged expansion of the gas in the HP cylinder **2902**, mid-pressure vessel **2906**, and low-pressure vessel **2904** then proceeds as described above for system **2700**.

The system **2900** thus uses heat-exchange liquid, foamed with gas during expansion and compression of the gas, both as an exergy storage medium and to enable rapid, substantially isothermal expansion and compression of gas. Unlike system **2700**, system **2900** does not use a single vessel (or interconnected set of vessels) to store both high-pressure gas and heat-exchange liquid. This has the advantage that a smaller volume of high-pressure storage is required; the total volume

of storage required on the hot side of the system **2900** (i.e., the storage of both hot liquid in vessel **2926** and hot, high-pressure gas in vessel **2908**) is approximately the same as for system **2700**, but since vessel **2926** is low-pressure it is likely to be lower-cost per unit volume than high-pressure vessel **2908**.

Moreover, heat from a variety of external sources (e.g., solar heat, waste heat from fuel-burning power plants) may be transferred to the liquid in thermal well **2926** with relative ease (compared to transferring heat to the contents of high-pressure stores **2700** or **2908**), since heat-exchange mechanisms tolerating high pressures will not be needed for such heat harvesting. Thermal energy thus added to thermal well **2926** may be partly realized as useful work in the cylinders **2902** and **2904**, and thus as cogenerated electrical power output from the system **2900**. Lower total storage cost and/or cogeneration may more than compensate for the energy loss entailed by transferring high-pressure liquid from the separation vessel **2922** to a low pressure in thermal well **2926** in compression modes and by pumping low-pressure liquid from thermal well **2926** to a high pressure for foaming with gas in the HP cylinder **2902** during expansion modes.

During a generation mode of a compressed-gas energy storage system employing storage reservoirs of fixed volume for storage of high-pressure gas, gas is progressively exhausted, continuously or in batches, from a high-pressure storage reservoir in order that its potential energy may be partly realized as mechanical and electrical energy. During such progressive exhaustion of the high-pressure store, the pressure and temperature of the gas within the store will tend to decrease in an approximately adiabatic manner. As will be apparent to persons familiar with the principles of thermodynamics, this approximately adiabatic pressure and temperature decrease will entail a loss of recoverable energy due to lower available pressures and/or an exergy loss due to temperature mixing. Similarly, during a storage mode of the compressed-gas energy storage system, gas is progressively delivered, continuously or in batches, to the high-pressure storage reservoir in order that its potential energy may be stored. During such progressive delivery of gas to the high-pressure store, the pressure and temperature of the gas within the store will tend to increase in an approximately adiabatic manner, with corresponding increased work to compress to higher pressure and/or mixing exergy loss due to mismatched temperatures.

To prevent exergy losses during either exhaustion of gas from or delivery of gas to the high-pressure store, it may be desirable to maintain heat exchange between gas undergoing either compression or expansion within the high-pressure store and a heat-exchange liquid. Heat exchange between gas and liquid in the high-pressure store may be achieved by partly or substantially filling the high-pressure store with foam, where the liquid component of the foam is a heat-exchange liquid. The liquid component of the foam will tend to either give up thermal energy to the gas component of the foam, or to absorb thermal energy from the gas component, enabling approximately isothermal increase or decrease of pressure within the high-pressure store during either a storage or generation mode of operation of the system. The temperature of the liquid component of the foam, or of the foam mixture may be further altered by a heat-exchange mechanism (heat exchanger) external to the high-pressure store, shedding heat from the environment or harvesting heat from the environment or some source of cogenerative heat. Either foam or separated liquid may be circulated through a heat exchanger external to the high-pressure store. In other embodiments, heat-exchange mechanisms (e.g., finned

tubes) may be provided internally to the high-pressure store, so that an external heat-exchange fluid (e.g., environmental air) may be circulated into the high-pressure store without mingling with its contents, rather than contents of the high-pressure being circulated to an external heat exchanger. Techniques for heat exchange with a compressed gas stored in a gas-only high-pressure store are described in U.S. patent application Ser. No. 13/094,960, filed Apr. 27, 2011 (the '960 application), the entire disclosure of which is incorporated by reference herein. The minimization of this lost exergy is achieved when the process time constant is considerably less than the heat-transfer time constant. In general, a compression or expansion within the storage reservoir occurs at a much slower time constant than within the cylinders and power unit. For example, compression of gas from 750 psig to 3,000 psig in a storage reservoir may take approximately one hour. The heat-transfer time constant depends in part on the surface area and proximity between the compressing or expanding gas and the liquid. Small droplets or a foam matrix maximize this surface area. In general, spheroidal droplets will have a lower surface area than a matrix of foam cells; thus, a foam matrix may result in a lower heat-transfer time constant, less lost exergy, and a more efficient energy storage system. For the storage reservoir heat exchange, a lower quality foam or low quality or intermittent spray or circulation may be sufficient to achieve the desired heat transfer time constant (e.g., substantially lower time constant than 1 hour).

FIG. 30 is a schematic representation of an illustrative mechanism for circulating fluid from a high-pressure store in order to achieve approximately isothermal changes in pressure in the store during the exhaustion of gas from or delivery of gas to the store, or to add energy to the gas within the store from a cogenerative or other source through the use of a heat exchanger. Fluid from the reservoir (3002a-3002d) is circulated through a heat exchanger 3004 using a pump 3006 operating as a circulator. The circulated fluid may be gas, or heat-exchange liquid, or a foam including both gas and liquid. The pump 3006 operates with a small pressure change sufficient for circulation, but within a housing that is able to withstand high pressures, as detailed in the '409 application. The pump 3006 circulates the high-pressure fluid through the heat exchanger 3004 without substantially increasing its pressure (e.g., a 50 psi increase for 3,000 psi air). The fluid is then re-injected into the reservoir 3002a-3002d, possibly through a mechanism that regenerates a foam or other two-phase mixture (e.g., spray of droplets) within the reservoir 3002a-3002d. In this way, the temperature of the stored compressed gas may be controlled (e.g., raised, lower, held approximately constant, or held approximately equal to the internal liquid temperature) by opening valve 3008 with valve 3010 closed and heated during expansion (release of gas from the reservoir 3002a-3002d) or cooled during compression (delivery of gas to the reservoir 3002a-3002d) by closing valve 3008 and opening valve 3010. Valve 3010, when open, places the subsystem 3000 in fluid communication with an energy-storage system such as system 2700 in FIG. 27. The heat exchanger 3004 may be any sort of standard heat-exchanger design; illustrated in FIG. 30 is a tube-in-shell type heat exchanger with high-pressure air inlet and outlet ports 3012 and 3014 and low-pressure shell ports 3016 and 3018 (which may be connected to an external heating or cooling source).

In other embodiments, foam is circulated from reservoir 3002a-3002d through heat exchanger 3004. The fluid circulated through the external loop of heat exchanger 3004 may, in various embodiments, be a gas, liquid, or foam. The reser-

voir 3002a-3002d is depicted in FIG. 30 in a horizontal position but other orientations are contemplated and within the scope of the invention.

FIG. 31 is a schematic of an illustrative alternative compressed-air storage reservoir subsystem 3100 for heating and cooling of compressed gas in energy storage systems in order to expedite transfer of thermal energy to and from the compressed gas prior to and/or during expansion or compression. As depicted, thermal energy transfer to and from stored fluid in storage reservoirs 3102, 3104 is expedited via liquid circulation using a pump 3106. The liquid pump 3106 operates with a small pressure change sufficient for circulation and spray (and/or foam generation), but within a housing that is able to withstand high pressures; that is, it circulates high-pressure water (or other suitable heat-transfer fluid) through heat exchanger 3108 and introduces the liquid into storage reservoirs 3102 and 3104 without substantially increasing its pressure (e.g., a 50 psi increase for circulating and spraying within 3,000 psig stored compressed gas). The heat exchanger may be omitted or bypassed in other embodiments. The heat exchanger 3108 may be any sort of standard heat exchanger design; illustrated here is a tube-in-shell heat exchanger with high-pressure liquid inlet and outlet ports 3112 and 3114 and low-pressure shell liquid ports 3116 and 3118. The shell ports 3116 and 3118 may permit communication with a second heat exchanger, a thermal well, or some other body of fluid.

Heat exchange within the storage reservoirs 3102, 3104 is expedited by active spraying or foaming of liquid (e.g., water) into the vessels 3102, 3104. Herein, "spraying" refers to any passage of liquid through a mechanism (e.g., small orifice, engineered nozzle, mechanism directing a spray against an impingement pin or plate) that acts upon the liquid mechanically in such a manner as to divide the liquid into droplets. "Foaming" refers to any passage of liquid through a mechanism that mingles it with gas to form a foam; such mechanisms include schemes where the liquid is directed against a surface producing or acted upon by ultrasound, which surface vibrates the liquid in such a way as to produce breakup or foaming. All such mechanisms are contemplated and within the scope of the invention. The illustrative system of FIG. 31 shows multiply perforated rods (spray rods) as the spray/foaming mechanism. As illustrated in FIG. 31, perforated rods 3120 and 3122 may be installed inside storage reservoirs 3102 and 3104. The perforated rods 3120, 3122 may be located along or at the top of the storage reservoirs 3102, 3104, along the middle portion of the storage reservoirs (as illustrated in FIG. 31), and/or along the bottom of the storage reservoirs (e.g., a sparging type arrangement). The rods 3120, 3122 may extend through part or all of the length of the storage reservoirs 3102, 3104. The pump 3106 increases the liquid pressure above the reservoir pressure such that liquid is actively circulated and sprayed/foamed out of rods 3120, 3122, as shown by arrows 3124 and 3126. With spraying and/or foaming into storage reservoirs 3102 and 3104, droplets or foam matrices of the liquid within the gas inside storage reservoirs 3102, 3104 occurs, enabling efficient heat transfer between the liquid and the gas. Foam may partially or substantially fill the storage reservoirs 3102, 3104. Over time, the foam will tend to separate, producing accumulations of liquid 3128, 3130 at the bottom of the storage reservoirs 3102, 3104. Liquid thus accumulated may be removed through ports 3132, 3134 and associated piping 3136. The piping 3136 returns the liquid to the heat exchanger 3108, through which the liquid 3128, 3130 is circulated as part of the closed-loop water circulation and spray/foaming system. Valve

3110, when open, places the subsystem 3100 in fluid communication with an energy-storage system such as system 2700 in FIG. 27.

In various other embodiments, foam or gas is circulated from storage reservoirs 3102, 3104 through heat exchanger 3108. The fluid circulated through the external loop of heat exchanger 3108 may, in various embodiments, be a gas, liquid, or foam. The ports 3132, 3134 may be located on the top or sides of storage reservoirs 3102, 3104 such as to pull gas (e.g., in a sparging arrangement) or foam instead of preferentially pulling separated liquid. The storage reservoirs 3102, 3104 and their internal spray mechanisms 3120, 3122 are depicted in FIG. 31 in a horizontal position but other orientations are contemplated and within the scope of the invention. Two storage reservoirs 3102, 3104 are depicted in FIG. 31 but other numbers of storage reservoirs, such as, e.g., pipelines and natural or artificial caverns are contemplated and within the scope of the invention.

FIG. 32 is a schematic of an alternative compressed-air storage reservoir subsystem 3200 for heating and cooling of compressed gas in energy storage systems, to expedite transfer of thermal energy to and from the compressed gas prior to and/or during expansion or compression. Thermal energy transfer to and/or from stored compressed gas in storage reservoirs 3202 is expedited via fluid circulation using an enclosure 3204 and air circulation fans 3206. The storage reservoirs 3202 may also include heat-exchange liquid, which may be separated or mingled with the gas in the storage reservoirs 3202 to form a foam that partially or entirely fills the storage reservoirs 3202. Separated liquid, foam, and gas not incorporated in a foam may coexist in the storage reservoirs 3202 and in all other high-pressure storage reservoirs depicted herein. In the subsystem 3200, fluid (e.g., air) enters the enclosure 3204 through intake openings (e.g., vents) 3208. The fluid may be at a temperature different from the compressed gas within the storage reservoirs 3202. The storage reservoirs 3202 are in an arrangement that permits substantial circulation of fluid around and between them. Fluid circulating around and between the storage reservoirs 3202 gains thermal energy from the storage reservoirs 3202 if the fluid entering through the vents 3208 is at a lower temperature than the fluid within the storage reservoirs 3202; similarly, the storage reservoirs 3202 gain thermal energy from the fluid entering through the vents 3208 if the circulating fluid is at a higher temperature than the fluid within the storage reservoirs 3202. Fluid that has circulated around and between the storage reservoirs 3202 is typically pulled from the enclosure 3204 by exhaust devices (e.g., pumps, fans) 3206, represented illustratively in FIG. 32 as fans. The gas exhausted by devices 3206 may be confined by one or more ducts (not shown), circulated through a heat-exchange system to change its temperature, and returned to the vents 3208 through the ducts. The exterior of the enclosure 3204 may be insulated. The fluid entering the intake openings 3208 may be heated or cooled and thus change the temperature of storage reservoirs 3202 and their interior contents. The source of such heating may be waste heat from a source such as a thermal power plant or industrial process, and may be a direct source such as solar heating or fuel fired heating elements.

Valves and piping (not shown) may place the contents of the storage reservoirs 3202 in fluid communication with an energy-storage system such as system 2700 in FIG. 27. The storage reservoirs 3202 are depicted in FIG. 32 in a horizontal position but other orientations are contemplated and within the scope of the invention. Six storage reservoirs 3202 are depicted in FIG. 32 but other numbers of storage reservoirs,

as well as other types of gas storage, are contemplated and within the scope of the invention.

FIG. 33 is a schematic of yet another compressed-air storage reservoir subsystem 3300 for use with heating and cooling of compressed gas in energy storage systems, to expedite transfer of thermal energy to and from the compressed gas prior to and/or during expansion or compression. Thermal energy transfer to and from stored compressed gas in storage reservoirs 3302 is expedited via circulation of one or more fluids (e.g., water, aqueous foam) in an enclosure 3304 and using piping 3306, 3308 to respectively admit fluid to and remove fluid from the enclosure 3304. The storage reservoirs 3302 may also contain heat-exchange liquid, which may be separated or mingled with the gas in storage reservoirs 3302 to form a foam that partially or entirely fills the storage reservoirs 3302. In the exemplary subsystem 3300 depicted in FIG. 33, the fluid level 3310 in enclosure 3304 is indicated by closely-spaced vertical lines. Fluid enters the enclosure 3304 through pipe 3306. The fluid may be at a temperature different from that of the fluid within the storage reservoirs 3302. The storage reservoirs 3302 are preferably in an arrangement that permits substantial circulation of water (or other fluid) around and between them. Fluid circulating around and between the storage reservoirs 3302 gains thermal energy from the storage reservoirs 3302 if the fluid entering through pipe 3306 is at a lower temperature than the fluid within the storage reservoirs 3302; similarly, the storage reservoirs 3302 gain thermal energy from the fluid if the fluid entering through the pipe 3306 is at a higher temperature than the fluid within the storage reservoirs 3302. Fluid that has circulated around and between the storage reservoirs 3302 is removed from the enclosure through pipe 3308. The fluid removed through pipe 3308 may be circulated through a heat-exchange system (not shown in FIG. 33) to change its temperature and returned to the enclosure 3304 through pipe 3306.

Valves and piping (not shown) may place the contents of the storage reservoirs 3302 in fluid communication with an energy-storage system such as system 2700 in FIG. 27. The storage reservoirs 3302 are depicted in FIG. 33 in a horizontal position but other orientations are contemplated and within the scope of the invention. Six storage reservoirs 3302 are depicted in FIG. 33 but other numbers of storage reservoirs are contemplated and within the scope of the invention.

FIG. 34 illustrates another compressed-air storage reservoir subsystem 3400 for heating and cooling of compressed gas in energy-storage systems, to expedite transfer of thermal energy to and from the compressed gas prior to and/or during expansion or compression. Thermal energy transfer to and from stored compressed gas in a pressurized reservoir such as a cavern 3402 (e.g., a naturally occurring or artificially created cavern, which may be located underground) is expedited via liquid circulation using a liquid pump 3404 and heat exchanger 3406. The cavern 3402 may also contain heat-exchange liquid, which may be separated or mingled with the gas in the cavern 3402 to form a foam that partially or entirely fills the cavern 3402. Liquid or foam 3420 may pool at the bottom of the cavern 3402. The pump 3404 operates with a small pressure change sufficient for circulation and spray/foam generation, but within a housing that is able to withstand high pressures; pump 3404 circulates high-pressure fluid through heat exchanger 3406 and then to a spray/foam-generation mechanism 3408, creating a foaming spray 3410 inside the cavern 3402 without substantially increasing the pressure of the fluid (e.g., a 50 psi increase for circulating and spraying within 3,000 psi stored compressed air). In this way, the stored compressed gas may be pre-heated (or pre-cooled) using a fluid circulation and spraying/foaming method, which

also may allow for active liquid monitoring of the storage cavern **3402**. The two-phase heat exchange may occur as pre-heating prior to expansion and/or pre-cooling prior to compression. The circulation may be done without heat exchanger **3406** and serve to maintain the heat exchange liquid and gas at substantially the same temperature during an expansion or compression. The pump **3404** may be submerged in the liquid or foam **3420** or be external to the liquid or foam **3420**. The heat exchanger **3406** may be of any standard heat-exchanger design; illustrated here is a tube-in-shell heat exchanger with high-pressure liquid inlet and outlet ports **3412** and **3414** and low-pressure shell liquid ports **3416** and **3418**. The shell ports **3416** and **3418** may permit communication with a second heat exchanger or a thermal well or some other body of fluid.

Heat exchange within the storage cavern **3402** is expedited by active spraying and foam generation **3410** of liquid (e.g., water with one or more foaming additives) into the cavern **3402**. Illustrated in FIG. **34** is a scheme where one or more perforated spray heads **3408** are installed within the storage cavern **3402**. Pump **3404** increases the fluid pressure above the cavern pressure such that fluid is actively circulated and sprayed out of spray head **3408**. Foam may partially or entirely fill the volume of cavern **3402**. Due to foam separation, liquid and/or foam **3420** may accumulate at the bottom of the cavern **3402** and be removed through piping **3422**. The piping **3422** returns the liquid and/or foam **3420** to the pump **3404** and heat exchanger **3406**, through which the liquid and/or foam is circulated as part of the closed-loop fluid circulation and foam-generation and/or foam-regeneration system. A valve or valves and piping (not shown) may place cavern **3402** in fluid communication with an energy-storage system such as system **2700** in FIG. **27**.

If the cavern **3402** is of sufficient size, a substantial mass of liquid and/or foam **3420** may be allowed to accumulate at the bottom of the cavern **3402**. In this case, this mass of liquid and/or foam **3420** may exchange heat relatively slowly with the air also contained in cavern **3402**, and may be used as a thermal reservoir.

A vertical cavern shape and spray-head-type internal foam-generation mechanism **3408** are depicted in FIG. **34** but other orientations and spray or foam-generation mechanisms (e.g., spray rod, multiple nozzles) are contemplated and within the scope of the invention. The spray head **3408** may be located at the bottom of the cavern to allow sparging of air into the accumulating liquid and/or foam **3420** to form or regenerate a foam within the cavern **3402**. A single cavern **3402** is depicted in FIG. **34** but other numbers of caverns and storage reservoirs featuring both caverns and other forms of gas storage (e.g., pressure vessels and/or pipes) are contemplated and within the scope of the invention.

FIG. **35** is a diagram of various components of an energy storage and recovery system in accordance with various embodiments of the invention. The illustrated system includes or consists essentially of an installation **3500** where thermal energy is available for recovery, extracted from the surroundings, needed for usage, and/or may be removed for cooling. Example installations **3500** include fossil-fuel based power plants (e.g., coal, natural gas); other heat-engine based power plants such as nuclear, solar thermal, and geothermal; industrial processes with waste heat; heat pumps, heat sources, and heat sinks; buildings needing space heating or cooling; and sources of environmentally chilled water. In FIG. **35**, for illustrative purposes, a power plant **3502** is shown whose excess thermal energy is recoverable through a standard heat-exchange unit **3504**. Generated power **3506** from the power plant **3502** may be used to drive the compressed-

gas energy storage system **3508** as determined by the operator (e.g., when market demand for power is low), storing energy in the form of compressed gas in storage reservoir **3510**. Energy may be additionally stored as the thermal energy or exergy of liquids cooled below the environmental temperature or warmed above it, and these liquids may be located in the same vessels that contain the compressed gas (e.g., mingled with it as a foam) or separated from the gas and stored in separate vessels. Upon demand for increased power, this stored energy undergoes expansion (e.g., staged expansion) in the compressed-gas energy storage system **3508** to generate power for usage (e.g., power grid delivery **3512**). The recovered thermal energy from the power plant **3502** may be used in the heat-exchange subsystem of the compressed-gas storage reservoir **3510** (or other pressurized storage) to preheat the stored compressed gas and/or to heat the heat-exchange fluid and gas before or during expansion and/or between expansion/compression stages in mid-pressure vessels, increasing the work done by a given volume of pressurized gas and improving system efficiency and/or performance. Likewise, but not illustrated herein, water cooled by heat exchange with cold environments, ground loops, water loops, or other low-temperature reservoirs may be used in the heat-exchange subsystem to pre-cool and/or continually cool the compressed gas prior to and during further compression, improving system efficiency and/or performance. In all these instances, performance and/or value of the system may be markedly improved.

FIG. **36** depicts an illustrative system **3600** that substantially isothermally compresses or expands gas over a predetermined pressure range in accordance with various embodiments of the present invention. System **3600** includes a cylinder **3602** containing a mobile piston **3604** (or other suitable boundary mechanism) that divides the interior of the cylinder **3602** into a gas-filled chamber (also termed air chamber or pneumatic chamber) **3606** (and a liquid-filled, i.e., hydraulic) chamber **3608**. Alternatively, chamber **3608** may be gas-filled, and/or the air chamber **3606** may contain one or more of gas, liquid, and foam. An integrated heat-exchange mechanism is typically present in chambers **3606** and/or **3608**, as described in the '155 patent and/or as shown in FIG. **2**. In the illustrative embodiment shown in FIG. **36**, a spray head **3610** injects a spray **3612** of fluid into the upper chamber **3606** of the cylinder **3602**. This spray **3612** may include or consist essentially of an aqueous foam comprising both gas and a heat-exchange liquid, or of a liquid that mixes with gas in the air chamber **3606** to form an aqueous foam. Foam **3614** partially or entirely fills the air chamber **3606**; partial separation of the foam **3614** may also occur, allowing liquid to accumulate on top of piston **3604**. Ports **3620** and **3630** with valves **3622** and **3632** allow gas to be admitted to or exhausted from chamber **3606** as desired. A port or ports (not shown) with associated pipes and valves (not shown) allow fluid to be admitted to or withdrawn from chamber **3608** as desired.

During air expansion, the gas in chamber **3606** expands, performing work on piston **3604**. As the gas in chamber **3606** expands, its temperature tends to fall, and thermal energy is transferred from the gas from the heat-transfer liquid within chamber **3606** (e.g., the liquid component of a foam partly or wholly filling chamber **3606**). The transfer of thermal energy to the gas from the liquid in chamber **3606** increases the amount of work performed by the expanding gas on the piston **3604**. As the gas in chamber **3606** expands, its temperature tends to fall, and thermal energy is transferred from the gas from the heat-transfer liquid within chamber **3606** (e.g., the liquid component of a foam partly or wholly

filling chamber 3606). The transfer of thermal energy to the gas from the liquid in chamber 3606 increases the amount of work performed by the expanding gas on the piston 3604.

During air compression, piston 3604 moves upward and thus compresses the gas in chamber 3606. As the gas in chamber 3606 is compressed, its temperature tends to rise, and thermal energy is transferred from the gas to the heat-transfer liquid within chamber 3606 (e.g., the liquid component of a foam partly or wholly filling chamber 3606). The transfer of thermal energy from the gas to the liquid in chamber 3606 decreases the amount of work that the piston 3604 must perform on the expanding gas. The transfer of thermal energy to the liquid from the gas in chamber 3606 reduces the amount of work that the piston 3604 performs on the gas in chamber 3606 in order to compress the gas.

To prepare the cylinder 3602 for compression, low-pressure gas is admitted from point 3634 through valve 3632 and port 3630 into upper chamber 3606 during a downward stroke starting with piston 3604 near or at the top of cylinder 3602. The gas may be mingled with liquid to form a foam, either before, during, or after admission to chamber 3606. In various embodiments of the invention, the inlet pressure at point 3634 is raised above atmospheric pressure by a blower (e.g., lobe type) or pump/compressor (e.g., screw pump) 3642 that draws in atmospheric-pressure or near-atmospheric-pressure gas through inlet/vent 3640. The compression by pump/compressor 3642 may be predominantly adiabatic; alternatively, pump/compressor 3642 may include, e.g., a screw pump that permits the introduction of a heat-exchange foam and/or droplets into air undergoing compression and/or expansion within screw pump 3642, enabling the substantially isothermal compression and/or expansion of air within screw pump 3642. The foam may be subsequently pumped by the screw pump 3642 to chamber 3606. Moreover, as shown in FIG. 36, the screw pump 3642 may be a bidirectional expander/compressor; hence, references herein to “compressor 3642” and “expander 3642” below may refer to a single bidirectional screw-pump unit. The outlet of the compressor 3642 may be attached to a low-pressure vessel 3650 near or at the predetermined minimum system pressure at point 3634 (i.e., the super-atmospheric pressure enabled by the compressor 3642 and that serves as the inlet pressure to cylinder 3602) in order that low-pressure vessel 3650 may provide a buffer such that the compressor 3642 may operate continuously at near-constant power. The low-pressure vessel 3650 may contain integrated heat exchange as described above and in the '155 patent. At or near the bottom of a downward (intake) stroke preparatory to compression, where piston 3604 is at or near the bottom of cylinder 3602 and chamber 3606 is filled with gas (and/or foam) at a predetermined pressure by the action of compressor 3642 and valve 3632, valve 3632 is closed. An upward compression stroke follows. At a predetermined high pressure, which may be equal to the pressure at point 3624 (e.g., the pressure in a high-pressure storage reservoir like reservoir 222 or higher-pressure cylinder in a multi-stage system), valve 3622 is opened, connecting chamber 3606 through port 3620 to point 3624. The pressurized gas and/or foam is then forced through valve 3622 to point 3624, until piston 3604 is near or at the top of cylinder 3606, whereupon valve 3622 closes and the process repeats with another intake stroke.

In comparison to a system otherwise identical to system 3600 but lacking a compressor 3642, the presence of the compressor 3642 in system 3600 enables a greater amount (mass) of gas to be compressed in a single upstroke of piston 3604 within cylinder 3602. The work of compression done in

a single stroke with compressor 3642 is higher than without compressor 3642 and more gas is compressed to point 3624.

The efficiency of the total compression for predominantly adiabatic compression by compressor 3642 and substantially isothermal compression in the cylinder 3602 is typically less than a substantially isothermal compression completely within the cylinder 3602 over the entire pressure range, as previously mentioned. The efficiency of the total compression for substantially isothermal compression by compressor 3642 and substantially isothermal compression in the cylinder 3602 is also typically less than a substantially isothermal compression completely within the cylinder 3602 over the entire pressure range. The addition of the compressor 3642 thus generally increases the power of system 3600 (i.e., the rate at which system 3600 transforms work to potential energy of compressed gas) at the expense of efficiency. The degree of tradeoff between power and efficiency that is optimal typically varies depending on the application in which system 3600 is used. Additionally, for a given outlet pressure at port 3620, the higher starting pressure within chamber 3606 of the cylinder 3602 reduces the pressure range (ratio of outlet pressure to inlet pressure) over which the cylinder 3602 acts during the course of a stroke; as reviewed above, this also narrows the range of forces that act on rod 3618 that is attached to the piston 3604 and whose nether end extends out of cylinder 3602. This narrowing of the range of forces in turn enables more efficient conversion of electrical energy by a motor/generator (not shown) to work in the system 3600, as previously discussed.

During an expansion, a predetermined amount of compressed gas and/or foam at high pressure is admitted from point 3624 (e.g., from a storage vessel such as reservoir 222 in FIG. 2 or higher-pressure cylinder in a multi-stage system such as system 2700 in FIG. 27) through valve 3622 and port 3620 into chamber 3606. The amount of gas and/or foam admitted may be set by a control system (e.g., controls system 122 in FIG. 1) such that after fully expanding on a downward stroke (i.e., when piston 3604 reaches the bottom of cylinder 3602), the gas and/or foam reaches a predetermined minimum system pressure that is typically super-atmospheric (e.g., approximately 5 psig). For example, the control system may be responsive to one or more sensors measuring gas flow rate and/or pressure within cylinder 3602 to meter the gas introduction. On the upward return stroke of the cylinder 3602, that gas is exhausted through valve 3632 to point 3634.

In various embodiments of the invention, the piping at point 3634 is attached to an expander 3642 that converts the pressurized gas flow into rotational motion; in such embodiments, gas flow through the expander 3642 generates power additional to the amount generated by the expansion within the cylinders. The expansion through the expander 3642 may be predominantly adiabatic; alternatively, expander 3642 may permit the introduction of a heat-exchange foam and/or droplets into air undergoing expansion within expander 3642, enabling the substantially isothermal expansion of air within expander 3642. After expansion through the expander 3642, the gas (or gaseous component of foam) may be exhausted to the atmosphere through vent 3640. In addition, as shown in FIG. 36, a low-pressure vessel 3650 near or at the predetermined minimum system pressure (i.e., the super-atmospheric pressure input to the expander 3642 and that serves as the outlet pressure of cylinder 3602) may also be connected at point 3634 in order to provide a buffer such that the expander 3642 may operate continuously at near-constant power. As mentioned above, the low-pressure vessel 3650 may contain an integrated heat-exchange mechanism.

By ending the expansion stroke within cylinder **3602** at a pressure above atmospheric pressure, a greater amount (mass) of gas may be expanded in a single downstroke of piston **3604** within cylinder **3602**. The work of expansion done in that single stroke (higher forces acting over a distance) will be higher than the amount of work performed by an otherwise identical stroke during which a smaller amount of gas is expanded (lower forces acting over the same distance). Moreover, if an expander **3642** is employed, additional power may be generated that would be lost if the super-atmospheric-pressure gas in chamber **3606** at the end of an expansion stroke were vented directly to the atmosphere. The total efficiency of a predominantly adiabatic expansion in expander **3642** combined with a predominantly isothermal expansion in cylinder **3602** is typically less than the efficiency of a near-isothermal expansion completely within the cylinder **3602** over the entire pressure range. The efficiency of the total expansion for substantially isothermal expansion by expander **3642** and substantially isothermal expansion in the cylinder **3602** is also typically less than a substantially isothermal expansion completely within the cylinder **3602** over the entire pressure range. The employment of super-atmospheric venting pressure combined with an expander **3642** thus generally adds power at the expense of efficiency. The degree of tradeoff between power and efficiency that is optimal typically varies depending on the application in which system **3600** is used. Additionally, the higher vent pressure of the cylinder **3602** reduces the pressure range over which the cylinder **3602** acts for a given outlet pressure (i.e., where range is outlet/inlet pressure), such that some benefit of efficiency of power transmission may be achieved by operating the cylinder **3602** over a narrower pressure (and thus force) range.

A control system (e.g., control system **122** in FIG. 1) may control the compressor/expander **3642** and cylinder **3602** in order to enforce substantially isothermal expansion and/or compression of gas in cylinder **3602** over a particular range of super-atmospheric pressures and substantially adiabatic compression and/or expansion in expander/expander **3642** between approximately atmospheric pressure and the minimum super-atmospheric pressure of operation of cylinder **3602**. For example, the control system may direct the introduction of gas and/or foam into and the exhausting of gas and/or foam out of cylinder **3602** and expander/expander **3642** via, e.g., control over the various ports and/or valves associated with these components. The control system may be responsive to one or more sensors disposed in or on cylinder **3602** and/or expander/expander **3642** for measuring the pressure of the gas within these components, and direct movement of the gas within system **3600** accordingly. As described above, control of substantially isothermal compression and/or expansion within cylinder **3602** may also entail control over an associated heat-transfer subsystem that may foam heat-exchange liquid with the gas. Such heat-transfer subsystems may be turned off or rendered idle during substantially adiabatic or substantially isothermal compression and/or expansion in expander/expander **3642**.

FIG. 37 depicts an illustrative system **3700** that substantially isothermally compresses or expands gas over a predetermined pressure range in accordance with various embodiments of the present invention. System **3700** employs the same substantially isothermal cylinder stage shown in system **3600** of FIG. 36, but features a separate and parallel set of control valves and other components for expansion and compression. System **3700** includes a cylinder **3702** containing a mobile piston **3704** that divides the interior of the cylinder **3702** into a gas-filled (pneumatic) chamber **3706** and a liquid-

filled (hydraulic) chamber **3708**. Alternatively, both chambers **3706** and **3708** may be gas-filled. An integrated heat-exchange mechanism may be present in chambers **3706** and/or **3708**, as described in the '155 patent and/or as shown in FIG. 36. In the illustrative embodiment, a spray head **3710** forms a spray **3712** of heat-exchange liquid, thereby forming a foam with the gas in the upper chamber **3706** of the cylinder **3702**. In other embodiments, the spray head **3710** may be located outside the cylinder **3702**. This spray **3712** may produce an accumulation of liquid **3714** on top of piston **3704**. Ports **3720** and **3730** with valves **3722** and **3732** allow gas to be admitted to or exhausted from chamber **3706** as desired. A port or ports (not shown) with associated pipes and valves (not shown) allows fluid to be admitted to or withdrawn from chamber **3708** as desired.

During air expansion, gas and/or foam in chamber **3706** expands, performing work on piston **3704**. As the gas in chamber **3706** expands, its temperature tends to fall. If during expansion the spray **3712** enters chamber **3706** at a suitable temperature (e.g., the temperature of the gas in chamber **3706** before compression begins), then the liquid component of the foam is at a higher temperature during expansion than the gas in chamber **3706**, and the liquid component of the foam transfers thermal energy to the gas in chamber **3706**. The transfer of thermal energy from the liquid component of the foam to the gas in chamber **3706** increases the amount of work performed by the expanding gas on the piston **3704**. In effect, this transfer of thermal energy from the liquid component of the foam to the gas in chamber **3706** enables the conversion of some of the thermal energy in the spray **3712** into work.

During air compression, piston **3704** moves upward and thus compresses the gas in chamber **3706**. While the gas in chamber **3706** is being compressed by the piston **3704**, its temperature tends to rise. If during compression the liquid spray **3712** enters chamber **3706** at a suitable temperature (e.g., the temperature of the gas in chamber **3706** before compression begins), then the gas in chamber **3706** is at a higher temperature during compression than the liquid component of the foam, and the gas in chamber **3706** transfers thermal energy to the liquid component of the foam. The transfer of thermal energy to the liquid component of the foam from the gas in chamber **3706** reduces the amount of work that the piston **3704** must perform on the gas in chamber **3706** in order to compress the gas.

During a downward stroke (preparatory to a compression stroke) starting with piston **3704** near or at the top of cylinder **3702**, low-pressure gas is admitted from point **3734** through valve **3730** (shown here as a check valve) and through port **3730** into upper chamber **3706**. In various embodiments of the invention, the inlet pressure at point **3734** is raised above atmospheric pressure by a compressor **3740** (e.g., a screw pump **3740**) drawing in atmospheric or near-atmospheric pressure gas through inlet/vent **3741**. The compression by compressor **3740** may be predominantly adiabatic; alternatively, compressor **3740** may permit the introduction of a heat-exchange foam and/or droplets into air undergoing compression within compressor **3740**, enabling the substantially isothermal compression of air within compressor **3740**. As shown in the illustrative example of FIG. 37, the compressor **3740** need not be a bidirectional expander/compressor, but may be implemented as a unidirectional device that may be turned off or rendered idle during expansion mode. The outlet of the compressor **3740** may include an after-cooler or other heat-exchange system (not shown) and may be attached to a low-pressure vessel **3750** near or at the predetermined minimum system pressure at point **3734** in order to provide a

buffer such that the compressor 3740 may operate continuously at substantially constant power during compression mode. The low-pressure vessel 3750 may contain integrated heat exchange as described above. At or near the bottom of a downward stroke, where piston 3704 is at or near the bottom of cylinder 3702, chamber 3706 is filled with fluid (e.g., foam) at the predetermined pressure by the action of compressor 3740 and valve 3730, valve 3730 is closed, and an upward compression stroke is performed. Alternatively, as shown, valve 3730 operates as a check valve and closes as soon as the upward compression stroke pressurizes chamber 206 above the pressure at point 3734. At a predetermined high pressure, preferably equal to the pressure at point 3724 (e.g., from a storage reservoir such as reservoir 222 or a higher-pressure cylinder in a multi-stage system), valve 3720 (shown here as a check valve) is opened, connecting chamber 3706 through port 3720 to point 3724. The pressurized fluid is then forced through valve 3720 to point 3724, until piston 3704 is near or at the top of cylinder 3706, when valve 3720 closes and the process repeats with another intake stroke. Alternatively, as shown in FIG. 37, valve 3720 operates as a check valve and opens as soon as the upward compression stroke pressurizes chamber 3706 above the pressure at point 3724 and closes as soon as the downward intake stroke begins, reducing pressure in chamber 3706 below the pressure at point 3724.

Using the compressor 3740, a greater amount (mass) of gas may be compressed in a single upstroke of piston 3704 within cylinder 3702 than may be compressed without using compressor 3740. The work of compression done in that single stroke will be higher than without compressor 3740 and more gas will be compressed to point 3724. The efficiency of the total compression for a predominantly adiabatic compression in compressor 3740 and a predominantly isothermal compression in cylinder 3702 tends to be less than for a substantially isothermal compression completely within the cylinder 3702 over the entire pressure range. The efficiency of the total compression for substantially isothermal compression by compressor 3740 and substantially isothermal compression in the cylinder 3702 is also typically less than a substantially isothermal compression completely within the cylinder 3702 over the entire pressure range. The addition of the compressor 3740 thus typically adds power at the expense of efficiency. Additionally, the higher super-atmospheric starting pressure within the cylinder 3702 reduces the pressure range over which the cylinder 3702 acts for a given outlet pressure (i.e. where range is outlet/inlet pressure), such that some benefit of efficiency of power transmission may be achieved by operating the cylinder 3702 over a narrower pressure (and thus force) range.

During expansion, a predetermined amount of compressed gas at high pressure is admitted from point 3724 (e.g. from a storage reservoir such as reservoir 222 or a higher-pressure cylinder in a multi-stage system) through valve 3722 and port 3720 into chamber 3706. As illustrated in FIG. 37, valve 3722 may be a unidirectional valve, i.e., optimized for flow in only one direction. The amount of gas admitted may be set by the control system 122 such that after fully expanding on a downward stroke (i.e., piston 3704 reaches the bottom of cylinder 3702) the gas reaches the predetermined minimum system pressure for cylinder compression and/or expansion (e.g. approximately 5 psig). On the upward return stroke of the cylinder 3702, that gas is exhausted through valve 3732 to point 3736. In various embodiments of the invention, point 3736 may be attached to an expander 3742 that converts the pressurized gas flow to rotational motion, performing work and generating additional power above the amount generated

by the expansion within the cylinder(s). As shown in the illustrative example, the expander 3742 need not be a bidirectional expander/compressor, but may be implemented as a unidirectional expander that may be turned off or rendered idle during compression mode. The expansion through the expander 3742 may be predominantly adiabatic, such as that achieved by a centrifugal or axial-turbine-type expander; alternatively, expander 3742 may permit the introduction of a heat-exchange foam and/or droplets into air undergoing expansion within expander 3742, enabling the substantially isothermal expansion of air within expander 3742. After expansion through the expander 3742, the gas may be exhausted to atmosphere through vent 3741. In addition, as shown in this illustrative embodiment, a low-pressure vessel 3752 near or at the predetermined minimum system pressure may also be connected at point 3736 in order to provide a buffer such that the expander 3742 may operate continuously at substantially constant power. The low-pressure vessel 3752 may contain integrated heat exchange as described above.

By ending the expansion stroke within cylinder 3702 at a pressure above atmospheric pressure, a greater amount (mass) of gas may be expanded in a single downstroke of piston 3704 within cylinder 3702. The work of expansion done in that single stroke is typically higher than that done with less gas. Additionally, with an expander 3742, additional power may be generated that would be lost if the super-atmospheric-pressure gas were vented directly to atmosphere. The efficiency of the total expansion for a predominantly adiabatic expansion in expander 3750 and a predominantly isothermal expansion in cylinder 3702 may be less than a substantially isothermal expansion completely within the cylinder 3702 over the entire pressure range. The efficiency of the total expansion for substantially isothermal expansion by expander 3742 and substantially isothermal compression in the cylinder 3702 is also typically less than a substantially isothermal compression completely within the cylinder 3702 over the entire pressure range. The addition of the higher vent pressure thus typically adds power at the expense of efficiency. The degree of tradeoff between power and efficiency that is optimal typically varies depending on the application in which system 3700 is used. (For example, at certain low pressures, the cost of an expander may not be worth the recovered power; in such a case, vessel 3752 and expander 3742 may be profitably omitted.) Additionally, the higher vent pressure of the cylinder 3702 typically reduces the pressure range over which the cylinder 3702 acts for a given outlet pressure; as a result, the benefit of efficiency of power transmission may be achieved by operating the cylinder 3702 over a narrower pressure (and thus force) range.

Additionally, the higher vent pressure at port 3730 reduces the pressure range (ratio of outlet pressure to inlet pressure) over which the cylinder 3702 acts during the course of a stroke; this also narrows the range of forces that act on rod 3718. This narrowing of the range of forces in turn enables more efficient conversion of work performed by system 3700 to electrical energy by a motor/generator (not shown).

Reference is now made to FIG. 38, which depicts another illustrative embodiment of the invention. A volume 3800 (e.g., pipeline, fluid reservoir, gas reservoir, pneumatic chamber filled with gas or foam) contains fluid at a pressure P_s . Due to frictional losses and work performed in creating fluid motion, this pressure P_s may be lower than the pressure P_i at which the fluid was injected into the volume 3800. Alternatively or additionally, pressure P_i may simply be some pressure, higher than P_s , to which it is desired to raise fluid extracted from volume 3800. In order to continuously pump the fluid back into the volume 3800, or into another volume

3804 at any pressure (e.g., P_i) higher than P_s , a screw pump **3802** may be installed as a booster pump, symbolized in FIG. **38** by a cartoon of a screw pump. The screw pump **3802** efficiently takes inlet fluid from the volume **3800** at pressure P_s , and outputs fluid at pressure P_i for injection back into volume **3800** or into a second volume **3804** (as depicted in FIG. **38**).

A screw pump may be employed as a booster or circulation pump in any of the illustrative mechanisms depicted herein that employs a booster or circulation pump. In such applications, the screw pump may feature apparatus that permits the introduction of a heat-exchange foam and/or droplets into air undergoing compression and/or expansion within screw pump, enabling the substantially isothermal compression and/or expansion of air within screw pump. The foam thus generated may be transported by piping from the screw pump to a pneumatic cylinder, separator, storage reservoir, or other component of the energy storage system.

FIG. **39** depicts an illustrative system **3900** that features a power unit **3902** (including a cylinder assembly unit for compression and expansion of gas), a cylinder heat-exchange system **3904**, a vent **3905** to draw air from and exhaust air to the environment, a storage reservoir **3906** capable of holding fluid (e.g., air and/or water) at high pressure (e.g., 3,000 psi), a thermal well **3908** for storage and retrieval of thermal energy (e.g., a body of water), a waste-heat heat-exchange system **3910** coupled to waste heat generated by mechanical and/or electronic components of the power unit **3902**, and an environmental heat-exchange system **3912** for exchanging thermal energy with the environment (e.g., the air, the ground). Lines **3914**, **3916**, **3918**, **3919**, **3920**, **3922**, **3924**, and **3926** denote piping, valves, and other arrangements for exchange of gas, liquid, and/or thermal energy between the components the lines connect. The cylinder heat-exchange system **3904** features components for generating or otherwise processing foams and/or sprays, for changing the pressure of fluids, and for routing fluid transfers between the various components with which the cylinder heat-exchange system **3904** is in fluid communication (e.g., store **3906**, power unit **3902**, thermal well **3908**); the cylinder heat-exchange systems depicted in subsequent figures may include components performing similar functions. In FIG. **39** and subsequent figures, the power unit **3902** is depicted as including a single spray- or foam-cooled pneumatic cylinder (at top) connected to a crankshaft, seen in cross-section; however, this depiction is illustrative and conceptual only, and is not intended to restrict the mechanisms that might be employed in system **3900** (or in other illustrative systems depicted herein) for the interconversion of thermal, gas elastic potential, mechanical, and electrical energy. In other embodiments, not depicted herein, the power unit **3902** includes multiple cylinders, and interconversion of mechanical and electrical energy may occur via hydraulic systems, linear generators, and other alternatives to the cylinder-crankshaft combination depicted in FIG. **39** and some other figures herein. Moreover, in various embodiments, the water employed as a heat-exchange and thermal-energy-storage material in system **3900** includes one or more additives, or is replaced by a different fluid (e.g., an oil). Also, materials other than water, including non-fluid or multiphase materials (e.g., aqueous foams), may be employed as the energy-storage medium of the thermal well **3908**. The depictions of power units, heat-exchange liquids, and thermal wells in all figures herein are illustrative and nonrestrictive. Moreover, in all illustrative systems described herein, environmental heat-exchange units and waste-heat heat-exchange units are optional wherever depicted.

Possible modes of operation of system **3900** include an expansion mode and a compression mode. In the compression mode, a quantity of gas (e.g., air) at relatively low (e.g., atmospheric) pressure is admitted at an ambient or moderate temperature to the cylinder assembly in power unit **3902**. The compression of the gas in the cylinder assembly is maintained substantially isothermal by introduction into the gas of a spray of foaming liquid drawn from the thermal well **3908** via the heat-exchange system **3904**, thereby forming a foam in the power unit **3902**. The water in the thermal well **3908** is here presumed to be at a relatively low (e.g., ambient) temperature at the beginning of the compression-mode cycle, and may include one or more foaming additives (alternatively, the additive(s) may be added by the heat-exchange system **3904**). The liquid component of the foam undergoing compression may be returned via the cylinder heat-exchange system **3904** to the thermal well **3908** at a higher temperature than the water was drawn from the thermal well **3908**, having gained thermal energy during compression. At or near the end of each compression stroke of the cylinder assembly, gas at high pressure and approximately ambient temperature is conveyed through piping to the high-pressure reservoir **3906**.

Throughout a single cylinder compression cycle, or throughout a series of cylinder compression cycles, return of heated water to the thermal well **3908** will generally tend to raise the temperature of the water in the thermal well **3908**. If thermal well **3908** is a single body of water, then the temperature of that body will tend to rise; if the thermal well **3908** includes one or more hot-water reservoirs and one or more cold-water reservoirs, the temperature of the water in the one or more hot-water reservoirs (and thus the average temperature of the contents of thermal well **3908**) will tend to rise. In effect, some energy that originated as mechanical work performed on gas undergoing compression in the power unit **3902** will be stored as thermal energy in the thermal well **3908**.

In the expansion mode of system **3900** (e.g., an expansion cycle subsequent to the compression cycle described herein-above), gas at high pressure may be transferred from the reservoir **3906** to the cylinder of the power unit **3902**, where it expands, performing work on a piston. As or before the gas expands within the cylinder, foamable liquid may be transferred from the thermal well **3908** to the power unit **3902** via the cylinder heat-exchange system **3904**. This liquid (e.g., water with one or more additives) may be at a relatively high temperature due to the transfer of thermal energy to the thermal well **3908** during prior compression cycles or by other processes. Water from the thermal well **3908** forms a foam with the gas undergoing expansion, transferring heat to the gas as the gas cools and thus tending to keep the expansion substantially isothermal and causing the gas to perform more work on the piston. In effect, thermal energy stored in the thermal well **3908** may be converted to work in the power unit **3902** during an expansion cycle of system **3900**. Thermal energy stored in the thermal well **3908** may come from compression cycles of the power unit **3902**, or from other sources; in particular, the waste-heat heat-exchange unit **3910** may be employed to transfer heat from the mechanical and electrical components of power unit **3902** to the thermal well **3908**. Heat from other sources, not shown in FIG. **39**, may also be transferred to the thermal well **3908**.

The temperature of the thermal well **3908** may be decreased or held constant despite the addition of heat thereto (e.g., via the cylinder heat exchange system **3904**) by shedding heat from the thermal well **3908** to the environment (e.g., atmosphere or ground) via an environmental heat-exchange unit **3912**. Waste heat from the power unit **3902** may also be

shed via the environmental heat-exchange unit **3912**. For example, if at the end of a series of expansion cycles the temperature of the water within the thermal well **3908** is not sufficiently low for use in a subsequent series of compression cycles, heat may be shed from the thermal well **3908** to the environment via environmental heat-exchange unit **3912** during an inactive interval, i.e., a period when reservoir **3906** contains stored pressurized gas but system **3900** is not being employed as a generator. An environmental heat-exchange unit **3912** that is designed to allow system **3900** to shed unwanted heat slowly during an inactive interval will tend to be smaller and less costly than one designed to shed heat quickly (in real time) during active operation of system **3900**, reducing the cost of system **3900**. The use of a thermal well **3908** enables the time-shifting of waste thermal energy to the environment, which may have the advantage of both making the environmental heat-exchange unit smaller due to lengthening the time over which a certain amount of thermal energy is dissipated and also allowing the heat exchange to potentially take place at times different from the operation times of the power unit, which may allow usage at more optimal environmental temperatures (e.g., colder night temperatures for dissipating heat). Moreover, unwanted heat from the reservoir **3906**, gas undergoing compression in the power unit **3902**, and heat from mechanical and electronic inefficiencies of the power unit **3902** may all be shed to the environment by the single environmental heat-exchange unit **3912**, realizing further cost and simplicity advantages over comparable systems that utilize multiple heat-exchange units to control the temperature of various subsystems.

During gas-expansion cycles of system **3900**, the temperature of the thermal well **3908** may be increased or held constant despite the removal or loss of heat from the thermal well **3908** by adding heat to the thermal well **3908** harvested from the environment via the environmental heat-exchange unit **3912**. During gas-compression cycles, the temperature of the thermal well **3908** may be decreased or held constant despite the addition of heat to the thermal well **3908** by shedding heat from the thermal well **3908** to the environment via the environmental heat-exchange unit **3912**. Such temperature management of the thermal well **3908** may be desirable for efficiency reasons or, for example, to keep the water in the thermal well **3908** from either freezing or boiling.

Transferring energy to the thermal well **3908** from foam undergoing compression in a series of compression cycles will generally tend to produce a body of high-temperature water for use in a subsequent series of expansion cycles; transferring energy out of the thermal well **3908** to foam undergoing expansion in a series of expansion cycles will generally tend to produce a body of low-temperature water for use in a subsequent series of compression cycles. By maintaining a generally hotter-than-ambient reservoir of liquid in the thermal well **3908** for spraying during or before expansions, and a generally cooler-than-ambient reservoir of liquid in the thermal well **3908** for spraying during or before compressions, the efficiency of the energy storage and generation system **3900** may be increased over that of an otherwise comparable system whose foaming liquid is always ambient in temperature. Moreover, obtaining higher and lower temperature extremes in the thermal well **3908** by storing thermal energy obtained from gas undergoing compression and expansion, rather than by using heaters, refrigeration, or heat-pump devices to obtain the desired temperature extremes, may reduce parasitic energy expenditures and consequently increase the overall efficiency of the system **3900**.

Capture of heat from mechanical and electronic inefficiencies in the power unit **3902** via the waste-heat heat-exchange

unit **3910**, and the transfer of such heat to thermal well **3908** for partial conversion to work in subsequent expansion cycles, will typically also tend to increase the overall efficiency of the system **3900**.

In some embodiments, the thermal well **3908** includes a vessel (not shown) for the storage of liquid at high pressure and high temperature; additionally or alternatively, liquid at high pressure and temperature may be stored in the vessel **3906** along with gas at high pressure and high temperature. These and other bodies of high-temperature liquid may be employed during expansion cycles of system **3900** to achieve substantially isothermal gas compression.

FIG. **40** depicts an illustrative system **4000** that features a power unit **4002**, a cylinder heat-exchange system **4004**, a vent **4005** to draw and exhaust air from and to the environment, a storage reservoir **4006** capable of holding fluid (e.g., air and water) at high pressure (e.g., 3,000 psi), a thermal well **4008** for storage and retrieval of thermal energy (e.g., a body of water), a waste-heat heat-exchange system **4010** coupled to waste heat generated by mechanical and electronic components of the power unit **4002**, an environmental heat-exchange system **4012** capable of exchanging thermal energy with the environment (e.g., the air, the ground), a spray-liquid (for foam generation) reservoir **4028**, and a spray-to-well heat-exchange unit **4030** fluidly coupled on one side to the thermal well **3908** and on the other to the spray reservoir **4028**. System **4000** may also include an optional secondary environmental heat exchange unit **4032**.

Possible modes of operation of system **4000** include an expansion mode and a compression mode. In the compression mode, a quantity of gas (e.g., air) at relatively low (e.g., atmospheric) pressure is admitted at an ambient or moderate temperature to the cylinder assembly of power unit **4002** from vent **4005** via piping **4019**. The compression in the cylinder assembly is kept substantially isothermal by introduction into the gas of a spray of foaming liquid (e.g., water with one or more additives) drawn from the spray reservoir **4028** via the spray-to-well heat-exchange unit **4030** and the cylinder heat-exchange system **4004**, thereby forming a foam in the cylinder assembly. The water in the spray reservoir **4028** is here presumed to be at a relatively low (e.g., ambient) temperature. The water sprayed through the gas undergoing (and/or prior to) compression may be returned via the cylinder heat-exchange system **4004** to the spray reservoir **4028** at a higher temperature than the water was drawn from spray reservoir **4028**, having gained thermal energy from the gas undergoing compression. The temperature of the water in spray reservoir **4028** will typically thus tend to be increased by compression cycles of the power unit **4002**. However, as water from spray reservoir **4028** passes through the spray-to-well heat exchanger **4030**, heat may be transferred from the spray fluid to the thermal well **4008**, reducing the temperature of the spray fluid. Heat added to the spray reservoir **4028** by compression cycles of the power unit **4002** may thus be transferred during subsequent compression cycles to the thermal well **4008**, allowing the temperature of the spray liquid in reservoir **4028** to be kept approximately constant.

System **4000** may realize advantages already described hereinabove for system **3900** in FIG. **39**, including temperature management of the contents of thermal well **4008** and partial conversion to work of waste heat from power unit **4002**. Additionally, in system **4000**, the thermal-storage liquid in the thermal well **4008** does not mix with the spray liquid, and the quantity of liquid in the thermal well **4008** may be significantly larger than the quantity of spray liquid. Separation of thermal-storage liquid and spray liquid in system **4000** may be advantageous because any liquid sprayed inside

the power unit **4002** is preferably maintained in a state of relatively high purity (notwithstanding the presence of one or more foaming additives) so that spray contaminants do not degrade the performance of components of the power unit **4002**. The thermal-storage liquid in system **4000** is not sprayed inside the power unit **4002** and therefore need not be maintained in as high a state of purity as the spray liquid. Maintenance of a relatively small volume of spray liquid in a state of high purity is generally less costly than maintaining the relatively large volume of the thermal well **4008** in a state of high purity, as would be preferable if the contents of the thermal well **4008** were to be used as spray liquid (as the contents of thermal well **3908** are in system **3900**). Moreover, the spray liquid may contain additives that may be omitted from the thermal-storage liquid, another opportunity for economic gain in the operation of system **4000** as compared to operation of system **3900**. Additionally, heat exchanger **4030** may be embedded in the thermal well **4008** and the contents of the thermal well **4008** may be solid (e.g., gravel), a phase-change material (e.g., paraffin wax), or some other thermal-storage material (e.g., oil, ceramics).

FIG. **41** depicts an illustrative system **4100** that features a power unit **4102** (including a cylinder assembly unit for compression and expansion of gas), cylinder heat-exchange system **4104**, a vent **4105** to draw and exhaust air from and to the environment, a storage reservoir **4106** capable of holding fluid (e.g., air and water) at high pressure (e.g., 3,000 psi), a hot thermal well **4108** (e.g., thermally insulated body of water), a cold thermal well **4113** (e.g., a second thermally insulated body of water), a waste-heat heat-exchange system **4110** coupled to waste heat generated by mechanical and electronic components of the power unit **4102**, a waste-to-well heat-exchange system **4112** coupled on one side to the hot thermal well **4108** and on the other side to the waste-heat heat-exchange system **4110**, a first environmental heat-exchange system **4132** capable of exchanging thermal energy with the environment (e.g., the air, the ground), and a second environmental heat-exchange system **4136** also capable of exchanging thermal energy with the environment.

Possible modes of operation of system **4100** include an expansion mode and a compression mode. In the compression mode, a quantity of gas (e.g., air) at relatively low (e.g., atmospheric) pressure is admitted from vent **4105** at an ambient or moderate temperature to the cylinder assembly of power unit **4102**. The compression is maintained substantially isothermal by introduction into the gas of a spray of water drawn from the cold thermal well **4113** via the cylinder heat exchange system **4104**, thereby forming a foam within the cylinder assembly. The water thus sprayed through the gas undergoing or prior to compression may be returned via the cylinder heat-exchange system **4104** to the hot thermal well **4108** at a higher temperature than the water was drawn from cold thermal well **4113**, having gained thermal energy from the gas undergoing compression. Water will therefore tend to be transferred from the cold thermal well **4113** to the hot thermal well **4108** during compression cycles of the power unit **4102**.

Similarly, in the expansion mode of system **4100**, a quantity of gas (e.g., air) at relatively high pressure (e.g., 3,000 psi) is admitted at an ambient or moderate temperature to the cylinder assembly of power unit **4102**. The expansion is maintained substantially isothermal by introduction into the gas of a spray of water drawn from the hot thermal well **4108** via the cylinder heat exchange system **4104**, thereby forming a foam within the cylinder assembly. The water thus sprayed into the gas during expansion may be returned via the cylinder heat exchange system **4104** to the cold thermal well **4113** at a

lower temperature than the water was drawn from hot thermal well **4108**, the sprayed water having imparted thermal energy to the gas undergoing expansion. Water will therefore tend to be transferred from the hot thermal well **4108** to the cold thermal well **4113** during expansion cycles of the power unit **4102**.

The environmental heat exchangers **4132** and **4136** enable the temperatures of the thermal wells **4108**, **4113** to be managed in both expansion and compression modes as already described hereinabove for the thermal wells of systems **3900** and **4000**. Heat from the waste-heat heat-exchange unit **4110** may be transferred to the hot thermal well **4108** by means of the waste-to-well heat-exchange system **4112** or to the environment by means of an additional environmental heat exchange system (not shown).

System **4100** may realize advantages already described hereinabove for systems **3900** and **4000**, including temperature management of the contents of thermal wells **4108**, **4113** and partial conversion to work of waste heat from power unit **4102**. Further, it will be apparent to persons reasonably familiar with the principles of thermodynamics that the maintenance of two thermal wells **4108**, **4113** at (preferably) distinct temperatures decreases the entropy (due to mixing of hot and cold streams) and increases the exergy (extractable work) of system **4100**, making the operation of system **4100** potentially more efficient than the operation of a system (e.g., system **4000**) having only a single thermal well. Moreover, heat may be added to the hot thermal well **4108** from any source without altering the temperature of the cold thermal well **4113**, and heat may be transferred out of the cold thermal well **4113** (e.g., by environmental heat exchanger **4136**) without altering the temperature of the hot thermal well **4108**.

FIG. **42** depicts an illustrative system **4200** that features a power unit **4202** (including a cylinder assembly unit for compression and expansion of gas), a cylinder heat-exchange system **4204**, a vent **4205** to draw and exhaust air from and to the environment, a storage reservoir **4206** capable of holding fluid (e.g., air and water) at high pressure (e.g., 3,000 psi), a hot thermal well **4208** (e.g., thermally insulated body of water), a cold thermal well **4234** (e.g., a second thermally insulated body of water), a waste-heat heat-exchange system **4210** that extracts waste heat generated by mechanical and electronic components of the power unit **4202**, a waste-to-well heat-exchange system **4212** coupled on one side to the hot thermal well **4208** and on the other to the waste-heat heat-exchange system **4210**, a spray reservoir **4228**, a spray-to-well heat-exchange unit **4230** fluidly coupled on one side to the hot thermal well **4208** and cold thermal well **4234** and on the other side to the spray reservoir **4228**, a first environmental heat-exchange system **4232** capable of exchanging thermal energy with the environment (e.g., the air, the ground), and a second environmental heat-exchange system **4236** also capable of exchanging thermal energy with the environment.

Possible modes of operation of system **4200** include an expansion mode and a compression mode. In the compression mode, a quantity of gas (e.g., air) at relatively low (e.g., atmospheric) pressure is admitted from vent **4205** at an ambient or moderate temperature to the cylinder assembly of power unit **4202**. The compression is maintained substantially isothermal by introduction into the gas of a spray of water drawn from the spray reservoir **4228** via the spray-to-well heat exchanger **4230** and the cylinder heat exchange system **4204**, thereby forming a foam within the cylinder assembly. The water in the spray reservoir **4228** is here presumed to be at a relatively low (e.g., ambient) temperature at the beginning of the compression-mode cycle. The water thus

sprayed through the gas undergoing or prior to compression may be returned via spray heat-exchange unit **4204** to the spray reservoir **4228** at a higher temperature than the water was drawn from spray reservoir **4228**, having gained thermal energy from the gas undergoing compression. The temperature of the water in spray reservoir **4228** will thus tend to be increased by compression cycles of the power unit **4202**. However, as spray liquid from spray reservoir **4228** passes through one side of the spray-to-well heat exchanger **4230** on its way to the spray heat-exchange unit **4204**, heat may be transferred from the spray liquid to thermal-well liquid passing from the cold thermal well **4234** to the hot thermal well **4208** through the other side of the spray heat-exchange unit **4230**, reducing the temperature of the spray liquid and tending to increase the temperature of the liquid in the hot thermal well **4208**. Thermal energy added to the spray reservoir **4228** by compression cycles of the power unit **4202** may thus be transferred during subsequent compression cycles to the hot thermal well **4208**, and the temperature of the spray liquid in reservoir **4228** may thus be kept substantially constant.

Similarly, in an expansion mode of system **4200**, a quantity of gas (e.g., air) at relatively high pressure (e.g., 3,000 psi) is admitted at an ambient or moderate temperature to the cylinder assembly of power unit **4202**. The expansion is maintained as substantially isothermal by introduction into the gas of a spray of water drawn from the spray reservoir **4228** via the spray-to-well heat-exchange unit **4230** and the cylinder heat exchange system **4204**, thereby forming a foam within the cylinder assembly. The water in the spray reservoir **4228** is here presumed to be at a relatively high (e.g., approximately 60° C., or even higher) temperature at the beginning of the compression-mode cycle. The water thus sprayed through the gas undergoing or prior to compression may be returned via spray heat-exchange unit **4204** to the spray reservoir **4228** at a lower temperature than the water was drawn from spray reservoir **4228**, having imparted thermal energy to the gas undergoing expansion. The temperature of the water in spray reservoir **4228** will thus tend to be decreased by compression cycles of the power unit **4202**. However, as spray liquid from spray reservoir **4228** passes through one side of the spray-to-well heat exchanger **4230**, heat may be transferred to the spray liquid from fluid passing from the hot thermal well **4208** to the cold thermal well **4234** through the other side of the spray-to-well heat exchanger **4230**, increasing the temperature of the spray liquid and decreasing the temperature of the liquid being moved from the hot thermal well **4208** to the cold thermal well **4234**. Heat removed from the spray reservoir **4228** by expansion cycles of the power unit **4202** may thus be restored during each subsequent compression cycle by extracting heat from the hot thermal well **4208**, and the temperature of the spray liquid in reservoir **4228** may be kept approximately constant.

The environmental heat exchangers **4232** and **4236** enable the temperatures of the thermal wells **4208**, **4234** to be managed in both expansion and compression modes as already described hereinabove for the thermal wells of systems **3900** and **4000**. The directions of flow through heat exchanger **4230** may be reversed when switching between compression and expansion mode via additional valving and piping (not shown) to maintain counterflow. Also, heat from the waste-heat heat-exchange unit **4210** may be transferred from the power unit **4202** to the hot thermal well **4208** by means of the waste-to-well heat-exchange system **4212**.

System **4200** may realize advantages already described hereinabove for systems **3900**, **4000**, and **4100**, including temperature management of the contents of thermal wells **4208**, **4234** and partial conversion to work of waste heat from

power unit **4202**. Further, it will be apparent to persons reasonably familiar with the principles of thermodynamics that the maintenance of two thermal wells **4208**, **4234** at (preferably) distinct temperatures decreases the entropy and increases the exergy (extractable work) of system **4200**, making the operation of system **4200** potentially more efficient than the operation of a system (e.g., system **4000**) having only a single thermal well. As in system **4100**, heat may be added to the hot thermal well **4208** from any source without altering the temperature of the cold thermal well **4234** or of the spray reservoir **4228**, and heat may be transferred out of the cold thermal well **4234** (e.g., by environmental heat exchanger **4236**) without altering the temperature of the hot thermal well **4208** or of the spray reservoir **4228**. Additionally, in system **4200**, the thermal-storage liquid in the thermal wells **4208**, **4234** does not mix with the spray liquid, and the quantity of liquid in the thermal wells **4208**, **4234** may be significantly larger than the quantity of spray liquid. Separation of thermal-storage liquid and spray liquid in system **4200** may be advantageous because any liquid sprayed inside the power unit **4202** is preferably maintained in a state of relatively high purity so that spray contaminants do not degrade the performance of components of the power unit **4202**. The thermal-storage liquid in system **4200** is not sprayed inside the power unit **4202** and therefore need not be maintained in as high a state of purity as the spray liquid. Maintenance of a relatively small volume of spray liquid in a state of high purity is generally less costly than maintaining the relatively large volume of the thermal wells **4208**, **4234** in a state of high purity. Moreover, the spray liquid may contain additives that may be omitted from the thermal-storage liquid, another opportunity for economic gain in the operation of system **4200** (as compared to, e.g., operation of system **4100**). Additionally, heat exchanger **4230** may be embedded in the thermal well **4208** and/or **4234** and the contents of the thermal well **4208** and/or **4234** may be solid (e.g., gravel), a phase-change material (e.g., paraffin wax), or some other thermal-storage material (e.g., oil, ceramics).

FIG. **43** depicts an illustrative system **4300** that features a power unit **4302** (including a cylinder assembly unit for compression and expansion of gas), a cylinder heat-exchange system **4304**, a storage reservoir **4306** capable of holding both gas and liquid at high pressure (e.g., 3,000 psi) and relatively high temperature, a waste-heat heat-exchange system **4310** coupled to waste heat generated by mechanical and electronic components of the power unit **4302**, a waste-to-well heat-exchange system **4312** coupled on one side to the high-pressure fluid reservoir **4306** and on the other side to the waste-heat heat-exchange system **4310**, a cold thermal well **4334** including or consisting essentially of, e.g., a body of water, a first environmental heat-exchange system **4332** capable of exchanging thermal energy with the environment (e.g., the ground), and a second environmental heat-exchange system **4338** also capable of exchanging thermal energy with the environment. The high-temperature, high-pressure reservoir **4306** combines functions of a high-pressure gas store with functions of a hot thermal well and may be a single unit (e.g., insulated pressure tanks, insulated pipelines, underground geologic formation such as salt domes).

Possible modes of operation of system **4300** include an expansion mode and a compression mode. In the compression mode, a quantity of gas (e.g., air) at relatively low (e.g., atmospheric) pressure is admitted from vent **4305** at an ambient or moderate temperature to the cylinder assembly of power unit **4302**. The compression of the gas is maintained substantially isothermal by introduction into the gas of a spray of water drawn from the cold thermal well **4334** via the

cylinder heat exchange system **4304**, thereby forming a foam within the cylinder assembly. The water thus sprayed into the gas undergoing or prior to compression may be directed, along with the compressed gas, via the cylinder heat-exchange system **4304** to the high-temperature, high-pressure reservoir **4306** at a higher pressure and temperature than the water was drawn from cold thermal well **4334**, having gained thermal energy from the gas undergoing compression. Water will therefore tend to be transferred from the cold thermal well **4334** to the high-temperature, high-pressure reservoir **4306** during compression cycles of the power unit **4302**.

Similarly, in the expansion mode of system **4300**, a quantity of gas (e.g., air) at relatively high pressure (e.g., 3,000 psi) and relatively high temperature is transferred from the high-temperature, high-pressure reservoir **4306** to the cylinder assembly of power unit **4302**. As the cylinder assembly expands the gas, the temperature of the gas tends to decrease; the degree of this decrease is limited by the foam formation with the gas, and the expansion is preferably maintained substantially isothermal. In the expansion mode of system **4300**, the spray liquid includes or consists essentially of water (e.g., with one or more foaming additives) drawn from the high-temperature, high-pressure reservoir **4306** via the cylinder heat-exchange system **4304**. At the end of an expansion cycle, this liquid will tend to be at a lower temperature and pressure than when sprayed into the gas undergoing or prior to expansion, the liquid having imparted thermal energy to the gas undergoing expansion, and may be directed via the cylinder heat-exchange system **4304** to the cold thermal well **4334**. Expanded gas at relatively low temperature and pressure may be vented via vent **4305** to the environment from power unit **4302**. Liquid will thus tend to be transferred from the high-temperature, high-pressure reservoir **4306** to the cold thermal well **4334** during expansion cycles of the power unit **4302**.

The environmental heat exchangers **4332** and **4338** enable the temperatures of the cold thermal well **4334** and the high-temperature, high-pressure reservoir **4306** to be managed in both expansion and compression modes as already described hereinabove for thermal wells communicating with environmental heat exchangers. Heat from the waste-heat heat-exchange unit **4310** may be transferred to the high-temperature, high-pressure reservoir **4306** via the waste-to-well heat-exchanger **4312**. In other embodiments, some or all of these heat exchangers are eliminated.

System **4300** may realize advantages already described hereinabove for systems **3900**, **4000**, **4100**, and **4200**, including temperature management of the contents of the thermal well **4334** and of the high-temperature, high-pressure reservoir **4306**, and partial conversion to work of waste heat from power unit **4302**. As with systems **4100** and **4200**, it will be apparent to persons reasonably familiar with the principles of thermodynamics that the maintenance of two bodies of liquid (i.e., in the cold thermal well **4334** and in the high-temperature, high-pressure reservoir **4306**) at (preferably) distinct temperatures decreases the entropy and increases the exergy (extractable work) of system **4300**, making the operation of system **4300** potentially more efficient than the operation of a system (e.g., system **4000**) having only a single thermal well. Moreover, due to the elevation of the boiling point of water with increasing pressure, system **4300** offers the additional advantage that the upper (non-vaporizing) temperature limit of water stored in the high-temperature, high-pressure reservoir **4306** is higher than the upper temperature limit of water stored in a non-pressurized hot thermal well such as hot thermal well **4208** of system **4200**. It will be apparent to persons reasonably familiar with the principles of thermody-

namics that the exergy of a system increases when the temperature difference between two bodies of liquid in the system is increased; thus, for example, the exergy of the bodies of hot and cold liquid of system **4300** may be higher than the exergy of similar quantities of hot and cold liquid in system **4200**, because the temperature difference between the bodies of hot and cold liquid in system **4300** may be, in some operating conditions of system **4300**, larger than the temperature difference between the bodies of hot and cold liquid of system **4200**.

FIG. **44** depicts an illustrative system **4400** that features a power unit **4402** (including a cylinder assembly unit for compression and expansion of gas) that may include two or more different cylinder assemblies (that may have different diameters), each compressing or expanding gas over a different range of pressures (i.e., a two or more stage compressor and expander power unit); a cylinder heat-exchange system **4404**; a storage reservoir **4406** capable of holding both gas and liquid at high pressure (e.g., 3,000 psi) and relatively high temperature; a hot thermal well **4408** including or consisting essentially of an insulated body of water at low pressure (e.g., atmospheric pressure); a cold thermal well **4434** also including or consisting essentially of a body of water; a waste-heat heat-exchange system **4410** coupled to waste heat generated by mechanical and electronic components of the power unit **4402**; a waste-to-well heat-exchange system **4412** coupled on one side to the hot thermal well **4408** and on the other side to the waste-heat heat-exchange system **4410**; a first environmental heat-exchange system **4432** capable of exchanging thermal energy with the environment (e.g., the air, the ground); and a second environmental heat-exchange system **4436** also capable of exchanging thermal energy with the environment (e.g., the air, the ground). The high-temperature, high-pressure reservoir **4406** combines functions of a high-pressure gas store with functions of a hot thermal well.

Possible modes of operation of system **4400** include an expansion mode and a compression mode. In the compression mode, a quantity of gas (e.g., air) at relatively low (e.g., atmospheric) pressure is admitted via vent **4405** at an ambient or moderate temperature to the cylinder assembly of power unit **4402**. As the cylinder assembly of power unit **4402** compresses the gas, the compression is maintained substantially isothermal by introduction into the gas of a spray of water drawn from the cold thermal well **4434** via the cylinder heat-exchange system **4404**, thereby forming a foam within the cylinder assembly. The water thus sprayed into the gas undergoing or prior to compression may be directed, along with the compressed gas, via the cylinder heat-exchange system **4404** to the high-temperature, high-pressure reservoir **4406** at a higher pressure and temperature than the water was drawn from cold thermal well **4434**, having gained thermal energy from the gas undergoing compression. Some or all spray water may also be directed to the low-pressure hot thermal well **4408** via the cylinder heat-exchange system **4404**. Water will therefore tend to be transferred from the cold thermal well **4434** to the high-temperature, high-pressure reservoir **4406** and/or low pressure hot thermal well **4408** during compression cycles of the power unit **4402**.

Similarly, in the expansion mode of system **4400**, a quantity of gas (e.g., air) at relatively high pressure (e.g., 3,000 psi) and relatively high temperature is transferred from the high-temperature, high-pressure reservoir **4406** to the cylinder assembly of power unit **4402**. As the cylinder assembly expands the gas, the expansion is maintained substantially isothermal by introduction into the gas of a spray of water drawn from the high-temperature, high-pressure reservoir **4406** via the cylinder heat-exchange system **4404**, thereby

forming a foam within the cylinder assembly. As the gas is expanded to lower pressures, the spray may be partially or even fully formed from water drawn from the low-pressure hot thermal well **4408**. The water sprayed through the gas undergoing or prior to expansion may be directed via the cylinder heat-exchange system **4404** to the cold thermal well **4434** at a relatively low pressure and temperature, having imparted thermal energy to the gas undergoing expansion. Expanded gas may be vented to the environment via vent **4405** from power unit **4402**. Water will thus tend to be transferred from the high-temperature, high-pressure reservoir **4406** and/or low-pressure hot thermal well **4408** to the cold thermal well **4434** during expansion cycles of the power unit **4402**.

The environmental heat exchangers **4436** and **4432** enable the temperatures of the cold thermal well **4434** and low-pressure hot thermal well **4408** to be managed in both expansion and compression modes, as already described hereinabove for the thermal wells of systems **3900**, **4000**, **4100**, **4200**, and **4300**. Heat from the waste-heat heat-exchange unit **4410** may be transferred to the low-pressure hot thermal well **4408** via the waste-to-well heat-exchange system **4412**.

System **4400** may realize advantages already described hereinabove for systems **3900**, **4000**, **4100**, **4200**, and **4300**, including temperature management of the contents of the thermal wells **4408**, **4434** and partial conversion to work of waste heat from power unit **4402**. As with systems **4100**, **4200**, and **4300**, it will be apparent to persons reasonably familiar with the principles of thermodynamics that the maintenance of two or more bodies of liquid (i.e., in the cold thermal well **4434**, in the hot thermal well **4408**, and in the high-temperature, high-pressure reservoir **4406**) at (preferably) distinct temperatures decreases the entropy and increases the exergy (extractable work) of system **4400**, making the operation of system **4400** potentially more efficient than the operation of a system (e.g., system **400**) having only a single thermal well. Due to the elevation of the boiling point of water with increasing pressure, system **4400** offers (as does system **4300** in FIG. **43**) the advantage that the upper (non-vaporizing) temperature limit of water stored in the high-temperature, high-pressure reservoir **4406** is higher than the upper temperature limit of water stored in a non-pressurized hot thermal well such as hot thermal well **4408**. Moreover, system **4400** offers the additional advantage that waste heat may be transferred from the power unit **4402** to the low-pressure hot thermal well **4408** using a low-pressure waste-to-well heat exchanger **4412**, rather than a high-pressure waste-to-well heat exchanger **4312** as in system **4300**. A low-pressure waste-to-well heat exchanger **4412** will tend to be less costly than a high-pressure waste-to-well heat exchanger.

Where power unit **4402** includes two different diameter cylinders (not depicted), one (C1) compressing gas over a first, lower pressure range, and the second (C2) compressing gas over a second, higher pressure range, advantages (e.g., increased overall efficiency of system **4400**) may be realized in a compression mode of operation of system **4400** by maintaining the low-pressure hot thermal well **4408** at a temperature (and optionally also at the mid-pressure) achieved at the end of the substantially isothermal compression in C1. That is, low-pressure hot thermal well **4408** may be maintained at a lower temperature than the contents of the high-pressure, high-temperature store **4406**. This allows the quantity of spray introduced during or prior to compressions to be independently adjusted in C1 and C2 as the pressure in the store **4406** increases over sequential compression cycles. Further, if low-grade waste heat (e.g., from a thermal power plant; not

depicted) is available, it may be transferred via a heat exchanger to the low-pressure, lower-temperature hot thermal well, increasing effective overall system efficiency. The temperature of the low-pressure hot thermal well **4408** operating at a midpoint of a multi-stage compression/expansion process may be optimal for usage of waste heat at available temperatures (e.g., approximately 40° C., 60° C., or similar), whereas the high-pressure high temperature reservoir **4406** may be maintained at substantially higher temperature (e.g., approximately 80° C., 120° C. or similar) that may not allow usage of typical waste heat temperatures. By operating the multi-stage compression/expansion process at higher temperatures, reduced water spray volume may be used, increasing storage volume and system efficiency (e.g., reducing valve losses for passing two-phase flow). It will be apparent to persons reasonably familiar with thermodynamics that similar advantages may be realized in an expansion mode of system **4400**.

FIG. **45** depicts an illustrative embodiment of the invention in which one or more batteries **4508** and/or other high-power, short-duration energy storage devices (e.g., an energy storage device with less than 1 hour of storage, e.g., 15 minutes) are connected in parallel with a compressed-gas energy storage system **4502** to generate power for usage (e.g., power grid delivery **4500**). The energy storage system **4502** may resemble illustrative storage systems depicted elsewhere herein. The battery **4508** is configured to provide stored energy during periods of low power demand (e.g., less than 500 kW), while the compressed-gas energy storage system **4502** is configured to provide stored energy during periods of increased power-demand fluctuations (e.g., above 500 kW). In one example, the operator of a power generation facility that includes a solar power generation and the energy storage system depicted in FIG. **45** receives payment to maintain a constant power level of 2,000 kW. At an instant, solar power generation drops from 2,000 kW to 1,900 kW as a cloud shadows part of the array. Measured power output may be maintained at the required constant power level by requiring that the battery **4508** discharge at a rate of 0 to 100 kW as the cloud shadows the array. At another instant, a storm passes the area and the solar power generation drops to 1000 kW to 500 kW for an extended period of time. Measured power output may be maintained at the constant power level by requiring that the compressed-gas energy storage system **4502** discharges at a rate of 1000 to 1500 kW as the cloud shadows the array. Upon demand for increased power (e.g., above 500 kW), stored energy in the form of compressed gas in storage reservoir **4504** undergoes expansion in the compressed-gas energy storage system **4502** to generate power for usage (e.g., power grid delivery **4500**). Any excess thermal energy from the battery **4508** may be recoverable through a heat-exchange unit **4506**. The recovered thermal energy from the battery **4508** may be used in the heat-exchange subsystem of the compressed-gas storage reservoir **4504** (or other pressurized storage) to preheat the stored compressed gas and/or to heat the heat-exchange fluid and gas during expansion, increasing the work done by a given volume of pressurized gas, and so improving system efficiency and/or performance. For example, the recovered thermal energy may be utilized to thermally condition stored compressed gas and/or gas undergoing expansion and/or compression as described in the '960 application.

The response time of the high-power, short-duration energy storage device **4508** may be optimized to respond within microseconds to changing power levels and demand. The rate of the power response may be limited to approxi-

mately one millisecond based on the data acquisition rate of the control system, but can readily be configured to respond in less than one second.

FIG. 46 depicts an integrated system 4600 in which a compressed-gas energy storage system 4610 including one or more storage reservoirs with stored compressed gas (not depicted) is connected to an electric motor 4612. During periods of higher power demand fluctuations (e.g., above 500 kW) the compressed-gas energy storage system 4610 is discharged to provide motor 4612 with stored energy. The motor 4612 converts the stored energy into electric power. In some embodiments, for a synchronous electric machine running at synchronous speeds (e.g., 1800 RPM), no power electronics are required. In other embodiments, for a variable-speed electric machine, as illustrated in FIG. 46, electric power is sent to load-side power electronics 4608 that convert the electric current from AC to DC before sending the power through a common DC bus line 4606. Electric power may then be sent to line-side power electronics 4604 (DC to AC) for usage (e.g., by power grid 4602). During periods of low power-demand fluctuations (e.g., less than 500 kW) one or more batteries 4650, and/or other high-power, short-duration energy storage devices (e.g., flywheels and/or ultracapacitors), are discharged to provide power for usage. For a DC device such as a battery, the electrical output may be connected to the same line-side power electronics. For example, electric power may be discharged from the battery 4650 through the common DC bus line 4606 to line-side power electronics 4604 before being sent for usage (e.g., power grid 4602).

In various embodiments, the battery 4650 is connected to a cooling system featuring a heat exchanger 4648, a radiator 4634, a battery inlet pipe 4632 with a pump 4630, a fluid control valve 4628, and a battery return pipe 4638 with a fluid control valve 4636. Similarly, the compressed-gas energy storage system 4610 is connected to a heat-exchange subsystem featuring a heat exchanger 4614, a radiator 4620, an inlet pipe 4622 with a pump 4616, a fluid control valve 4618, and a return pipe 4626 with a fluid control valve 4624. Radiator 4620 may alternatively or additionally include or consist essentially of a thermal well. The battery inlet pipe 4632 may be connected to the inlet pipe 4622 via pipe 4642. Likewise, the battery return pipe 4638 may be connected to the return pipe 4626 via pipe 4640. Pipes 4642 and 4640 may contain fluid control valves 4644 and 4646 respectively.

In a state of operation in which the compressed-gas energy storage system 4610 is discharged to provide power to the grid (e.g., demand exceeds supply by more than 500 kW), valve 4628 is closed and valve 4644 is opened to allow heat-transfer fluid from battery inlet pipe 4632 to be sent to inlet pipe 4622 via pipe 4642. Heat-transfer fluid is circulated via pump 4616 through heat exchanger 4614, return pipe 4626, and radiator 4620. During circulation in the heat-exchange subsystem, waste heat from the battery 4650 cooling system is used to heat the compressed gas prior to and/or during expansion in the compressed-gas storage system 4610 (e.g., by formation of foam between the gas and the heated heat-transfer fluid). The storage system 4610 power density is thereby increased and/or overall efficiency is improved.

In a different state of operation in which the battery 4650 is discharged to provide power to the grid (e.g., demand exceeds supply by less than 500 kW), valve 4644 and 4646 are closed and heat exchanger 4648, battery inlet pipe 4622, pump 4630, radiator 4634, and battery return pipe 4638, form a closed-loop battery-cooling system independent of the heat-exchange subsystem of the compressed-gas energy storage system 4610. In other modes of operation, waste heat from the

battery 4650 may be directed to the thermal well 4620 where the thermal energy may be stored to be used at a later time during operation of the compressed-gas storage system 4610.

FIG. 47 is an illustrative plot of electricity supply and demand for an exemplary 24-hour period. The supply curve is based on a simulation of a source of constant-baseload power and an exemplary solar installation, whereas electricity demand is based on simulated data from an exemplary day. Electricity demand is typically lower during the evening and higher during the day. In the illustrative plot shown in FIG. 47, demand exceeds supply from approximately hour 15 (900 minutes) to hour 24 (1440 minutes).

FIG. 48 is an illustrative plot of the effect of a combined high-power, short-duration energy storage device and compressed-gas energy storage system on electricity supply and demand for a given 24-hour period. In the illustrative plot shown in FIG. 48, at minute zero demand exceeded supply by around 200 kW. The high-power, short-duration energy storage device is configured to discharge power to meet excess demand values less than 500 kW. Therefore, the high-power, short-duration energy storage device is shown in a discharging state from minute zero to minute 60 where the range of excess demand is 200 kW to 0 kW respectively. From minute 60 to minute 120, supply exceeds demand by less than 500 kW. Therefore, the high-power energy-storage device is shown in a charging state (depicted as negative values in FIG. 48) until the maximum power is reached at -500 kW.

The compressed-gas energy storage system is configured to discharge power to meet excess demand values above 500 kW. (In one embodiment, multiple 1 MW systems act as a larger system to address any power above 500 kW by employing multiple power units, e.g., two 1 MW systems may address power levels between 500 and 2000 kW). In the illustrative plot shown in FIG. 47, when supply exceeds demand in the range of 500 kW or more, the excess power is used to charge the compressed-gas energy storage system (i.e., store energy in the form of compressed gas). Therefore, the compressed-gas storage system is shown in a charging state from minute 120 to minute 540 when the excess power falls below 500 kW (depicted as negative values in FIG. 48). When the excess power falls below 500 kW, the high-power energy-storage device takes over and is therefore shown in a charging state (depicted as negative values in FIG. 48) from minute 540 to minute 600.

During the period ranging from minute 600 to minute 900, supply exceeds demand by varying values less than 500 kW; therefore, the high-power, short-duration energy storage device is shown in a charging state when values are less than 500 kW. Additionally, to maintain the state-of-charge of the high-power, short-duration energy storage device within a certain range, the compressed-gas energy storage device is shown in a charging state at -500 kW whenever the state-of-charge of the high power, short duration energy storage device exceeds a set maximum value (e.g., 900 kWh, as shown in FIG. 48) or in a discharging state at 500 kW whenever the state-of-charge of the high-power, short-duration energy storage device drops below a set minimum value (e.g., 100 kWh, as shown in FIG. 48). When demand exceeds supply from minute 900 to minute 1440, the high-power, short-duration energy storage device is discharged for the first 500 kW demand period. Afterwards, the compressed-gas energy storage system takes over and discharges power for the period where demand exceeds supply by 500 kW or more.

FIG. 49 is an illustrative plot of the state-of-charge for the combined high-power, short-duration energy storage device and compressed-gas energy storage system for the given 24-hour period illustrated in FIGS. 47 and 48. In this simu-

lated scenario, a 2 MW compressed-gas energy storage system with 10 MWh of storage capacity operates in parallel with a 500 kW short-duration energy-storage device with storage capacity up to 1 MWh. Whenever the state-of-charge of the high-power, short-duration energy storage device exceeds 900 kWh (90% of maximum capacity), a portion of the stored energy is discharged to either the grid or to the compressed-gas energy storage system. Whenever the state-of-charge of the high-power, short-duration energy storage device drops below 100 kWh (10% of maximum capacity), the high-power, short-duration energy storage device is recharged via either the grid or the compressed-gas energy storage system. In this manner, the state-of-charge of the high-power, short-duration energy storage device may be maintained within an optimal range while the compressed gas energy storage system provides bulk energy storage and recovery.

Embodiments of the invention may be applied in a wide variety of settings where generation assets are connected to a grid whose loads may vary over time (e.g., with time of day), and where the power output of some generation assets may vary (e.g., with wind conditions, cloud conditions, mechanical breakdowns, transmission line failures, closures for scheduled refueling of a reactor core). Some of these applications are discussed further below.

Embodiments of the invention may also be applied in a variety of “behind the meter” settings, i.e., where a power user’s access to power, or cost of power, varies over time (e.g., with time of day) and it is advantageous for the user to buy and store energy using a compressed-air energy storage system at some times and to generate power using the storage system at other times.

FIG. 50 is a conceptual drawing of an illustrative power generation and consumption network or grid 5000 of conventional baseload power plants 5002, very-high-voltage transmission lines 5004, transmission substations 5006, regional high-voltage transmission lines 5008, large power loads 5010 with their own step-down transformers 5012, centralized renewable power generators 5014 (e.g., solar panels, wind turbines) connected by transmission lines 5015 to the network at, e.g., substations 5006, area transmission lines 5018, distribution substations 5020, local distribution lines 5022, small-scale power loads 5024 (e.g., homes), and isothermal compressed-air storage (ICAES™) systems 5026, 5028, 5030, 5032, 5034 that may exchange energy with other components of the network 5000 at a variety of points (as indicated by double-headed arrows). Such ICAES systems may include or consist essentially of any one or more of the illustrative energy storage systems described elsewhere herein, including those which employ foam-based heat transfer to increase thermal efficiency and speed (hence power density) of operation of cylinder assemblies.

Single representations of power lines, substations, loads, and ICAES systems stand, in the conceptual drawing of FIG. 50, for a possible multiplicity of complexly interconnected units of the same types: that is, network 5000 is a simplified representation of components of a class of real-world networks (power grids) that may be far more complex than network 5000 as represented in FIG. 50 and that may contain components (e.g., peak generators fired by natural gas) not represented in FIG. 50. Nevertheless, relationships indicated by FIG. 50 may accurately represent relationships between components in more complex real-world networks.

Applications of ICAES in network 5000 may be classed into at least four major categories, (1) conventional power

generation, (2) renewable power generation and cogeneration, (3) transmission and network services, and (4) end user support.

Conventional Power Generation

Where ICAES 5026 is connected to the low-voltage side of the step-up transformer system at a conventional power plant 5002, several functions may be performed by the ICAES 5026. The operation of the ICAES 5026 and of its electrical connection with the low-voltage (local) electrical system of the power plant 5002 is governed by a control system (not depicted) including or consisting essentially of automatic controls (e.g., digital computers), human controllers, or both. Signals derived from a variety of sources may be directed to the control system of ICAES 5026. Such signals include measured, electronically coded, and remotely transmitted (reported) information describing the availability and output of other generation sources (both conventional 5002 and renewable 5014) attached to the network 500, the magnitude and location of loads (e.g., 5010, 5024), recent changes in the availability and output of generators of all types throughout network 5000 (including generators not represented in FIG. 50, e.g., rooftop solar panels co-located with loads 5010, 5024 in a geographically distributed manner), recent changes in magnitudes of loads 5010, 5024, quantitative estimates of energy stored in ICAES systems and other storage systems (e.g., hydroelectric storage reservoirs), quantitative forecasts (from, e.g., the National Weather Service) of temperatures and other aspects of weather in areas where loads are located, forecasts of renewable (e.g., hydroelectric) generation capacity based on recent weather events (e.g., precipitation) over geographically relevant areas, instantaneous market prices for exchange of power between network 5000 and other networks, impending physical challenges to the network 5000 (e.g., storms), operational status and loading of transmission facilities 5004, etc.

The controller bases decisions about the operation of ICAES 5026 upon the signals it receives. For example, energy from the conventional generator 5002 (or from elsewhere in the network 5000 via transmission lines 5004) may be stored in ICAES 5026 at a time when there is a surplus of generating capacity relative to load (e.g., at night). At such times as there is a shortage of generating capacity relative to demand (e.g., during peak demand near mid-day), or when more-expensive generators (e.g., gas-fired peak generators) would necessarily be called into action to meet demand, energy may be retrieved from ICAES 5026 and transmitted to loads through network 5000. Such electric energy time-shifting may decrease energy costs in network 5000 by obviating or mitigating the operation of more-expensive peak generators.

Alternatively or additionally, the ICAES 5026 associated with a particular generator may act as reserve capacity from which energy may be extracted when one or more other generators (not depicted) in network 5000 become unavailable (e.g., due to mechanical failure or scheduled refueling) or must operate at reduced capacity (e.g., due to low water levels at a hydroelectric facility).

Alternatively or additionally, energy may be extracted from ICAES 5026 in response to increases in loads 5024, 5010 throughout network 5000. Such increases in load may be routine (e.g., the daily peak in demand) or unusual (e.g., due to statistical fluctuations in large numbers of smaller loads, or due to a large user 5010 coming on line). Such applications may generally be termed a form of “load following.”

Renewable Power Generation

ICAES 5028, co-located with renewable generators 5014 of significant size (i.e., wind farms or other non-distributed

generators), can increase the value of the power provided by such generators by reducing the intermittency of their power output as seen by a purchaser of that output through the transmission lines **5015**. That is, during periods when demand for power is low or generation by the renewable generator **5014** is relatively high, some or all energy produced by the renewable generator **5014** may be stored in ICAES **5028**. At periods when demand (and/or price) for power is higher or when generation by the renewable generator **5014** is relatively low, energy may be retrieved from ICAES **5028** and transmitted to the network **5000** via power lines **5015**. Retrieval of energy from ICAES **5028** on a regular schedule is generally termed energy time-shifting; use of ICAES **5028** to mitigate the output intermittency of the generator **5014** is generally termed firming of the generator. In many real-world networks, the per-unit value of energy from a given generator is partly conditioned on the on-demand availability of that energy: since the availability of a unit of energy from a renewable generator **5014** is increased by the partial buffering of the output of generator **5014** through ICAES **5028**, the use of ICAES **5028** to firm the output of renewable generator **5014** may be advantageous.

Transmission and Network Services

By means of appropriate electronic control signals, the controller of ICAES **5026** may simultaneously or independently control ICAES units **5026**, **5028**, **5030**, **5032**, **5034** and other energy-storage systems that may be located throughout the network **5000**. ICAES units may be attached to network **5000** at some or all of the points indicated in FIG. **50**, and/or at additional points not depicted in FIG. **50**. Simultaneous remote-control operation of ICAES units and other storage units throughout network **5000** may provide a variety of transmission and network services, for example, enable the lowest-cost matching of generators (including storage units) to loads throughout the network at all times, or, if total load should exceed the generating capacity of network **5000**, the minimization of economic and other losses due to supply-demand mismatch. Short-term fluctuations in load **5024**, **5010**, which may cause voltages on transmission lines to drop throughout portions of network **5000**, may be mitigated by the rapid activation of ICAES units (e.g., units **5034**, **5030**) to add energy to network **5000**. Such activation of rapid-response generators may generally be termed voltage support.

At times when some transmission lines (e.g., **5018**) are heavily loaded, i.e., are carrying as much, or nearly as much, power as they are safely capable of carrying, yet demand increases (e.g., at load **5024**), the controller may cause energy to be extracted from storage (e.g., ICAES **5034**) in order to obviate the need for the transmission of additional power through the heavily loaded transmission line. Such transmission support may allow scheduled upgrades of the capacity of certain transmission lines in network **5000** to be deferred. Relief of temporary transmission congestion may also be afforded by such means.

Power to individual substations (e.g., **5006**, **5020**) may be supplied by ICAES units attached thereto (e.g., **5030**, **5034**) during widespread power outages, supporting on-site operations and thus speedier network recovery.

End User

Energy stored at ICAES units distributed in the grid (e.g., **5032**, **5034**) may be used to temporarily supply power to local loads when long-distance transmission lines (e.g., **5004**, **5008**) are disabled or overloaded, or when primary generators (e.g., **5002**) are disabled, or in other outage conditions. Such powering of a local network of loads is generally termed islanding. Islanding of residential neighborhoods, industrial

parks, large buildings, military bases, large single users (e.g., **5010**), and other local loads may be enabled or supported by ICAES units.

Time-of-use management for single large users **5010** may be enabled by ICAES **5032**. That is, energy may be purchased by the user **5010** from the grid when prices are lower (e.g., at night), stored in ICAES **5032**, then extracted from storage when prices are higher (e.g., during the day). Additionally or alternatively, ICAES **5032** may assure power quality is high to the user **5010**, protecting against economic losses (e.g., data losses) entailed by fluctuations in quality or availability of power from the network **5000**. Additionally or alternatively, storage of energy in and retrieval of energy from ICAES **5032** may enable user **5010** to shape its demand profile in a way that manages demand charges and time-of-use.

All these applications of the invention, as well as others not explicitly described herein, are contemplated.

Generally, the systems described herein may be operated in both an expansion mode and in the reverse compression mode as part of a full-cycle energy storage system with high efficiency. For example, the systems may be operated as both compressor and expander, storing electricity in the form of the potential energy of compressed gas and producing electricity from the potential energy of compressed gas. Alternatively, the systems may be operated independently as compressors or expanders.

Embodiments of the invention may, during operation, convert energy stored in the form of compressed gas and/or recovered from the expansion of compressed gas into gravitational potential energy, e.g., of a raised mass, as described in U.S. patent application Ser. No. 13/221,563, filed Aug. 30, 2011, the entire disclosure of which is incorporated herein by reference.

Systems in accordance with embodiments of the invention may utilize a substantially incompressible fluid and/or one or more pressurized reservoirs to minimize or eliminate dead space within one or more cylinder assemblies and/or other components, as described in the '914 application and in U.S. patent application Ser. No. 13/080,910, filed Apr. 6, 2011, the entire disclosure of which is incorporated herein by reference. As also described in these applications, embodiments of the invention may incorporate mechanisms for substantially preventing the flow of compressible fluid (e.g., gas or foam) from the cylinder assembly into the heat-exchange components (e.g., heat exchangers, pumps, and/or pipes connected thereto and/or between the cylinder assembly and such components), and may thereby substantially prevent formation of dead space in the heat-exchange components. For example, various embodiments incorporate one or more check valves on the upstream side of one or more of the nozzles in the spray-generating or foam-generating mechanism introducing heat-exchange fluid into a cylinder assembly.

The terms and expressions employed herein are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding any equivalents of the features shown and described or portions thereof, but it is recognized that various modifications are possible within the scope of the invention claimed.

What is claimed is:

1. A method of recovering energy, the method comprising: transferring a first foam to a first cylinder assembly, the first foam having a first foam expansion ratio; expanding the first foam in the first cylinder assembly, thereby recovering energy therefrom; thereafter, transferring a second foam to a second cylinder assembly different from the first cylinder assembly, the

115

- second foam having a second foam expansion ratio larger than the first foam expansion ratio; and expanding the second foam in the second cylinder assembly, thereby recovering energy therefrom.
2. The method of claim 1, further comprising exhausting the expanded second foam from the second cylinder assembly.
3. The method of claim 2, wherein at least a gaseous portion of the expanded second foam is exhausted to ambient atmosphere.
4. The method of claim 1, wherein (i) after expanding the first foam, the expanded first foam is exhausted from the first cylinder assembly and (ii) the second foam comprises at least a portion of the expanded first foam.
5. The method of claim 4, wherein the expanded first foam is exhausted into a foam vessel, and further comprising circulating heat-transfer liquid in the foam vessel to form the second foam.
6. The method of claim 1, further comprising:
after expanding the first foam, separating at least a portion of the expanded first foam into gaseous and liquid components; and
forming the second foam by introducing heat-transfer liquid into the gaseous component of the expanded first foam.
7. The method of claim 6, wherein the at least a portion of the expanded first foam is separated via at least one of mechanical separation or application of ultrasound energy.
8. The method of claim 7, wherein the at least a portion of the expanded first foam is separated via mechanical separation by at least one of a blade, a shear, a baffle, or a centrifuge.
9. The method of claim 6, further comprising storing the liquid component of the expanded first foam.
10. The method of claim 1, wherein a mass ratio of the first foam is approximately equal to a mass ratio of the second foam.
11. The method of claim 1, further comprising altering at least one of an average cell size or a uniformity of cell size of the first foam before expanding the first foam.
12. The method of claim 1, further comprising altering at least one of an average cell size or a uniformity of cell size of the second foam before expanding the second foam.
13. The method of claim 1, wherein a foam mass ratio of the first foam is selected from the range of 1 to 4.
14. The method of claim 1, wherein a foam mass ratio of the second foam is selected from the range of 1 to 4.
15. The method of claim 1, wherein the first foam is expanded substantially isothermally and the second foam is expanded substantially isothermally.

116

16. The method of claim 1, further comprising forming the first foam by mingling heat-transfer liquid and compressed gas.
17. The method of claim 16, further comprising controlling a void fraction of the first foam by controlling a rate of transfer of heat-transfer liquid into the compressed gas.
18. The method of claim 17, further comprising sensing at least one of a pressure or a temperature within the first cylinder assembly, wherein the rate of transfer is controlled in response thereto.
19. The method of claim 1, wherein expanding the first foam and expanding the second foam both drive a crankshaft mechanically coupled to the first and second cylinder assemblies.
20. The method of claim 1, further comprising, after expanding the second foam, separating at least a portion of the expanded second foam into gaseous and liquid components.
21. The method of claim 20, wherein the at least a portion of the expanded second foam is separated via at least one of mechanical separation or application of ultrasound energy.
22. The method of claim 20, wherein the at least a portion of the expanded second foam is separated via mechanical separation by at least one of a blade, a shear, a baffle, or a centrifuge.
23. The method of claim 20, further comprising storing the liquid component of the expanded second foam.
24. The method of claim 20, further comprising exhausting the gaseous component of the expanded second foam to ambient atmosphere.
25. The method of claim 19, wherein driving the crankshaft produces electrical current via an electric generator mechanically coupled to the crankshaft.
26. The method of claim 25, further comprising converting at least a portion of the electrical current from alternating-current to direct-current.
27. The method of claim 16, wherein the heat-transfer liquid comprises water containing at least one foaming additive.
28. The method of claim 27, wherein the at least one foaming additive comprises at least one of a mineral oil, a glycol, a sulfonate, a fluorosurfactant, or an ethanolamine.
29. The method of claim 16, wherein forming the first foam comprises spraying the heat-transfer fluid on a screen.
30. The method of claim 1, wherein (i) the second foam comprises water containing at least one foaming additive, and (ii) the at least one foaming additive comprises at least one of a mineral oil, a glycol, a sulfonate, a fluorosurfactant, or an ethanolamine.

* * * * *